



■ Features :

- AC input 180 ~ 264VAC
- AC input active surge current limiting
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Forced air cooling by built-in DC ball bearing fan
- High power density 7.8w/inch³
- With DC OK signal output
- Built-in remote ON-OFF control
- Built-in remote sense function
- UL / CUL approved
- Low cost
- 2 years warranty

User's Manual




SPECIFICATION

MODEL	SE-1500-5	SE-1500-12	SE-1500-15	SE-1500-24	SE-1500-27	SE-1500-48		
OUTPUT	DC VOLTAGE 5V	12V	15V	24V	27V	48V		
	RATED CURRENT 300A	125A	100A	62.5A	55.6A	31.3A		
	CURRENT RANGE 0 ~ 300A	0 ~ 125A	0 ~ 100A	0 ~ 62.5A	0 ~ 55.6A	0 ~ 31.3A		
	RATED POWER 1500W	1500W	1500W	1500W	1501.2W	1502.4W		
	RIPPLE & NOISE (max.) Note.2 150mVp-p	150mVp-p	150mVp-p	150mVp-p	150mVp-p	150mVp-p		
	VOLTAGE ADJ. RANGE 3.3 ~ 5.5V	10.8 ~ 13.5V	13.5 ~ 16.5V	21.6 ~ 26.4V	25 ~ 30V	43.2 ~ 56V		
	VOLTAGE TOLERANCE Note.3 ±2.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%		
	LINE REGULATION ±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%		
	LOAD REGULATION ±2.0%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%		
	SETUP, RISE TIME 150ms, 12ms / 230VAC at full load							
INPUT	HOLD UP TIME (Typ.) 26ms / 230VAC at full load							
	VOLTAGE RANGE 180 ~ 264VAC	254 ~ 370VDC						
	FREQUENCY RANGE 47 ~ 63Hz							
	EFFICIENCY (Typ.) 81%	85%	85%	87%	88%	89%		
	AC CURRENT (Typ.) 17.5A / 230VAC							
	INRUSH CURRENT (Typ.) 60A / 230VAC							
PROTECTION	LEAKAGE CURRENT <3.5mA / 240VAC							
	OVERLOAD 105 ~ 125% rated output power							
	Protection type : Shut down o/p voltage, re-power on to recover							
	OVER VOLTAGE 5.75 ~ 6.75V	14.5 ~ 16.2V	18 ~ 21V	27.6 ~ 32.4V	31 ~ 35V	57.6 ~ 67.2V		
FUNCTION	OVER TEMPERATURE Protection type : Shut down o/p voltage, re-power on to recover							
	DC_OK SIGNAL PSU turn on:3.3V ~ 5.6V	PUS turn off:0 ~ 1V						
	REMOTE CONTROL RC+/RC-: 0 ~ 0.8V power on; 4 ~ 10V power off							
ENVIRONMENT	WORKING TEMP. -20 ~ +70°C (Refer to "Derating Curve")							
	WORKING HUMIDITY 20 ~ 90% RH non-condensing							
	STORAGE TEMP., HUMIDITY -40 ~ +85°C, 10 ~ 95% RH							
	TEMP. COEFFICIENT ±0.05%/°C (0 ~ 50°C)							
	VIBRATION 10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes							
SAFETY & EMC (Note 4)	SAFETY STANDARDS UL62368-1, BSMI CNS14336-1, EAC TP TC 004 approved; Design refer to BS EN/EN62368-1							
	WITHSTAND VOLTAGE I/P-O/P:3KVAC I/P-FG:1.5KVAC O/P-FG:0.5KVAC							
	ISOLATION RESISTANCE I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25°C / 70% RH							
	EMC EMISSION	Parameter	Standard	Test Level / Note				
		Conducted	BS EN/EN55032 (CISPR32)	Class B				
		Radiated	BS EN/EN55032 (CISPR32)	Class A				
		Harmonic Current	BS EN/EN61000-3-2	----				
	EMC IMMUNITY	Voltage Flicker	BS EN/EN61000-3-3	----				
		Parameter			Test Level / Note			
		ESD	BS EN/EN61000-4-2	Level 3, 8KV air ; Level 2, 4KV contact				
		Radiated	BS EN/EN61000-4-3	Level 3				
		EFT / Burst	BS EN/EN61000-4-4	Level 3				
		Surge	BS EN/EN61000-6-2	2KV/Line-Line 4KV/Line-Earth				
		Conducted	BS EN/EN61000-4-6	Level 3				
OTHERS	Magnetic Field BS EN/EN61000-4-8			Level 4				
	Voltage Dips and Interruptions BS EN/EN61000-4-11			>95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250 periods				
	MTBF 333.3K hrs min. Telcordia SR-332 (Bellcore) ; 134.5K hrs min. MIL-HDBK-217F (25°C)							
DIMENSION	278*177.8*63.5mm (L*W*H)							
	PACKING 3.3Kg; 4pcs/14.2Kg/1.14CUFT							
NOTE	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. The power supply is considered a component which will be installed into a final equipment. All the EMC tests are been executed by mounting the unit on a 720mm*360mm metal plate with 1mm of thickness. The final equipment must be re-confirmed that it still meets EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies." (as available on http://www.meanwell.com) 5. The ambient temperature derating of 3.5°C/1000m with fanless models and of 5°C/1000m with fan models for operating altitude higher than 2000m(6500ft). 6. This power supply does not meet the harmonic current requirements outlined by EN61000-3-2. Please do not use this power supply under the following conditions: a) the end-devices is used within the European Union, and b) the end-devices is connected to public mains supply with 220Vac or greater rated nominal voltage, and c) the power supply is: - installed in end-devices with average or continuous input power greater than 75W, or - belong to part of a lighting system Exception: Power supplies used within the following end-devices do not need to fulfill EN61000-3-2 a) professional equipment with a total rated input power greater than 1000W; b) symmetrically controlled heating elements with a rated power less than or equal to 200W ※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx							

■ Mechanical Specification

Case No.982A Unit:mm




Terminal Pin No. Assignment :

Pin No.	Assignment
1	AC/L
2	AC/N
3	FG \pm


Control Pin (CN3) : JST B6B-XH or equivalent

Pin No.	Assignment	Pin No.	Assignment	Mating Housing	Terminal
1	DC_OK Signal	4	+S	JST XHP or equivalent	JST SXH-001T or equivalent
2	DC_OK GND	5	RC-		
3	-S	6	RC+		


■ Block Diagram



■ Derating Curve



■ Static Characteristics





1500W Single Output Power Supply

SE-1500 series

■ Function Description of CN3


Pin No.	Function	Description
1	DC_OK	DC_OK signal is a TTL level signal, referenced to pin2(DC_OK GND). "High" when PSU turns on.
2	GND	This pin connects to the negative terminal (-V). Return for DC_OK signal output.
3	-S	Negative sensing. The -S signal should be connected to the negative terminal of the load. The -S and +S leads should be twisted in pair to minimize noise pick-up effect.
4	+S	Positive sensing. The +S signal should be connected to the positive terminal of the load. The +S and -S leads should be twisted in pair to minimize noise pick-up effect.
5	RC-	Return for RC+ signal input.
6	RC+	Turns the output on and off by electrical or dry contact between pin 6 (RC+) and pin 5 (RC-). 0~0.8V: Power ON, 4~10V: Power OFF.

■ Function Manual

1. DC_OK Signal

DC_OK Signal is a TTL level signal. "High" when PSU turns on.


Between DC_OK(pin1) and GND(pin2)	Output Status
3.3 ~ 5.6V	ON
0 ~ 1V	OFF



2. Remote Control

The PSU can be turned ON/OFF by using the "Remote Control" function.

Between RC+(pin6) and RC-(pin5)	Output Status
SW OFF (0 ~ 0.8V)	ON
SW ON (4 ~ 10V)	OFF



3. Remote Sense

