



■ Features

- Ultra slim
- Universal AC input / Full range
- 2 pole EURO plug, Class II power unit
- No load power consumption < 0.075W for 5~7.5V
<0.15W for 9 ~48V

• Energy efficiency Level VI

- Comply with EU ErP and meet CoC version 5
- Protections: Short circuit / Overload / Over voltage
- Fully enclosed plastic case
- Pass LPS
- LED indicator for power on
- 54V model available for PoE(optional)
- **Various DC plug quick adapter accessory available**
(Plug kit sold separately, please refer to : https://www.meanwell.com/upload/pdf/DC_plug.pdf)
- 3 years warranty

■ Applications

- Consumer electronic devices
- Telecommunication devices
- Office facilities
- Industrial equipments
- Power sourcing equipment of PoE


■ Description

SGA60E is a 60W ultra slim wall-mounted style single-output green adaptor series, which is compact and convenient for carry. SGA60E is a class II power unit (no FG) equipped with the standard 2-Pin European plug, accepting the input range from 90VAC to 264VAC. The whole series provides different models with output voltages ranging between 5VDC and 48VDC that it can satisfy the demands for various types of consumer electronic devices.

With the efficiency up to 89.5% and the extremely low no-load power consumption below 0.075W for 5~7.5V, below 0.15W for 9 ~48V, SGA60E is compliant with EU ErP and 9~48V meet CoC version 5. The supreme feature allows the adaptor to save the energy when it is under either the operating mode or the standby mode. The entire series is approved for international safety regulations; moreover, it adopts the 94V-0 flame retardant plastic case that it can effectively prevent users from electric hazards.

■ Model Encoding

SGA 60 E 05 -P1J



SPECIFICATION


ORDER NO.	SGA60E05-P1J	SGA60E07-P1J	SGA60E09-P1J	SGA60E12-P1J	SGA60E15-P1J	SGA60E18-P1J	SGA60E24-P1J	SGA60E48-P1J															
OUTPUT	SAFETY MODEL NO.	SGA60E05	SGA60E07	SGA60E09	SGA60E12	SGA60E15	SGA60E18	SGA60E24	SGA60E48														
	DC VOLTAGE Note.2	5V	7.5V	9V	12V	15V	18V	24V	48V														
	RATED CURRENT	6A	6A	5.5A	5A	4A	3.33A	2.5A	1.25A														
	CURRENT RANGE	0 ~ 6A	0 ~ 6A	0 ~ 5.5A	0 ~ 5A	0 ~ 4A	0 ~ 3.33A	0 ~ 2.5A	0 ~ 1.25A														
	RATED POWER (max.)	30W	45W	50W	60W	60W	60W	60W	60W														
	ripple & noise (max.) Note.3	80mVp-p	80mVp-p	80mVp-p	80mVp-p	80mVp-p	80mVp-p	100mVp-p	120mVp-p														
	VOLTAGE TOLERANCE Note.4	± 5.0%	± 5.0%	± 5.0%	± 3.0%	± 3.0%	± 2.0%	± 2.0%	± 2.0%														
	LINE REGULATION Note.5	± 1.0%	± 1.0%	± 1.0%	± 1.0%	± 1.0%	± 1.0%	± 1.0%	± 1.0%														
	LOAD REGULATION Note.6	± 5.0%	± 5.0%	± 5.0%	± 3.0%	± 3.0%	± 2.0%	± 2.0%	± 2.0%														
SETUP, RISE, HOLD UP TIME		2500ms, 50ms, 10ms/230VAC				2500ms, 50ms, 10ms/115VAC at full load																	
INPUT	VOLTAGE RANGE Note.7	90 ~ 264VAC																					
	FREQUENCY RANGE	47 ~ 63Hz																					
	EFFICIENCY (Typ.)	83.5%	85%	86.5%	87.5%	87%	88%	88%	89.5%														
	AC CURRENT	1.5A / 115VAC	0.75A / 230VAC																				
	INRUSH CURRENT (max.)	Cold start 40A / 115VAC		80A / 230VAC																			
PROTECTION	LEAKAGE CURRENT(max.)	0.25mA / 240VAC																					
	OVERLOAD	110 ~ 200% rated output power Protection type : Hiccup mode, recovers automatically after fault condition is removed																					
	OVER VOLTAGE	110 ~ 140% rated output voltage Protection type : Clamp by zener diode, output short																					
ENVIRONMENT	WORKING TEMP.	-20 ~ +50°C (Refer to "Derating Curve")																					
	WORKING HUMIDITY	20% ~ 90% RH non-condensing																					
	STORAGE TEMP., HUMIDITY	-20 ~ +85°C, 10 ~ 95% RH non-condensing																					
	TEMP. COEFFICIENT	± 0.03% / °C (0 ~ 40°C)																					
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes																					
SAFETY & EMC (Note. 8)	SAFETY STANDARDS	TUV BS EN/EN62368-1, EAC TP TC 004 approved																					
	WITHSTAND VOLTAGE	I/P-O/P:4242VDC																					
	ISOLATION RESISTANCE	I/P-O/P:100M Ohms / 500VDC / 25°C / 70% RH																					
	EMC EMISSION	Parameter	Standard	Test Level / Note																			
		Conducted emission	BS EN/EN55032(CISPR32)	Class B																			
		Radiated emission	BS EN/EN55032(CISPR32)	Class B																			
		Harmonic current	BS EN/EN61000-3-2	Class A																			
	EMC IMMUNITY	Voltage flicker	BS EN/EN61000-3-3	-----																			
		Parameter	Standard	Test Level / Note																			
		ESD	BS EN/EN61000-4-2	Level 3, 8KV air; Level 2, 4KV contact																			
		RF field susceptibility	BS EN/EN61000-4-3	Level 2, 3V/m																			
		EFT bursts	BS EN/EN61000-4-4	Level 2, 1KV																			
		Surge susceptibility	BS EN/EN61000-4-5	Level 3, 1KV/L-N																			
		Conducted susceptibility	BS EN/EN61000-4-6	Level 2, 3V																			
		Magnetic field immunity	BS EN/EN61000-4-8	Level 1, 1A/m																			
		Voltage dips, interruption	BS EN/EN61000-4-11	>95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250 periods																			
OTHERS	LIFE	3 years : 100% load 40°C, 12hours / day																					
	MTBF	400Khrs min. MIL-HDBK-217F(25°C)																					
CONNECTOR	DIMENSION	93.5*35*51.5mm (L*W*H)																					
	PACKING	250g ; 60pcs / 17kg / CARTON																					
NOTE	PLUG	See page 4~5 ; Other type available by customer requested																					
	CABLE	See page 4~5; Other type available by customer requested																					
1. All parameters are specified at 230VAC input, rated load, 25°C 70% RH ambient. 2. DC voltage: The output voltage set at point measure by plug terminal & 50% load. 3. Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor. 4. Tolerance: includes set up tolerance, line regulation, load regulation. 5. Line regulation is measured from low line to high line at rated load. 6. Load regulation is measured from 10% to 100% rated load. 7. Derating may be needed under low input voltage. Please check the derating curve for more details. 8. The power supply is considered as an independent unit, but the final equipment still need to re-confirm that the whole system complies with the EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies." (as available on http://www.meanwell.com)																							
※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx																							




60WAC-DC High Reliability Slim Wall-mounted Adaptor

SGA60E series

■ Derating Curve





■ Static Characteristics



■ Mechanical Specification

Unit:mm



■ DC output plug

- ◎ Standard plug: P1J

Unit:mm

P1J	Pin Assignment
	Outside - - - - - Inside

- ◎ DC plug changeable through:

- (1) Customization of the standard part with an optional DC plug according to the table (MOQ applicable)
- (2) Quick adapter accessory (sold separately without MOQ)

Please refer to below table and online selection guide : https://www.meanwell.com/upload/pdf/DC_plug.pdf

Example quick adapter accessory:





- ◎ Optional DC plug: (Available in customized cable or quick adapter)

Tuning Fork Style	Type No.	A	B	C	Quick Adapter Accessory
		OD	ID	L	
 (Straight)	P1I	5.5	2.1	9.5	Available (Current rating: 7.5A max.)
	P1L	5.5	2.5	9.5	
	P1M	5.5	2.5	11.0	
	P1IR	5.5	2.1	9.5	
	P1JR	5.5	2.1	11.0	
	P1LR	5.5	2.5	9.5	
	P1MR	5.5	2.5	11.0	
Barrel Style		Type No.	A	C	None
 (Straight)	P2I	5.5	2.1	9.5	
	P2J	5.5	2.1	11.0	
	P2L	5.5	2.5	9.5	
	P2M	5.5	2.5	11.0	
	P2IR	5.5	2.1	9.5	
	P2JR	5.5	2.1	11.0	
	P2LR	5.5	2.5	9.5	
	P2MR	5.5	2.5	11.0	
Lock Style		Type No.	A	C	None
 Floating Locking SWITCHCRAFT original or equivalent	P2S(S761K)	5.53	2.03	12.06	
	P2K(761K)	5.53	2.54	12.06	
	P2C(S760K)	5.53	2.03	9.52	
	P2D(760K)	5.53	2.54	9.52	
Min. Pin Style		Type No.	A	C	Available (Current rating: 5A max.)
 EIAJ equivalent	P3A	2.35	0.7	11.0	
	P3B	4.0	1.7	11.0	
	P3C	4.75	1.7	11.0	



60WAC-DC High Reliability Slim Wall-mounted Adaptor

SGA60E series

Center Pin Style	Type No.	A	B	C	D	Quick Adapter Accessory				
		OD	ID	L	Center Pin					
	P4A	5.5	3.4	11.0	1.0	Available (Current rating: 7.5A max.)				
	P4B	6.5	4.4	11.0	1.4					
	P4C	7.4	5.1	11.0	0.6					
Min. DIN 3 Pin with Lock (male)	Type No.	Pin Assignment								
		PIN No.	Output							
		R6B	1	+Vo						
Min. DIN 4 Pin with Lock (male)	Type No.	2	-Vo							
		R7B	3	+Vo						
		1	+Vo							
Min. DIN 4 Pin with Lock (female)	Type No.	2	-Vo							
		R7BF	3	-Vo						
		4	+Vo							
Stripped and tinned leads	Type No.	Pin Assignment								
		PIN No.	Output							
		1	+Vo							
	by customer	2	-Vo							
		3	-Vo							
	by customer	4	+Vo							
		1 (Ribbed or White)	+Vo							
Length of Land L1 by request (MW's standard length, L: <u>25</u> mm, L1: <u>10</u> mm)	by customer	2 (Letter or Black)	-Vo							

■ Installation Manual

Please refer to : <http://www.meanwell.com/manual.html>