



1W SIP Package DC-DC Unregulated Converter

SPU01 & DPU01 series

■ Features

- SIP6 package with industry standard pinout
- Operating temperature range -40 ~ +90°C
- Comply to BS EN/EN55032 radiated Class A without additional components
- High efficiency up to 84%
- Protection: Short circuit
- 1.5KVDC I/O isolation
- Low cost
- 3 years warranty


■ Applications

- Telecom/datacom system
- Wireless network
- Industrial control facility
- Instrument
- Analyzer
- Detector
- Data switch

■ Description

SPU01 and DPU01 series are 1W isolated and unregulated module type DC-DC converter with SIP6 package. It features international standard pins, a high efficiency up to 84%, wide working temperature range -40~+90°C, 1.5KVDC I/P-O/P isolation voltage, compliance to BS EN/EN55032 radiated Class A without additional components, short circuit protection, etc. The models account for different input voltage 5V/12V/24V±10%, and various output voltage, 5V/12V/15V for single output and ±5V/±12V/±15V for dual outputs, which are suitable for all kinds of systems, Such as industrial control, telecommunication field, distributed power architecture, and so on.

■ Model Encoding





1W SIP Package DC-DC Unregulated Converter

SPU01 & DPU01 series**MODEL SELECTION TABLE**

ORDER NO.	INPUT			OUTPUT		EFFICIENCY (TYP.)	CAPACITOR LOAD (MAX.)		
	INPUT VOLTAGE (RANGE)	INPUT CURRENT		OUTPUT VOLTAGE	OUTPUT CURRENT				
		NO LOAD	FULL LOAD						
SPU01L-05	5V (4.5 ~ 5.5V)	40mA	253mA	5V	0 ~ 200mA	79%	220µF		
SPU01L-12		45mA	255mA	12V	0 ~ 84mA	79%	220µF		
SPU01L-15		45mA	258mA	15V	0 ~ 67mA	79%	220µF		
DPU01L-05		45mA	260mA	±5V	±0 ~ 100mA	78%	*100µF		
DPU01L-12		45mA	255mA	±12V	±0 ~ 42mA	78%	*100µF		
DPU01L-15		45mA	270mA	±15V	±0 ~ 33mA	75%	*100µF		
SPU01M-05	12V (10.8 ~ 13.2V)	15mA	104mA	5V	0 ~ 200mA	81%	220µF		
SPU01M-12		15mA	104mA	12V	0 ~ 84mA	83%	220µF		
SPU01M-15		15mA	103mA	15V	0 ~ 67mA	84%	220µF		
DPU01M-05		15mA	105mA	±5V	±0 ~ 100mA	81%	*100µF		
DPU01M-12		15mA	102mA	±12V	±0 ~ 42mA	83%	*100µF		
DPU01M-15		15mA	108mA	±15V	±0 ~ 33mA	78%	*100µF		
SPU01N-05	24V (21.6 ~ 26.4V)	7mA	52mA	5V	0 ~ 200mA	80%	220µF		
SPU01N-12		7mA	52mA	12V	0 ~ 84mA	81%	220µF		
SPU01N-15		8mA	52mA	15V	0 ~ 67mA	80%	220µF		
DPU01N-05		7mA	54mA	±5V	±0 ~ 100mA	80%	*100µF		
DPU01N-12		8mA	53mA	±12V	±0 ~ 42mA	80%	*100µF		
DPU01N-15		8mA	55mA	±15V	±0 ~ 33mA	78%	*100µF		

* For each output





1W SIP Package DC-DC Unregulated Converter

SPU01 & DPU01 series

SPECIFICATION			
INPUT	VOLTAGE RANGE	L: 4.5 ~ 5.5Vdc , M: 10.8 ~ 13.2Vdc , N: 21.6 ~ 26.4Vdc	
	SURGE VOLTAGE (100ms max.)	5Vin models : 9Vdc ; 12Vin models : 18Vdc ; 24Vin models : 30Vdc	
	FILTER	Internal capacitor	
	PROTECTION	Fuse recommended. 500mA Slow-Blow Type for all models	
	INTERNAL POWER DISSIPATION	500mW	
OUTPUT	VOLTAGE ACCURACY	±3.0%	
	RATED POWER	1W	
	RIPPLE & NOISE Note.2	75mVp-p	
	LINE REGULATION Note.3	1.2% for 1% input variation	
	LOAD REGULATION Note.4	10%	
	SWITCHING FREQUENCY (Typ.)	24Vin: 75KHz, other: 100KHz	
PROTECTION	SHORT CIRCUIT	1 second max.	
ENVIRONMENT	COOLING	Free-air convection	
	WORKING TEMP.	-40 ~ +90°C (Refer to "Derating Curve")	
	CASE TEMPERATURE	+100°C max.	
	WORKING HUMIDITY	20% ~ 90% RH non-condensing	
	STORAGE TEMP., HUMIDITY	-55 ~ +125°C, 10 ~ 95% RH non-condensing	
	TEMP. COEFFICIENT	0.03% / °C (0 ~ 85°C)	
	SOLDERING TEMPERATURE	1.5mm from case of 1 ~ 3sec./260°C max.	
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes	
SAFETY & EMC (Note.5)	SAFETY STANDARDS	EAC TP TC 020/2011 approved	
	WITHSTAND VOLTAGE	I/P-O/P:1.5KVDC	
	ISOLATION RESISTANCE	I/P-O/P:100M Ohms / 500VDC / 25°C / 70% RH	
	ISOLATION CAPACITANCE (Typ.)	10pF	
	EMC EMISSION	Parameter	Standard
		Conducted	BS EN/EN55032(CISPR32)
		Radiated	BS EN/EN55032(CISPR32)
	EMC IMMUNITY	Parameter	Standard
		ESD	BS EN/EN61000-4-2
		Radiated Susceptibility	BS EN/EN61000-4-3
		EFT/Burst	BS EN/EN61000-4-4
		Surge	BS EN/EN61000-4-5
		Conducted	BS EN/EN61000-4-6
		Magnetic Field	BS EN/EN61000-4-8
OTHERS	MTBF	1500Khrs MIL-HDBK-217F(25°C)	
	DIMENSION (L*W*H)	5/12Vin models: 19.5*6.1*10.2mm (0.77*0.24*0.40 inch); 24Vin models: 19.5*7.2*10.2mm (0.77*0.28*0.40 inch)	
	CASE MATERIAL	Non-Conductive black plastic (UL 94V-0 rated)	
	PACKING	5/12Vin models: 1.8g; 24Vin models: 2.7g	
NOTE	1. All parameters are specified at normal input(L:5Vdc, M:12Vdc, N:24Vdc), rated load, 25°C 70% RH ambient. 2. Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1µF & 47µF capacitor. 3. Line regulation is measured from low line to high line at rated load. 4. Load regulation is measured from 20% to 100% rated load. 5. The final equipment must be re-confirmed that it still meets EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies." (as available on http://www.meanwell.com) ※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx		

■ Mechanical Specification


- All dimensions in mm(inch)
- Tolerance: $x.x \pm 0.25\text{mm}(x.xx \pm 0.01")$
 $x.xx \pm 0.13\text{mm}(x.xxx \pm 0.005")$
- Pin pitch tolerance: $\pm 0.05\text{mm} (\pm 0.002")$



■ Plug Assignment

Pin-Out		
Pin No.	SPU01 (Single output)	DPU01 (Dual output)
1	+Vin	+Vin
2	-Vin	-Vin
4	-Vout	-Vout
5	No pin	Common
6	+Vout	+Vout

■ Derating Curve



■ Installation Manual

Please refer to : <http://www.meanwell.com/manual.html>