

Cepex flush mounted receptacle, alpine white  
Part no. 4245




- screw terminals
- with flush mounted installation box
- meeting DIN 18032 standards for ball rebound

Technical specifications

|                           |          |
|---------------------------|----------|
| Ampere                    | 32 A     |
| Poles                     | 5 p      |
| Voltage                   | 400 V    |
| Clock position            | 6 h      |
| Hertz                     | 50-60 Hz |
| Protection type           | IP 44    |
| Shutter                   | false    |
| Weight                    | 345 g    |
| Declaration of Conformity | VDE, EAC |

Drawing



| Drawing<br>1 MB 336      | Amp.<br>Poles | 16  |     |     | 32  |     |     |
|--------------------------|---------------|-----|-----|-----|-----|-----|-----|
|                          |               | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm               | a             | 93  | 93  | 93  | 93  | 93  | 93  |
|                          | b             | 90  | 90  | 90  | 90  | 90  | 90  |
|                          | c             | 95  | 95  | 95  | 95  | 95  | 95  |
|                          | h             | 111 | 111 | 111 | 111 | 111 | 111 |
|                          | i             | 124 | 124 | 124 | 124 | 124 | 124 |
|                          | k             | 33  | 33  | 33  | 33  | 33  | 33  |
|                          | n             | 91  | 91  | 91  | 91  | 91  | 91  |
|                          | o             | 95  | 95  | 95  | 95  | 95  | 95  |
| Terminal for cond. cross |               | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
| section (mm²) min.-max.  |               | —4  | —4  | —4  | —6  | —6  | —6  |