

< High Voltage Insulated Gate Bipolar Transistor: HVIGBT >

CM1200DA-34X

HIGH POWER SWITCHING USE INSULATED TYPE

6th-Version HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules

CM1200DA-34X




- I_C 1200A
- V_{CES} 1700V
- 2-elements in a Pack
- Insulated Type (Al base type)
- CSTBTTM(III) / RFC Diode

APPLICATION

Traction drives, High Reliability Converters / Inverters, DC choppers

OUTLINE DRAWING & CIRCUIT DIAGRAM

Dimensions in mm



MAXIMUM RATINGS

Symbol	Item	Conditions	Ratings	Unit
V_{CES}	Collector-emitter voltage	$V_{GE} = 0V, T_j = 25\ldots+150^\circ C$	1700	V
		$V_{GE} = 0V, T_j = -50^\circ C$	1550	
V_{GES}	Gate-emitter voltage	$V_{CE} = 0V, T_j = 25^\circ C$	± 20	V
I_C	Collector current	DC, $T_C = 98^\circ C$	1200	A
		Pulse (Note 1)	2400	
I_E	Emitter current (Note 2)	DC, $T_C = 70^\circ C$	1200	A
		Pulse (Note 1)	2400	
P_{tot}	Maximum power dissipation (Note 3)	$T_c = 25^\circ C$, IGBT part	7500	W
V_{iso}	Isolation voltage	RMS, sinusoidal, $f = 60Hz$, $t = 1$ min., $T_c = 25^\circ C$	6000	V
Q_{PD}	Partial discharge	Charged part to the baseplate $V1 = 3500$ Vrms, $V2 = 2600$ Vrms AC 60 Hz, $T_c = 25^\circ C$ (acc. to IEC 61287)	10	pC
T_j	Junction temperature		-50 ~ +150	°C
T_{top}	Operating junction temperature		-50 ~ +150	°C
T_{stg}	Storage temperature		-55 ~ +150	°C
t_{psc}	Short circuit pulse width	$V_{CC} = 1200V, V_{CE} \leq V_{CES}, V_{GE} = 15V, T_j = 150^\circ C$ $R_{G(on)} = 1.1\Omega, R_{G(off)} = 6.8\Omega, C_{GE} = 33nF$	6.5	μs

ELECTRICAL CHARACTERISTICS

Symbol	Item	Conditions	Limits			Unit	
			Min	Typ	Max		
I_{CES}	Collector cutoff current	$V_{CE} = V_{CES}, V_{GE} = 0V$	$T_j = 25^\circ C$	—	—	mA	
			$T_j = 125^\circ C$	—	1.5		
			$T_j = 150^\circ C$	—	9.0		
$V_{GE(th)}$	Gate-emitter threshold voltage	$V_{CE} = 10$ V, $I_c = 120$ mA, $T_j = 25^\circ C$	5.5	6.0	6.5	V	
I_{GES}	Gate leakage current	$V_{GE} = V_{GES}, V_{CE} = 0V, T_j = 25^\circ C$	-0.5	—	0.5	μA	
C_{ies}	Input capacitance	$V_{CE} = 10$ V, $V_{GE} = 0$ V, $f = 100$ kHz $T_j = 25^\circ C$	—	330	—	nF	
C_{oes}	Output capacitance		—	7.2	—	nF	
C_{res}	Reverse transfer capacitance		—	2.9	—	nF	
Q_G	Total gate charge	$V_{CC} = 900V, I_c = 1200A, V_{GE} = \pm 15V$	—	20.5	—	μC	
V_{CEsat}	Collector-emitter saturation voltage	$I_c = 1200$ A (Note 4) $V_{GE} = 15$ V	$T_j = 25^\circ C$	—	1.80	V	
			$T_j = 125^\circ C$	—	2.15		
			$T_j = 150^\circ C$	—	2.20		
$t_{d(on)}$	Turn-on delay time	$V_{CC} = 900$ V $I_c = 1200$ A $V_{GE} = \pm 15$ V $R_{G(on)} = 1.1$ Ω $L_s = 40nH$	$T_j = 150^\circ C$	—	1.30	μs	
t_r	Rise time		$T_j = 150^\circ C$	—	0.50	μs	
$E_{on(10\%)}$	Turn-on switching energy per pulse (Note 5)		$T_j = 25^\circ C$	—	0.27	J	
			$T_j = 125^\circ C$	—	0.38		
			$T_j = 150^\circ C$	—	0.40		
			$T_j = 25^\circ C$	—	0.30		
E_{on}	Turn-on switching energy per pulse (Note 6)	$I_c = 1200$ A $V_{GE} = \pm 15$ V $R_{G(on)} = 1.1$ Ω $L_s = 40nH$ Inductive load $C_{GE} = 33nF$	$T_j = 125^\circ C$	—	0.40	J	
			$T_j = 150^\circ C$	—	0.43		
			$T_j = 25^\circ C$	—	3.10		
			$T_j = 125^\circ C$	—	3.20		
$t_{d(off)}$	Turn-off delay time	$V_{CC} = 900$ V $I_c = 1200$ A $V_{GE} = \pm 15$ V $R_{G(off)} = 6.8$ Ω $L_s = 40nH$ Inductive load $C_{GE} = 33nF$	$T_j = 150^\circ C$	—	3.25	5.00	
t_f	Fall time		$T_j = 25^\circ C$	—	0.16	μs	
			$T_j = 125^\circ C$	—	0.19		
			$T_j = 150^\circ C$	—	0.20		
$E_{off(10\%)}$	Turn-off switching energy per pulse (Note 5)		$T_j = 25^\circ C$	—	0.30	J	
			$T_j = 125^\circ C$	—	0.36		
			$T_j = 150^\circ C$	—	0.39		
			$T_j = 25^\circ C$	—	0.36		
E_{off}	Turn-off switching energy per pulse (Note 6)		$T_j = 125^\circ C$	—	0.48	J	
			$T_j = 150^\circ C$	—	0.49		

< High Voltage Insulated Gate Bipolar Transistor : HVIGBT >

CM1200DA-34XHIGH POWER SWITCHING USE
INSULATED TYPE

6th-Version HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules

ELECTRICAL CHARACTERISTICS (continuation)

Symbol	Item	Conditions	Limits			Unit
			Min	Typ	Max	
V_{EC}	Emitter-collector voltage (Note 2)	$I_E = 1200 \text{ A}$ (Note 4) $V_{GE} = 0 \text{ V}$	$T_j = 25^\circ\text{C}$	—	1.80	—
			$T_j = 125^\circ\text{C}$	—	1.90	—
			$T_j = 150^\circ\text{C}$	—	1.90	2.40
t_{rr}	Reverse recovery time (Note 2)		$T_j = 25^\circ\text{C}$	—	0.35	—
			$T_j = 125^\circ\text{C}$	—	0.50	—
			$T_j = 150^\circ\text{C}$	—	0.53	—
I_{rr}	Reverse recovery current (Note 2)		$T_j = 25^\circ\text{C}$	—	830	—
			$T_j = 125^\circ\text{C}$	—	860	—
			$T_j = 150^\circ\text{C}$	—	880	—
$Q_{rr(10\%)}$	Reverse recovery charge (Note 2) (Note 7)	$V_{CC} = 900 \text{ V}$ $I_C = 1200 \text{ A}$ $V_{GE} = \pm 15 \text{ V}$ $R_{G(on)} = 1.1\Omega$ $L_s = 40\text{nH}$ Inductive load $C_{GE} = 33\text{nF}$	$T_j = 25^\circ\text{C}$	—	195	—
			$T_j = 125^\circ\text{C}$	—	310	—
			$T_j = 150^\circ\text{C}$	—	335	—
Q_{rr}	Reverse recovery charge (Note 2) (Note 6)		$T_j = 25^\circ\text{C}$	—	205	—
			$T_j = 125^\circ\text{C}$	—	320	—
			$T_j = 150^\circ\text{C}$	—	350	—
$E_{rec(10\%)}$	Reverse recovery energy per pulse (Note 2) (Note 5)		$T_j = 25^\circ\text{C}$	—	0.13	—
			$T_j = 125^\circ\text{C}$	—	0.17	—
			$T_j = 150^\circ\text{C}$	—	0.18	—
E_{rec}	Reverse recovery energy per pulse (Note 2) (Note 6)		$T_j = 25^\circ\text{C}$	—	0.13	—
			$T_j = 125^\circ\text{C}$	—	0.21	—
			$T_j = 150^\circ\text{C}$	—	0.22	—

THERMAL CHARACTERISTICS

Symbol	Item	Conditions	Limits			Unit
			Min	Typ	Max	
$R_{th(j-c)Q}$	Thermal resistance	Junction to Case, IGBT part , 1/2 module	—	—	16.5	K/kW
		Junction to Case, FWDi part, per 1/2 module	—	—	27.0	K/kW
$R_{th(c-s)}$	Contact thermal resistance	Case to heat sink, 1/2 module $\lambda_{grease} = 1\text{W/m}\cdot\text{k}$, $D_{(c-s)} = 70\mu\text{m}$	—	16.0	—	K/kW

NTC THERMISTOR PART

Symbol	Item	Conditions	Limits			Unit
			Min	Typ	Max	
R_{25}	Zero-power resistance	$T_c=25^\circ\text{C}$	-	5.00	-	$\text{k}\Omega$
$B_{(25/50)}$	B-constant (Note 8)	Approximate by equation	-	3375	-	K

MECHANICAL CHARACTERISTICS

Symbol	Item	Conditions	Limits			Unit
			Min	Typ	Max	
M_t	Mounting torque	Main terminals screw M8	7.0	—	14.0	N·m
M_s		Mounting screw M6	3.0	—	6.0	N·m
M_t		Auxiliary terminals screw M3	0.4	—	1.0	N·m
m	Mass		—	0.75	—	kg
CTI	Comparative tracking index		600	—	—	—
d_a	Clearance	Between terminals and baseplate	19.5	—	—	mm
d_s	Creepage distance	Between terminals and baseplate	32.0	—	—	mm
L_{P-P-N}	Parasitic stray inductance	Between terminal 1, 2 and terminal 6, 7	—	10.0	—	nH
R_{CC+EE}	Internal lead resistance	$T_C = 25^\circ\text{C}$, 1/2 module	—	0.41	—	$\text{m}\Omega$

Note 1. Pulse width and repetition rate should be such that junction temperature (T_j) does not exceed T_{jopmax} rating.

Note 2. The symbols represent characteristics of the anti-parallel, emitter to collector free-wheel diode (FWD_i).

Note 3. Junction temperature (T_j) should not exceed T_{jmax} rating (150°C).

Note 4. Pulse width and repetition rate should be such as to cause negligible temperature rise.

Note 5. The integration range of switching energies is from 10% V_{CE} to 10% $I_C(10\%I_E)$.

Note 6. Definition of all items is according to IEC 60747, unless otherwise specified.

Note 7. The integration range of reverse recovery charge is from $I_E = 0\text{A}$ to 10% I_E .

$$\text{Note 8. } B_{(25/50)} = \ln\left(\frac{R_{25}}{R_{50}}\right) / \left(\frac{1}{T_{25}} - \frac{1}{T_{50}}\right)$$





R_{25} : resistance at 25°C

R_{50} : resistance at 50°C

T_{25} [K]; $T_{25} = 25^\circ\text{C} + 273.15 = 298.15\text{[K]}$


T_{50} [K]; $T_{50} = 50^\circ\text{C} + 273.15 = 323.15\text{[K]}$

PERFORMANCE CURVES


OUTPUT CHARACTERISTICS
(TYPICAL)TRANSFER CHARACTERISTICS
(TYPICAL)COLLECTOR-EMITTER SATURATION VOLTAGE
CHARACTERISTICS (TYPICAL)FREE-WHEEL DIODE FORWARD
CHARACTERISTICS (TYPICAL)

PERFORMANCE CURVES


CAPACITANCE CHARACTERISTICS
(TYPICAL)




GATE CHARGE CHARACTERISTICS
(TYPICAL)







HALF-BRIDGE SWITCHING ENERGY
CHARACTERISTICS (TYPICAL)



HALF-BRIDGE SWITCHING ENERGY
CHARACTERISTICS (TYPICAL)




PERFORMANCE CURVES




PERFORMANCE CURVES


FREE-WHEEL DIODE REVERSE RECOVERY CHARACTERISTICS (TYPICAL)



FREE-WHEEL DIODE REVERSE RECOVERY CHARACTERISTICS (TYPICAL)







TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS



$$Z_{th(j-c)}(t) = \sum_{i=1}^n R_i \left\{ 1 - \exp \left(-\frac{t}{\tau_i} \right) \right\}$$

	1	2	3	4
$R_i / R_{th(j-c)}$:	0.0292	0.0832	0.2277	0.6599
τ_i [sec.] :	0.0025	0.0027	0.0155	0.0865

PERFORMANCE CURVES**REVERSE BIAS SAFE OPERATING AREA
(RBSOA)****SHORT CIRCUIT
SAFE OPERATING AREA (SCSOA)****FREE-WHEEL DIODE REVERSE RECOVERY
SAFE OPERATING AREA (RRSOA)****NTC THERMISTOR
TEMPERATURE CHARACTERISTICS
(TYPICAL)**

Important Notice

The information contained in this datasheet shall in no event be regarded as a guarantee of conditions or characteristics. This product has to be used within its specified maximum ratings, and is subject to customer's compliance with any applicable legal requirement, norms and standards.

Except as otherwise explicitly approved by Mitsubishi Electric Corporation in a written document signed by authorized representatives of Mitsubishi Electric Corporation, our products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

In usage of power semiconductor, there is always the possibility that trouble may occur with them by the reliability lifetime such as Power Cycle, Thermal Cycle or others, or when used under special circumstances (e.g. condensation, high humidity, dusty, salty, highlands, environment with lots of organic matter / corrosive gas / explosive gas, or situations which terminals of semiconductor products receive strong mechanical stress). Therefore, please pay sufficient attention to such circumstances. Further, depending on the technical requirements, our semiconductor products may contain environmental regulation substances, etc. If there is necessity of detailed confirmation, please contact our nearest sales branch or distributor.

The contents or data contained in this datasheet are exclusively intended for technically trained staff. Customer's technical departments should take responsibility to evaluate the suitability of Mitsubishi Electric Corporation product for the intended application and the completeness of the product data with respect to such application. In the customer's research and development, please evaluate it not only with a single semiconductor product but also in the entire system, and judge whether it's applicable. As required, pay close attention to the safety design by installing appropriate fuse or circuit breaker between a power supply and semiconductor products to prevent secondary damage. Please also pay attention to the application note and the related technical information.

Keep safety first in your circuit designs!

Mitsubishi Electric Corporation puts the maximum effort into making semiconductor products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with semiconductors may lead to personal injury, fire or property damage. Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (i) placement of substitutive, auxiliary circuits, (ii) use of non-flammable material or (iii) prevention against any malfunction or mishap.

Notes regarding these materials

- These materials are intended as a reference to assist our customers in the selection of the Mitsubishi Electric Semiconductor product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Mitsubishi Electric Corporation or a third party.
- Mitsubishi Electric Corporation assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.
- All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Mitsubishi Electric Corporation without notice due to product improvements or other reasons. It is therefore recommended that customers contact Mitsubishi Electric Corporation or an authorized Mitsubishi Electric Semiconductor product distributor for the latest product information before purchasing a product listed herein.

The information described here may contain technical inaccuracies or typographical errors. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.

Please also pay attention to information published by Mitsubishi Electric Corporation by various means, including the Mitsubishi Electric Semiconductor home page (<https://www.MitsubishiElectric.com/semiconductors/>).

- When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.
- Mitsubishi Electric Corporation semiconductors are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake. Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Electric Semiconductor product distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or systems for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
- The prior written approval of Mitsubishi Electric Corporation is necessary to reprint or reproduce in whole or in part these materials.
- If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination.

Any diversion or re-export contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.

- Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Electric Semiconductor product distributor for further details on these materials or the products contained therein.