


Mounting aid Safety

PG SLC-150



- Glass panel to protect the light outlet surface of safety light grids and curtains

Protective glass panes for SLC series



Technical Data

Ambient conditions

Storage temperature -40 ... 85 °C (-40 ... 185 °F)

Mechanical specifications

Material mineral glass lens

Suitable series

Safety Series SLC

Scope of Delivery

Notice

Mineral glass windows for protection of light exit surface of safety light curtains(example: Use of welding robots for protection from sparks).

Supplied accessories

One packaging unit contains 2 glass panes (one each for transmitter and receiver).

Protective glass panes 1050 mm or larger are separated.

SLC protective glass holders are required to mount protective glass panes.

Product Versions

Safety light curtain	Order code for matching protective glass pane	Recommended number of SLC protective glass holders		
		(complete transmitter and receiver)		
SLCxx-150...	PG SLC-150		2*	
SLCxx-300...	PG SLC-300		2*	
SLCxx-450...	PG SLC-450		2*	
SLCxx-600...	PG SLC-600		3*	
SLCxx-750...	PG SLC-750		3*	
SLCxx-900...	PG SLC-900		3*	
SLCxx-1050...	PG SLC-1050		5*	
SLCxx-1200...	PG SLC-1200		5*	
SLCxx-1350...	PG SLC-1350		5*	
SLCxx-1500...	PG SLC-1500		5*	
SLCxx-1650...	PG SLC-1650		6*	
SLCxx-1800...	PG SLC-1800		6*	

* Packaging units (1 unit = 4 Holder)