


Reflector, heatable REF-HEATER120


- Mounting holes for simple installation



Reflector, rectangular 120 mm x 51 mm, mounting holes, heatable 24 V DC



Dimensions



1	Green LED, ready indicator
2	Red LED, lights up when heater is active
3	M12x1 plug, 4-pin
4	Temperature sensor

Technical Data

General specifications

Construction type	rectangular
-------------------	-------------

Electrical specifications

Operating voltage	U_B	24 V DC
Operating current	I_B	200 mA
Power consumption	P_0	max. 6 W

Ambient conditions

Ambient temperature	-20 ... 60 °C (-4 ... 140 °F)
---------------------	-------------------------------

Mechanical specifications

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Connection	4-pin, M12 x 1 connector
Material	PMMA/ABS
Dimensions	119 mm x 51.5 mm x 27 mm
Mounting	mounting holes

Connection Assignment



Release date: 2020-03-21 Date of issue: 2020-06-29 Filename: 113964_eng.pdf

Safety Information

CAUTION:

Mount the reflector on a fireproof surface.

Do **not** use the reflector in potentially explosive spaces or near combustibles.

Release date: 2020-03-21 Date of issue: 2020-06-29 Filename: 113964_eng.pdf