



Solenoid Driver

KFD0-SD2-Ex1.1065


- 1-channel isolated barrier
- 24 V DC supply (loop powered)
- Current limit 65 mA at 9.8 V DC
- Up to SIL 3 acc. to IEC/EN 61508



Function

This isolated barrier is used for intrinsic safety applications. It supplies power to solenoids, LEDs, and audible alarms located in a hazardous area. It is loop powered, so the available energy at the output is received from the input signal. The output signal has a resistive characteristic. As a result the output voltage and current are dependent on the load and the input voltage. At full load, 9.8 V at 65 mA is available for the hazardous area application.

Connection



Technical Data

General specifications		
Signal type		Digital Output
Functional safety related parameters		
Safety Integrity Level (SIL)		SIL 3
Supply		
Rated voltage	U _r	20 ... 35 V DC , loop powered
Power dissipation		< 1 W (≤ 30 V)
Input		
Connection side		control side
Connection		terminals 7, 8
Rated voltage	U _r	20 ... 35 V DC

Release date: 2023-04-18 Date of issue: 2023-04-18 Filename: 133238_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0002
pa-info@us.pepperl-fuchs.com

Germany: +49 621 776 2222
pa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
pa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data


Current		72 mA at 20 V input voltage, load = 150 Ω 50 mA at 35 V input voltage, load = 150 Ω
Output		
Connection side		field side
Connection		terminals 1+, 2-
Internal resistor	R _i	≤ 90 Ω
Current	I _e	≤ 65 mA
Voltage	U _e	≥ 9.8 V
Open loop voltage	U _s	min. 15.4 V
Output rated operating current		65 mA
Output signal		These values are valid for the rated operating voltage 20 ... 35 V DC.
Energized/De-energized delay		single operation: 300 μs/50 μs; periodical: 5 μs / 50 μs
Indicators/settings		
Display elements		LED
Labeling		space for labeling at the front
Directive conformity		
Electromagnetic compatibility		
Directive 2014/30/EU		EN 61326-1:2013 (industrial locations)
Conformity		
Electromagnetic compatibility		NE 21:2006
Degree of protection		IEC 60529:2001
Protection against electrical shock		UL 61010-1:2004
Ambient conditions		
Ambient temperature		-20 ... 60 °C (-4 ... 140 °F)
Mechanical specifications		
Degree of protection		IP20
Connection		screw terminals
Mass		approx. 100 g
Dimensions		20 x 107 x 115 mm (0.8 x 4.2 x 4.5 inch) (W x H x D) , housing type B1
Mounting		on 35 mm DIN mounting rail acc. to EN 60715:2001
Data for application in connection with hazardous areas		
EU-type examination certificate		BASEEFA 06 ATEX 0252
Marking		Ⓢ II (1)G [Ex ia Ga] IIC Ⓢ II (1)D [Ex ia Da] IIIC Ⓢ I (M1) [Ex ia Ma] I
Voltage	U _o	17.22 V
Current	I _o	220 mA
Power	P _o	947 mW
Input		
Maximum safe voltage	U _m	250 V (Attention! The rated voltage can be lower.)
Certificate		TÜV 99 ATEX 1499 X
Marking		Ⓢ II 3G Ex nA II T4
Galvanic isolation		
Input/Output		safe electrical isolation acc. to IEC/EN 60079-11, voltage peak value 375 V
Directive conformity		
Directive 2014/34/EU		EN IEC 60079-0:2018+AC:2020 , EN 60079-11:2012 , EN 60079-15:2010
International approvals		
FM approval		
Control drawing		116-0309
UL approval		E106378
Control drawing		116-0316 (cULus)
IECEX approval		
IECEX certificate		IECEX BAS 06.0058 IECEX CML 19.0093X

Release date: 2023-04-18 Date of issue: 2023-04-18 Filename: 133238_eng.pdf

Technical Data

IECEEx marking	[Ex ia Ga] IIC , [Ex ia Da] IIIC , [Ex ia Ma] I Ex ec IIC T4 Gc
General information	
Supplementary information	Observe the certificates, declarations of conformity, instruction manuals, and manuals where applicable. For information see www.pepperl-fuchs.com .

Assembly



Matching System Components

	K-DUCT-BU	Profile rail, wiring comb field side, blue
---	------------------	--

Accessories


	KF-ST-5GN	Terminal block for KF modules, 3-pin screw terminal, green
	KF-ST-5BU	Terminal block for KF modules, 3-pin screw terminal, blue
	KF-CP	Red coding pins, packaging unit: 20 x 6

Release date: 2023-04-18 Date of issue: 2023-04-18 Filename: 133238_eng.pdf

Characteristic Curve

Output characteristics

Output circuit diagram



Output characteristic

