



RFID Transponder


IPC03-30P

- Battery-free data carrier
- 32 bit fixcode
- 928 bits memory available
- Readable and writable from both sides
- Mounting holes for simple installation
- Degree of protection IP68 / IP69K

Data carrier



Dimensions



Technical Data

General specifications		
Operating frequency		125 kHz
Transfer rate		2 kBit/s
Memory		
Chip Type		EM4450 Titan (EM Microelectronic)
EEPROM		928 Bit
Read cycles		unlimited
Write cycles		> 100000
Data retention period		10 years at 55 °C (131 °F)
Directive conformity		
Radio equipment		
Directive 2014/53/EU		EN 300330
RoHS		
Directive 2011/65/EU (RoHS)		IEC/EN 63000
Standard conformity		
Degree of protection		EN 60529
RFID		ISO/IEC 18000-2

Release date: 2024-07-05 Date of issue: 2024-07-05 Filename: 192203_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data


Ambient conditions		
Ambient temperature		-20 ... 100 °C (-4 ... 212 °F)
Storage temperature		-20 ... 100 °C (-4 ... 212 °F)
Mechanical specifications		
Degree of protection		IP68 / IP69K
Material		
Housing		PC (Polycarbonate)
Installation		
In air		yes
Dimensions		
Height		3 mm
Height tolerance		± 0.2 mm
Diameter		30 mm
Diameter tolerance		± 0.2 mm
Construction type		Cylindrical

Reading range in air IPC03-30..




Release date: 2024-07-05 Date of issue: 2024-07-05 Filename: 192203_eng.pdf

Writing range in air IPC03-30..




Reading range on aluminium IPC03-30..




Release date: 2024-07-05 Date of issue: 2024-07-05 Filename: 192203_eng.pdf

Writing range on aluminium IPC03-30..




Reading range on steel IPC03-30..



Release date: 2024-07-05 Date of issue: 2024-07-05 Filename: 192203_eng.pdf

Writing range on steel IPC03-30..



- | | | | |
|---------------|-------------|--------------|--------------|
| ① IPH-18GM-V1 | ③ IPH-F61 | ⑤ IPH-FP-V1 | ⑦ IPT1-FP-V1 |
| ② IPH-30GM-V1 | ④ IPH-L2-V1 | ⑥ IPH-F15-V1 | |

Application

The transponder can be read and written from either side.

Release date: 2024-07-05 Date of issue: 2024-07-05 Filename: 192203_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**