


# Inductive sensor

## NBB0,8-5GM25-E2-5M

■ Basic series



### Dimensions



### Technical Data

#### General specifications

|                            |       |                    |
|----------------------------|-------|--------------------|
| Switching function         |       | Normally open (NO) |
| Output type                |       | PNP                |
| Rated operating distance   | $s_n$ | 0.8 mm             |
| Installation               |       | flush              |
| Output polarity            |       | DC                 |
| Assured operating distance | $s_a$ | 0 ... 0.648 mm     |
| Reduction factor $r_{Al}$  |       | 0.45               |
| Reduction factor $r_{Cu}$  |       | 0.4                |
| Reduction factor $r_{304}$ |       | 0.77               |
| Output type                |       | 3-wire             |

#### Nominal ratings

|                             |       |                                        |
|-----------------------------|-------|----------------------------------------|
| Operating voltage           | $U_B$ | 10 ... 30 V                            |
| Switching frequency         | $f$   | 0 ... 3000 Hz                          |
| Hysteresis                  | $H$   | type 5 %                               |
| Reverse polarity protection |       | reverse polarity protected             |
| Short-circuit protection    |       | pulsing                                |
| Voltage drop                | $U_d$ | $\leq 3$ V                             |
| Operating current           | $I_L$ | 0 ... 200 mA                           |
| Off-state current           | $I_r$ | 0 ... 0.1 mA typ. 0.1 $\mu$ A at 25 °C |
| No-load supply current      | $I_0$ | $\leq 10$ mA                           |
| Switching state indicator   |       | LED, yellow                            |

Release date: 2024-04-25 Date of issue: 2024-04-25 Filename: 211472\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

|                                          |   |                                                              |
|------------------------------------------|---|--------------------------------------------------------------|
| Functional safety related parameters     |   |                                                              |
| MTTF <sub>d</sub>                        |   | 2190 a                                                       |
| Mission Time (T <sub>M</sub> )           |   | 20 a                                                         |
| Diagnostic Coverage (DC)                 |   | 0 %                                                          |
| Compliance with standards and directives |   |                                                              |
| Standard conformity                      |   |                                                              |
| Standards                                |   | EN IEC 60947-5-2                                             |
| Approvals and certificates               |   |                                                              |
| UL approval                              |   | cULus Listed, General Purpose                                |
| CCC approval                             |   | CCC approval / marking not required for products rated ≤36 V |
| Ambient conditions                       |   |                                                              |
| Ambient temperature                      |   | -25 ... 70 °C (-13 ... 158 °F)                               |
| Mechanical specifications                |   |                                                              |
| Connection type                          |   | cable                                                        |
| Housing material                         |   | Stainless steel 1.4305 / AISI 303                            |
| Sensing face                             |   | PC                                                           |
| Degree of protection                     |   | IP67                                                         |
| Cable                                    |   |                                                              |
| Wire end ferrules                        |   | yes                                                          |
| Cable diameter                           |   | 3.5 mm ± 0.2 mm                                              |
| Bending radius                           |   | > 10 x cable diameter                                        |
| Material                                 |   | PVC                                                          |
| Color                                    |   | grey                                                         |
| Number of cores                          |   | 3                                                            |
| Core cross section                       |   | 0.14 mm²                                                     |
| Length                                   | L | 5 m                                                          |
| Dimensions                               |   |                                                              |
| Length                                   |   | 25 mm                                                        |
| Diameter                                 |   | 5 mm                                                         |

Connection



Release date: 2024-04-25 Date of issue: 2024-04-25 Filename: 211472\_eng.pdf