

Connection cable

V3-WM-1M-PUR-V3-GM




- Degree of protection IP68
- Resistant to microbes and hydrolysis
- Halogen-free
- Specific design protects against loosening and inaccurate installation

Cordset M8 socket angled to M8 plug straight A-coded, 3-pin, PUR cable grey



Dimensions



Technical Data

General specifications

Connector 1		
Connection		socket
Construction type		M8
Style		angled
Locking		screw connection
Number of pins		3
Coding		A-coded
Connector 2		
Connection		plug
Construction type		M8
Style		straight
Locking		screw connection
Number of pins		3
Coding		A-coded

Electrical specifications

Operating voltage	U_B	max. 48 V AC / 60 V DC
Operating current	I_B	max. 3 A

Conformity

Degree of protection		EN 60529
Plug connection		connector M8 x 1 : IEC 61076-2-104
Halogen-free		IEC 60754-1

Release date: 2023-06-19 Date of issue: 2023-06-19 Filename: 213571_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Ambient conditions			
Ambient temperature			
Plug connector			-40 ... 90 °C (-40 ... 194 °F)
Cable, fixed			-40 ... 80 °C (-40 ... 176 °F)
Cable, flexing			-20 ... 80 °C (-4 ... 176 °F)
Pollution degree			3
Mechanical specifications			
Plug connector			
Tightening torque			0.4 Nm
Loosening protection			available
Tool installation			straight knurling and hexagon nut SW = 9 mm
Mating cycles			min. 100
Degree of protection			IP68
Cable			according to IEC/EN 60228 (DIN VDE 0295) class 5
Sheath diameter			4.3 mm
Bending radius			> 15 x cable diameter, moving > 8 x cable diameter, fixed
Sheath stripping force			max. 80 N / 500 mm
Sheath color			grey (similar to RAL 7001)
Number of cores			3
Core cross section			0.25 mm²
Cores color			Core 1: brown Core 3: blue Core 4: black
Core construction			14 x 0.15 mm Ø
Length	L		1 m
Cable code			Li 9Y 11Y 3 x 0,25
Drag chain suitability			
Drag chain cycles			max. 50 / day
Motion velocity			max. 0.3 m/s
Material			
Halogen-free			yes
Plug connector			
Screw connection			Zinc diecast, nickel-plated
Body			TPU, black
Seal			FKM
Contact surface			gold plated (Au)
Flammability			V-2
Cable			
Sheathing			PUR based on polyether
Core insulation			PP
Chemical resistance			good
Microbial resistance			yes
Hydrolysis resistance			yes

Connection



Accessories

	MH V3-SCREWDRIVER	Torque screwdriver (0.4 Nm)
	MH V3-BIT M8	plug-in cap for M8
	V1/V3-LABELHOLDER	Label holder
	V1/V3-LABEL	Label plate
	MH V3-Holder	Modular universal holder for M8 connectors