

# Inductive sensor


## NRN6-8GH40-E2-V1



- 6 mm non-flush
- Reduction factor = 1
- Magnetic field resistant
- Stainless steel housing
- Front face FDA conform



### Dimensions



### Technical Data

#### General specifications

|                             |       |                    |
|-----------------------------|-------|--------------------|
| Switching function          |       | Normally open (NO) |
| Output type                 |       | PNP                |
| Rated operating distance    | $s_n$ | 6 mm               |
| Installation                |       | non-flush          |
| Output polarity             |       | DC                 |
| Assured operating distance  | $s_a$ | 0 ... 4.86 mm      |
| Reduction factor $r_{Al}$   |       | 1                  |
| Reduction factor $r_{Cu}$   |       | 1                  |
| Reduction factor $r_{304}$  |       | 1                  |
| Reduction factor $r_{Si37}$ |       | 1                  |
| Output type                 |       | 3-wire             |

#### Nominal ratings

|                             |       |                            |
|-----------------------------|-------|----------------------------|
| Operating voltage           | $U_B$ | 10 ... 30 V DC             |
| Switching frequency         | $f$   | 0 ... 2500 Hz              |
| Hysteresis                  | $H$   | typ. 5 %                   |
| Reverse polarity protection |       | reverse polarity protected |
| Short-circuit protection    |       | pulsing                    |
| Voltage drop                | $U_d$ | $\leq 2$ V                 |
| Operating current           | $I_L$ | 0 ... 200 mA               |

Release date: 2024-05-28 Date of issue: 2024-06-02 Filename: 233615\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**


Technical Data

|                                                 |       |                                                                    |
|-------------------------------------------------|-------|--------------------------------------------------------------------|
| Off-state current                               | $I_r$ | 0 ... 0.5 mA typ. 0.1 $\mu$ A at 25 °C                             |
| No-load supply current                          | $I_0$ | $\leq$ 15 mA                                                       |
| Constant magnetic field                         | B     | 200 mT                                                             |
| Alternating magnetic field                      | B     | 200 mT                                                             |
| Switching state indicator                       |       | Multihole-LED, yellow                                              |
| <b>Functional safety related parameters</b>     |       |                                                                    |
| MTTF <sub>d</sub>                               |       | 1010.5 a                                                           |
| Mission Time (T <sub>M</sub> )                  |       | 20 a                                                               |
| Diagnostic Coverage (DC)                        |       | 0 %                                                                |
| <b>Compliance with standards and directives</b> |       |                                                                    |
| Standard conformity                             |       |                                                                    |
| Standards                                       |       | EN IEC 60947-5-2                                                   |
| <b>Approvals and certificates</b>               |       |                                                                    |
| UL approval                                     |       | cULus Listed, General Purpose, Class 2 Power Source                |
| CCC approval                                    |       | CCC approval / marking not required for products rated $\leq$ 36 V |
| <b>Ambient conditions</b>                       |       |                                                                    |
| Ambient temperature                             |       | -25 ... 85 °C (-13 ... 185 °F)                                     |
| Storage temperature                             |       | -40 ... 100 °C (-40 ... 212 °F)                                    |
| <b>Mechanical specifications</b>                |       |                                                                    |
| Connection type                                 |       | Connector plug M12 x 1 , 3-pin                                     |
| Housing material                                |       | Stainless steel 1.4404 / AISI 316L                                 |
| Sensing face                                    |       | LCP, (conforms with FDA)                                           |
| Degree of protection                            |       | IP67                                                               |
| Dimensions                                      |       |                                                                    |
| Length                                          |       | 40 mm                                                              |
| Diameter                                        |       | 8 mm                                                               |

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

|   |    |         |
|---|----|---------|
| 1 | BN | (brown) |
| 3 | BU | (blue)  |
| 4 | BK | (black) |

Release date: 2024-05-28 Date of issue: 2024-06-02 Filename: 233615\_eng.pdf