

# Female cordset

## V31-GM-OR5M-PUR-A




- Improved resistance to weld spatter
- Suitable for drag chains and abrasion resistant
- Suitable for robotic applications / torsion resistant
- Degree of protection IP68
- Free of paint wetting interfering substances
- Resistant to microbes and hydrolysis
- UL listed for USA and Canada
- Halogen-free
- Specific design protects against loosening and inaccurate installation

Female cordset single-ended M8 straight A-coded, 4-pin, PUR cable weld spatter resistant orange, UL approved, drag chain suitable, torsion resistant



### Dimensions



### Technical Data

#### General specifications

|                   |  |                  |
|-------------------|--|------------------|
| Connector 1       |  |                  |
| Connection        |  | socket           |
| Construction type |  | M8               |
| Style             |  | straight         |
| Locking           |  | screw connection |
| Number of pins    |  | 4                |
| Coding            |  | A-coded          |
| Connector 2       |  |                  |
| Connection        |  | cable end        |

#### Electrical specifications

|                   |       |                 |
|-------------------|-------|-----------------|
| Operating voltage | $U_B$ | max. 30 V AC/DC |
| Operating current | $I_B$ | max. 3 A        |

#### Conformity

|                       |  |                                     |
|-----------------------|--|-------------------------------------|
| Degree of protection  |  | EN 60529                            |
| Plug connection       |  | connector M8 x 1 : IEC 61076-2-104  |
| Flammability          |  | UL 1581; DIN EN 60332-2-2           |
| Halogen-free          |  | DIN VDE 0472-815<br>IEC 60754-1     |
| Microbial resistance  |  | DIN EN 50525-2-21 / DIN VDE 0282-10 |
| Hydrolysis resistance |  | DIN EN 50525-2-21                   |

#### Approvals and certificates

|             |  |                                                    |
|-------------|--|----------------------------------------------------|
| UL approval |  | AWM STYLE 20549 AWM I/II A/B 80°C 300V FT2 (cable) |
|-------------|--|----------------------------------------------------|

Release date: 2023-08-31 Date of issue: 2023-08-31 Filename: 240799-100012\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**

## Technical Data

|                                  |   |                                                                 |
|----------------------------------|---|-----------------------------------------------------------------|
| UL File Number                   |   | E231213                                                         |
| <b>Ambient conditions</b>        |   |                                                                 |
| Ambient temperature              |   |                                                                 |
| Plug connector                   |   | -40 ... 90 °C (-40 ... 194 °F)                                  |
| Cable, fixed                     |   | -40 ... 80 °C (-40 ... 176 °F)                                  |
| Cable, flexing                   |   | -25 ... 80 °C (-13 ... 176 °F)                                  |
| Pollution degree                 |   | 3                                                               |
| <b>Mechanical specifications</b> |   |                                                                 |
| Plug connector                   |   |                                                                 |
| Tightening torque                |   | 0.4 Nm                                                          |
| Loosening protection             |   | available                                                       |
| Tool installation                |   | straight knurling and hexagon nut SW = 9 mm                     |
| Mating cycles                    |   | min. 100                                                        |
| Degree of protection             |   | IP68                                                            |
| Cable                            |   | according to IEC/EN 60228 (DIN VDE 0295) class 6                |
| Sheath diameter                  |   | 4.3 mm                                                          |
| Bending radius                   |   | > 10 x cable diameter, moving<br>> 5 x cable diameter, fixed    |
| Sheath stripping force           |   | max. 50 N / 300 mm                                              |
| Sheath color                     |   | orange (similar to RAL 2003)                                    |
| Number of cores                  |   | 4                                                               |
| Core cross section               |   | 0.34 mm <sup>2</sup>                                            |
| Cores color                      |   | Core 1: brown<br>Core 2: white<br>Core 3: blue<br>Core 4: black |
| Core construction                |   | 42 x 0.1 mm Ø                                                   |
| Length                           | L | 5 m                                                             |
| Cable code                       |   | Li F 9Y 11Y 4 x 0,34                                            |
| Drag chain suitability           |   |                                                                 |
| Drag chain cycles                |   | min. 5000000                                                    |
| Motion velocity                  |   | max. 3.3 m/s                                                    |
| Traverse distance                |   | max. 5 m                                                        |
| Acceleration                     |   | max. 5 m/s <sup>2</sup>                                         |
| Torsion cycles                   |   | min. 1000000                                                    |
| Torsional stress                 |   | ± 180 °/m                                                       |
| <b>Material</b>                  |   |                                                                 |
| PWIS free                        |   | yes                                                             |
| Halogen-free                     |   | yes                                                             |
| Plug connector                   |   |                                                                 |
| Screw connection                 |   | Zinc diecast, nickel-plated                                     |
| Body                             |   | TPU, black                                                      |
| Seal                             |   | FKM                                                             |
| Contact surface                  |   | gold plated (Au)                                                |
| Flammability                     |   | V-2                                                             |
| Cable                            |   |                                                                 |
| Sheathing                        |   | PUR based on polyether                                          |
| Core insulation                  |   | PP                                                              |
| Weld spatter resistance          |   | yes                                                             |
| Chemical resistance              |   | good                                                            |
| Oil resistance                   |   | yes                                                             |
| Cooling lubricant resistance     |   | yes                                                             |
| Microbial resistance             |   | yes                                                             |
| Hydrolysis resistance            |   | yes                                                             |

Release date: 2023-08-31 Date of issue: 2023-08-31 Filename: 240799-100012\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

|              |     |
|--------------|-----|
| Flammability | FT2 |
|--------------|-----|

Connection



Accessories

|                                                                                     |                          |                                            |
|-------------------------------------------------------------------------------------|--------------------------|--------------------------------------------|
|    | <b>MH V3-SCREWDRIVER</b> | Torque screwdriver (0.4 Nm)                |
|    | <b>MH V3-BIT M8</b>      | plug-in cap for M8                         |
|    | <b>V1/V3-LABELHOLDER</b> | Label holder                               |
|   | <b>V1/V3-LABEL</b>       | Label plate                                |
|  | <b>MH V3-Holder</b>      | Modular universal holder for M8 connectors |

Release date: 2023-08-31 Date of issue: 2023-08-31 Filename: 240799-100012\_eng.pdf