

# Cable connector

## V3S-WM-E2-2M-PVC




- Built-in LED, as operating and function indicator
- Degree of protection IP68
- Specific design protects against loosening and inaccurate installation

Male cordset single-ended M8 angled A-coded, LED 3-pin, PVC cable grey



### Dimensions



### Technical Data

#### General specifications

|                   |  |                  |
|-------------------|--|------------------|
| Connector 1       |  |                  |
| Connection        |  | plug             |
| Construction type |  | M8               |
| Style             |  | angled           |
| Locking           |  | screw connection |
| Number of pins    |  | 3                |
| Coding            |  | A-coded          |
| Connector 2       |  |                  |
| Connection        |  | cable end        |

#### Indicators/operating means

|            |  |                          |
|------------|--|--------------------------|
| LED green  |  | Operating display        |
| LED yellow |  | Functional display pin 4 |

#### Electrical specifications

|                   |                |                            |
|-------------------|----------------|----------------------------|
| Operating voltage | U <sub>B</sub> | max. 24 V DC -20 % / +25 % |
| Operating current | I <sub>B</sub> | max. 3 A                   |

#### Conformity

|                      |  |                                    |
|----------------------|--|------------------------------------|
| Degree of protection |  | EN 60529                           |
| Plug connection      |  | connector M8 x 1 : IEC 61076-2-104 |

#### Ambient conditions

|                     |  |  |
|---------------------|--|--|
| Ambient temperature |  |  |
|---------------------|--|--|

Release date: 2023-09-04 Date of issue: 2023-09-04 Filename: 241646\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**

## Technical Data

|                                  |   |                                                               |
|----------------------------------|---|---------------------------------------------------------------|
| Plug connector                   |   | -40 ... 90 °C (-40 ... 194 °F)                                |
| Cable, fixed                     |   | -40 ... 70 °C (-40 ... 158 °F)                                |
| Cable, flexing                   |   | -5 ... 70 °C (23 ... 158 °F)                                  |
| Pollution degree                 |   | 3                                                             |
| <b>Mechanical specifications</b> |   |                                                               |
| Plug connector                   |   |                                                               |
| Tightening torque                |   | 0.4 Nm                                                        |
| Loosening protection             |   | available                                                     |
| Tool installation                |   | straight knurling and hexagon nut SW = 9 mm                   |
| Mating cycles                    |   | min. 100                                                      |
| Degree of protection             |   | IP68                                                          |
| Cable                            |   | according to IEC/EN 60228 (DIN VDE 0295) class 5              |
| Sheath diameter                  |   | 4.3 mm                                                        |
| Bending radius                   |   | > 15 x cable diameter, moving<br>> 10 x cable diameter, fixed |
| Sheath stripping force           |   | max. 80 N / 300 mm                                            |
| Sheath color                     |   | grey (similar to RAL 7001)                                    |
| Number of cores                  |   | 3                                                             |
| Core cross section               |   | 0.25 mm <sup>2</sup>                                          |
| Cores color                      |   | Core 1: brown<br>Core 3: blue<br>Core 4: black                |
| Core construction                |   | 14 x 0.15 mm Ø                                                |
| Length                           | L | 2 m                                                           |
| Cable code                       |   | Li YY 3 x 0,25                                                |
| <b>Material</b>                  |   |                                                               |
| Plug connector                   |   |                                                               |
| Screw connection                 |   | Zinc diecast, nickel-plated                                   |
| Body                             |   | TPU, transparent                                              |
| Contact surface                  |   | gold plated (Au)                                              |
| Flammability                     |   | V-2                                                           |
| Cable                            |   |                                                               |
| Sheathing                        |   | PVC                                                           |
| Core insulation                  |   | PVC                                                           |
| Flammability                     |   | flame-resistant                                               |

## Connection



## Accessories

|                                                                                     |                          |                             |
|-------------------------------------------------------------------------------------|--------------------------|-----------------------------|
|  | <b>MH V3-SCREWDRIVER</b> | Torque screwdriver (0.4 Nm) |
|  | <b>MH V3-BIT M8</b>      | plug-in cap for M8          |

Accessories

|                                                                                   |                          |                                            |
|-----------------------------------------------------------------------------------|--------------------------|--------------------------------------------|
|  | <b>V1/V3-LABELHOLDER</b> | Label holder                               |
|  | <b>V1/V3-LABEL</b>       | Label plate                                |
|  | <b>MH V3-Holder</b>      | Modular universal holder for M8 connectors |

Release date: 2023-09-04 Date of issue: 2023-09-04 Filename: 241646\_eng.pdf