

DIN mounting rail

UPR-MR




- 35 mm DIN mounting rail acc. to EN 60715:2001
- Standard length 2 m (6 foot), simple to customize to application space
- Slot for insert UPR-INS-**
- Packaging unit: 2 pieces

35 mm DIN mounting rail, length: 2 m (packaging unit: 2 pieces)

Function

The DIN mounting rail is used for mounting of K-System isolator modules. The insert UPR-INS-** can be fixed by a slot in the DIN mounting rail. The component comes in 2 m segments but can be cut to any size. The DIN mounting rail UPR-MR and the insert UPR-INS-** form the Power Rail.

Dimensions



Technical Data

Ambient conditions	
Ambient temperature	-40 ... 70 °C (-40 ... 158 °F)
Mechanical specifications	
Material	Aluminum
Mass	approx. 600 g
Dimensions	35 x 15 x 2000 mm (1.4 x 0.6 x 78.7 inch)
General information	
Packing unit	2 item(s)

Release date: 2023-05-22 Date of issue: 2023-05-22 Filename: 248607_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0002
pa-info@us.pepperl-fuchs.com

Germany: +49 621 776 2222
pa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
pa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Accessories

	UPR-INS-03	Insert for 35 mm DIN mounting rail
---	-------------------	------------------------------------

Release date: 2023-05-22 Date of issue: 2023-05-22 Filename: 248607_eng.pdf