

- CE CSA[®] UL[®] UK
C C C CA

Technical drawing of the LED module showing dimensions and components. The drawing includes the following labels and dimensions:


- M18 x 1**: Thread specification for the mounting screw.
- 4**: Dimension of the mounting screw head.
- 24**: Dimension of the mounting screw head.
- 40**: Dimension of the LED module body.
- 45**: Dimension of the LED module body.
- 62**: Dimension of the LED module body.
- 63**: Dimension of the LED module body.
- LEDs**: Label for the light-emitting diodes.

Electrical specifications

Technical Data

Rated operating voltage	U _e	20 ... 250 V AC/DC
Compliance with standards and directives		
Standard conformity		
Standards		EN IEC 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Storage temperature		-40 ... 85 °C (-40 ... 185 °F)
Mechanical specifications		
Connection type		cable
Housing material		brass, nickel-plated
Sensing face		PBT
Degree of protection		IP67
Cable		
Wire end ferrules		yes
Bending radius		> 10 x cable diameter
Material		PUR
Color		black
Number of cores		3
Core cross section		0.5 mm ²
Length	L	10 m
Mass		606 g
Dimensions		
Length		63 mm
Diameter		18 mm

Connection



Release date: 2024-10-17 Date of issue: 2024-10-17 Filename: 264306_eng.pdf