



## Adapter cable


V1S-G-BK0,75M-PUR-U-V1S-G-Y285720

- Pins 1-3 and 2-4 are crossed
- Suitable for robotic applications / torsion resistant
- Degree of protection IP67 / IP68 / IP69
- Free of paint wetting interfering substances
- Resistant to microbes and hydrolysis
- UV resistant
- cURus approval
- Halogen-free
- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching

Adapter cable M12 plug straight to M12 plug straight A-coded, 4-pin crossed, PUR cable black, UL approved, drag chain suitable, torsion resistant



## Dimensions



## Technical Data

### General specifications

|                   |                          |
|-------------------|--------------------------|
| Customization     | pins 1-3 and 2-4 crossed |
| Connector 1       |                          |
| Connection        | plug                     |
| Construction type | M12                      |
| Style             | straight                 |
| Locking           | screw connection         |
| Number of pins    | 4                        |
| Coding            | A-coded                  |
| Connector 2       |                          |
| Connection        | plug                     |
| Construction type | M12                      |
| Style             | straight                 |
| Locking           | screw connection         |
| Number of pins    | 4                        |

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

## Technical Data

|                                   |                |                                                                 |
|-----------------------------------|----------------|-----------------------------------------------------------------|
| Coding                            | A-coded        |                                                                 |
| UL File Number                    |                | E231213                                                         |
| <b>Electrical specifications</b>  |                |                                                                 |
| Operating voltage                 | U <sub>B</sub> | max. 250 V AC/DC                                                |
| Operating current                 | I <sub>B</sub> | max. 4 A                                                        |
| <b>Conformity</b>                 |                |                                                                 |
| Degree of protection              |                | EN 60529                                                        |
| Plug connection                   |                | connector M12 x 1 : IEC 61076-2-101                             |
| Flammability                      |                | UL 1581; DIN EN 60332-2-2                                       |
| Halogen-free                      |                | IEC 60754-1                                                     |
| <b>Approvals and certificates</b> |                |                                                                 |
| UL approval                       |                | AWM STYLE 20549 AWM I/II A/B 80°C 300V FT2 (cable)              |
| <b>Ambient conditions</b>         |                |                                                                 |
| Ambient temperature               |                |                                                                 |
| Plug connector                    |                | -40 ... 90 °C (-40 ... 194 °F)                                  |
| Cable, fixed                      |                | -40 ... 80 °C (-40 ... 176 °F)                                  |
| Cable, flexing                    |                | -20 ... 80 °C (-4 ... 176 °F)                                   |
| Pollution degree                  |                | 3                                                               |
| <b>Mechanical specifications</b>  |                |                                                                 |
| Plug connector                    |                |                                                                 |
| Tightening torque                 |                | 0.6 Nm                                                          |
| Loosening protection              |                | available                                                       |
| Tool installation                 |                | straight knurling                                               |
| Mating cycles                     |                | min. 100                                                        |
| Degree of protection              |                | IP67 / IP68 / IP69                                              |
| Cable                             |                | according to IEC/EN 60228 (DIN VDE 0295) class 6                |
| Sheath diameter                   |                | 4.3 mm                                                          |
| Bending radius                    |                | > 10 x cable diameter, moving<br>> 5 x cable diameter, fixed    |
| Sheath stripping force            |                | max. 80 N / 300 mm                                              |
| Sheath color                      |                | black (similar to RAL 9005)                                     |
| Number of cores                   |                | 4                                                               |
| Core cross section                |                | 0.34 mm <sup>2</sup>                                            |
| Cores color                       |                | Core 1: brown<br>Core 2: white<br>Core 3: blue<br>Core 4: black |
| Core construction                 |                | 42 x 0.1 mm Ø                                                   |
| Length                            | L              | 0.75 m                                                          |
| Cable code                        |                | Li 9Y 11Y 4 x 0.34                                              |
| <b>Drag chain suitability</b>     |                |                                                                 |
| Drag chain cycles                 |                | min. 5000000                                                    |
| Motion velocity                   |                | max. 3.3 m/s                                                    |
| Traverse distance                 |                | max. 5 m                                                        |
| Acceleration                      |                | max. 5 m/s <sup>2</sup>                                         |
| Torsion cycles                    |                | min. 1000000                                                    |
| Torsional stress                  |                | ± 180 °/m                                                       |
| <b>Material</b>                   |                |                                                                 |
| PWIS free                         |                | yes                                                             |
| Halogen-free                      |                | yes                                                             |
| Plug connector                    |                |                                                                 |
| Screw connection                  |                | Zinc diecast, nickel-plated                                     |
| Body                              |                | TPU, black                                                      |
| Contact surface                   |                | Au                                                              |

Release date: 2023-05-04 Date of issue: 2023-05-04 Filename: 285720\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.comUSA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.comGermany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.comSingapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com
 **PEPPERL+FUCHS**

Technical Data

|                              |                        |
|------------------------------|------------------------|
| Flammability                 | V-2                    |
| Cable                        |                        |
| Sheathing                    | PUR based on polyether |
| Core insulation              | PP                     |
| UV resistance                | yes                    |
| Chemical resistance          | good                   |
| Oil resistance               | yes                    |
| Cooling lubricant resistance | yes                    |
| Microbial resistance         | yes                    |
| Hydrolysis resistance        | yes                    |
| Flammability                 | FT2                    |

Connection Assignment

