

- 5 mm non-flush
- 3-wire DC
- Flat housing
- Mounting slots for cable ties
- Thru-holes for screw mounting

[illegible]

Technical Data

Switching function		Normally open (NO)
Output type		NPN
Rated operating distance	s_n	5 mm
Installation		non-flush
Output polarity		DC
Assured operating distance	s_a	0 ... 3.5 mm
Output type		3-wire

Installation conditions		
B		0 mm
C		10 mm
F		20 mm / 50 mm
Operating voltage	U _B	10 ... 30 V DC
Switching frequency	f	0 ... 10 Hz
Hysteresis	H	1 ... 10 % typ. 5 %

Technical Data

Reverse polarity protection		reverse polarity protected
Short-circuit protection		pulsing
Voltage drop	U_d	$\leq 2 \text{ V}$
Operating current	I_L	0 ... 100 mA
Lowest operating current	I_m	0 mA
Off-state current	I_r	0 ... 0.5 mA typ. 0.01 mA
Off-state current $T_U = 40^\circ\text{C}$, switching element off		$\leq 100 \mu\text{A}$
No-load supply current	I_0	$\leq 15 \text{ mA}$
Time delay before availability	t_v	$\leq 50 \text{ ms}$
Switching state indicator		LED, yellow

Compliance with standards and directives

Standard conformity		
Standards		EN IEC 60947-5-2

Approvals and certificates

UL approval		cULus Listed, General Purpose, Class 2 Power Source
CCC approval		CCC approval / marking not required for products rated $\leq 36 \text{ V}$


Ambient conditions

Ambient temperature		$-25 \dots 70^\circ\text{C}$ ($-13 \dots 158^\circ\text{F}$)
Storage temperature		$-40 \dots 85^\circ\text{C}$ ($-40 \dots 185^\circ\text{F}$)


Mechanical specifications

Connection type		fixed cable with plug
Housing material		PBT
Sensing face		PBT
Degree of protection		IP67
Connector		
Number of pins		3
Connection assembly		Molex connector 43025-0400 Molex contact 43030-0005
Cable		
Cable diameter		$3.5 \text{ mm} \pm 0.2 \text{ mm}$
Bending radius		$> 10 \times \text{cable diameter}$
Material		PVC
Color		grey
Number of cores		3
Core cross section		0.14 mm^2
Length	L	600 mm
Dimensions		
Height		20 mm
Width		50 mm
Length		5 mm

Connection



Installation Conditions



Release date: 2024-12-10 Date of issue: 2024-12-10 Filename: 286690_eng.pdf