




Cable Glands, Metal, for non-armored Cables

CG.NA.NPT1-1/4S.BN.C.20.K01


- For cables without armor
- Brass nickel-plated
- Thread NPT 1-1/4"
- Seal chloroprene
- Ex db, Ex eb and Ex tb certified
- Suitable for operation in Zone 1, Zone 2, Zone 21 and Zone 22
- Suitable for operation in Class I, Zone 1/2/22
- Suitable for operation in Class I, Division 2 when installed in accordance with NEC501.10(B)(2)
- Degree of protection IP66 / IP68, UL Type 4X
- Packaging unit: 1 piece, kit with accessories



Dimensions



Dimensions



Details see data table

Legend	
1	Washer gasket (accessory)
2	O-Ring
3	Gland body basis
4	Seal insert S3
5	Seal insert S2
6	Seal insert S1
7	Cap nut
D	Clamping range, cable sheath diameter
D2	Width across corners
H	Length outside enclosure
L	Total lenght
S*	Clamping range, seal insert combinations
SW*	Width across flats
TD	Thread size
TL	Thread length

Technical Data

Mechanical specifications

Technical Data

Cable type	non-armored cables	
Clamping range (D)		22 ... 32 mm
Seal combination S1		27 ... 32 mm
Seal combination S1+S2		24 ... 27 mm
Seal combination S1+S2+S3		22 ... 24 mm
Thread type		NPT ANSI ASME B1.20.1
Thread size (TD)		NPT 1-1/4"
Degree of protection		IP66 / IP68 , UL Type 4X
Material		
Finish		inherent color silver
Cable gland		brass, nickel-plated
Washer gasket		aramid fibers bonded with NBR
O-Ring		chloroprene
Seal insert		chloroprene
Mass		
Individual component		approx. 232 g
Packing unit		approx. 278 g
Dimensions		
Width across corners (D2)		49.5 mm
Diameter thru-hole (DT)		42.2 ... 42.4 mm
Length outside enclosure (H)		42.5 mm
Width across flats (SW1)		45 mm
Width across flats (SW2)		45 mm
Thread length (TL)		20 mm
Total length (L)		62.5 mm
Tightening torque		
Nut torque at enclosure (SW1)		10 Nm
Nut torque 2 with seal S1 (SW2)		45 Nm
Nut torque 2 with seals S1+S2 (SW2)		50 Nm
Nut torque 2 with seals S1+S2+S3 (SW2)		56 Nm
Ambient conditions		
Ambient temperature		-40 ... 80 °C (-40 ... 176 °F) washer gasket -40 ... 80 °C (-40 ... 176 °F)
Data for application in connection with hazardous areas		
EU-type examination certificate		IMQ 14 ATEX 012X
Marking		Ex II 2 GD Ex db IIC Gb Ex eb IIC Gb Ex tb IIIC Db
International approvals		
UL approval		
cULus		E490324 tested to UL 514B E490962 tested to UL 2225 CSA 60079-7 , CSA 60079-31
IECEx approval		IECEx IMQ 14.0004X
UKCA approval		CML 21 UKEX 11380X
INMETRO approval		DNV 20.0029 X
CCC approval		2021312313000344
Conformity		
Degree of protection		EN 60529
General information		
Delivery quantity		1
Scope of delivery		Cable gland shroud PVC Brief instructions

Technical Data

Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperl-fuchs.com .
Accessories	
Sealing plugs	BP.NA.M32-M40S.PA

Release date: 2023-10-17 Date of issue: 2023-10-17 Filename: 291385_eng.pdf