




Control Unit Ex e, GRP, 2 Functions LCP2.PGMX.JRMX.F.1

- Pushbutton green - 1x NO / 1x NC - labeling 'I'
- Key-release emergency mushroom button, red - 1x NO / 1x NC
- Glass-fiber reinforced polyester (GRP) enclosure
- Ex de and Ex tb certified
- Bottom face cable gland polyamide, 1x M25
- Installation in Zone 1, Zone 2, Zone 21 and Zone 22
- Degree of protection IP66




Connection

	11	23
0	X	
I		X
	12	24



Dimensions



Dimension values see data table.
Image and drawing are generic for this device type and may deviate from the specific variant.

Legend	
A	Height
B	Width
C	Depth
C1	Depth with operating element
G	Mounting holes distance, vertical
H	Mounting holes distance, horizontal
J	Mounting holes diameter
K	Maximum external dimension with mounting brackets
[A] ... [B]	Cable entry faces

Technical Data

Electrical specifications	
Operating voltage	250 V max.
Operating current	16 A max.
Terminal capacity	2.5 mm ²
Function	push button
Color	green
Contact configuration	1x NO / 1x NC all NC contacts have a direct opening action for emergency stop functions

Technical Data

Usage category	AC12 - 12 ... 250 V AC - 16 A AC15 - 12 ... 250 V AC - 10 A DC13 - 12 ... 110 V DC - 1 A DC13 - 12 ... 24 V DC - 1A	
Number of poles		2
Labeling		I
Function 2		mushroom button
Color		red
Contact configuration		1x NO / 1x NC all NC contacts have a direct opening action for emergency stop functions
Usage category	AC12 - 12 ... 250 V AC - 16 A AC15 - 12 ... 250 V AC - 10 A DC13 - 12 ... 110 V DC - 1 A DC13 - 12 ... 24 V DC - 1A	
Number of poles		2
Operator action		latching , key release
Lockable		yes
Mechanical specifications		
Enclosure range		LCP
Enclosure cover		fully detachable
Cover fixing		stainless steel socket cap head screws
Screws		M6
Number		4
Tightening torque		2 Nm
Degree of protection		IP66
Cable entry face B		
M25 quantity		1
M25 series		Cable Glands, Plastic
M25 type		CG.PEDS1.M25.*
M25 clamping range		10 ... 18 mm
Defined entry area		face B
Material		
Enclosure		carbon loaded, antistatic glass-fiber reinforced polyester (GRP)
Finish		inherent color black
Seal		one piece closed cell silicone
Mass		3 kg
Dimensions		
Height (A)		220 mm
Width (B)		110 mm
Depth (C)		101 mm
External dimension with operating element (C1)		133 mm
Mounting holes distance (G)		220 mm
Mounting holes distance (H)		78 mm
Mounting holes diameter (J)		7 mm
Maximum external dimension (K)		235 mm
Tightening torque		
Nut torque at enclosure (SW1)		see datasheets of cable glands
Grounding		2.5 mm ² grounding terminal
Ambient conditions		
Ambient temperature		-40 ... 55 °C (-40 ... 131 °F) @ T4 -40 ... 40 °C (-40 ... 104 °F) @ T6
Data for application in connection with hazardous areas		
EU-type examination certificate		CML 16 ATEX 3009X

Release date: 2023-10-04 Date of issue: 2023-10-04 Filename: 293242_eng.pdf

Technical Data

Marking		II 2 GD Ex db eb mb IIC T* Gb Ex tb IIC T** °C Db T6/T80 °C @ Ta +40 °C T4/T130 °C @ Ta +55 °C
International approvals		
IECEX approval		IECEX CML 16.0008X
UKCA approval		CML 22 UKEX 2550X
Further approvals		on request: CCC, ECAS, IA
Conformity		
Degree of protection		EN 60529
Usage category		IEC / EN 60947
CE marking		0080 or 0102, see type label
General information		
Supplementary information		EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperl-fuchs.com .
Accessories		
Optional accessories		engraved traffolyte tag label engraved AISI 316L stainless steel tag label color in-fill stainless steel tag label