

# Docking station IQZ-HH27-CHARGER1



Docking station for IQT1-HH27 and IPT-HH27

CE

## Function

The docking station QZ-HH27-CHARGER1 enables you to connect the IQT1-HH27 and IPT-HH27 handhelds to a PC via USB or Ethernet. The docking station is also able to charge the handhelds when a battery is inserted.

## Technical Data

### Indicators/operating means

LED red/green	Power: green/off Charge: green/red Connect: green/off
---------------	---

### Input

Input voltage	100 V AC ... 240 V AC 47 ... 63 Hz
---------------	---------------------------------------

Input current	max. 1 A
---------------	----------

### Output

Output rated operating current	2.6 A
--------------------------------	-------

Output voltage	15 V DC
----------------	---------

### Approvals and certificates

CE conformity	CE
---------------	----

### Ambient conditions

Ambient temperature	0 ... 45 °C (32 ... 113 °F)
---------------------	-----------------------------

Storage temperature	-20 ... 70 °C (-4 ... 158 °F)
---------------------	-------------------------------

### Mechanical specifications

Connection	USB (type A and B) and LAN (RJ45)
------------	-----------------------------------

Mass	785 g
------	-------

Dimensions	122 mm x 125 mm x 127 mm
------------	--------------------------

Note	No option to charge a spare battery available Power supply (EU, US) and USB cable included in the scope of delivery
------	--

## Matching system components

	<b>IPT-HH27</b>	Handheld (125 kHz)
	<b>IQT1-HH27</b>	Handheld (13.56 MHz)