



Fieldbus module ICE1-8DI8DO-G60L-V1D

- Multiprotocol-compatible
- M12 power connector
- Sturdy metallic housing
- Web-based configuration

Ethernet IO module with 8 digital inputs/outputs



Function


The ICE1-8DI8DO-G60L-V1D is a multiprotocol fieldbus module with 8 digital inputs and 8 digital outputs. The G60L design in fully cast metal housing is resistant to mechanical damage and environmental influences. The G60L has protection class IP65/IP67.

The fieldbus module serves as an interface between the controller of a fieldbus system and the field level. Thanks to its multiprotocol capability, the fieldbus module supports the Ethernet communication protocols PROFINET, EtherNet/IP, and EtherCAT.

An L-coded M12 connector plug used for supplying power enables a current rating of up to 2 x 16 A. The inputs and outputs are equipped with A-coded M12 connector plugs. Connection to the fieldbus is achieved using a D-coded M12 connector plug.

The communication protocols are configured either manually via a rotary switch or automatically. The diagnostics display status information for each channel via LEDs. An integrated web server enables access to the fieldbus module. Information regarding the status of the module is also displayed and network parameters such as the IP address and subnet mask can be configured.

Dimensions



Release date: 2023-02-22 Date of issue: 2023-02-22 Filename: 295312_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data


General specifications			
UL File Number		E223772	
Indicators/operating means			
LED indication		see manual	
Rotary switch		Setting the fieldbus protocol	
Electrical specifications			
Rated operating voltage	U _e	18 ... 30 V	
Nominal voltage		24 V DC	
Current consumption		120 mA	
Current loading capacity		Max. 2 x 16 A per module (Loop-through current via L-coded power supply) Total current: max. 9 A per module	
Galvanic isolation		between U _S and U _L	
Interface 1			
Interface type		Industrial Ethernet	
Physical		M12, D-coded	
Protocol		PROFINET IO with media redundancy protocol (MRP) EtherNet/IP with Device Level Ring (DLR) EtherCAT	
Transfer rate		10/100 Mbps	
Inputs/Outputs			
Number/Type		8 digital inputs (X1 – X4), 8 digital outputs (X5 – X8) Inputs: 2-, 3-, 4-wire PNP, DC, supply from U _S Outputs: 2-, 3-, 4-wire, PNP, DC, supply from U _L Short-circuit protected	
Sensor supply		max. 200 mA Per port (X1 – X4) via U _S	
Output rated operating current	I _e	max. 2 A per channel / 4 A Per port (X5 – X8) via U _L	
Directive conformity			
Electromagnetic compatibility			
Directive 2014/30/EU		EN 61000-6-2:2005, EN 61000-6-4:2007+A1:2011	
Standard conformity			
Degree of protection		EN 60529:2000	
Emitted interference		EN 61000-6-4:2007+A1:2011	
Noise immunity		EN 61000-6-2:2005	
Shock resistance		EN 61131-2:2004	
Ambient conditions			
Ambient temperature		-20 ... 70 °C (-4 ... 158 °F)	
Storage temperature		-40 ... 70 °C (-40 ... 158 °F)	
Cold start temperature		-40 °C (-40 °F)	
Relative humidity		max. 95 %	
Altitude		0 ... 2000 m	
Shock and impact resistance		50 g, 11 ms, all axes	
Vibration resistance		15 g at 5 - 500 Hz	
Pollution degree		3	
Mechanical specifications			
Contact elements		PA	
Degree of protection		IP65/IP67/IP69K	
Connection		Power Supply M12, L-coded Fieldbus M12, D-coded Inputs/Outputs M12, A-coded	
Material			
Contacts		CuSn, gold-plated CuNi, gold-plated	
Housing		Diecast zinc	
Seal		FKM	
Mass		500 g	
Tightening torque, fastening screws		1 Nm	

Release date: 2023-02-22 Date of issue: 2023-02-22 Filename: 295312_eng.pdf


Technical Data

Tightening torque, cable gland	0.6 Nm
Construction type	Field housing
Tightening torque of clamping screws	0.5 Nm

Connection



Assembly



Accessories

	V15L-G-2M-PUR-U-V15L-G	Cordset M12 socket straight to M12 plug straight L-coded, 5-pin, PUR cable grey, UL approved
	V15L-G-5M-PUR-U	Female cordset single-ended M12 straight L-coded, 5-pin, PUR cable grey, UL approved

Release date: 2023-02-22 Date of issue: 2023-02-22 Filename: 295312_eng.pdf

Accessories

	V15L-G-BK	Female connector M12 straight L-coded 5-pin, for cable diameter 8 - 13 mm, field-attachable
	V1SD-G-GN2M-PUR-E1S-V45-G	Ethernet bus cable M12 plug straight D-coded to RJ45 Ethernet-coded, 4-pin, PUR cable green, Cat5e, shielded, drag chain suitable
	V1SD-G-GN2M-PUR-E1S-V1D-G	Ethernet bus cable M12 plug straight to M12 plug straight D-coded, 4-pin, PUR cable green, Cat5e, shielded, UL approved, drag chain suitable
	V1SD-G-ABG-PG9	Male connector M12 straight D-coded 4-pin, for cable diameter 5 - 8 mm, shielded, field-attachable
	V1S-T-V1	Y-Splitter M12 plug 5-pin to 2x M12 socket 4-pin A-coded
	V1-G-BK1M-PUR-A-T-V1-G	Y connection cable M12 plug straight A-coded 4-pin to 2x M12 socket straight A-coded 4-pin, 2x PUR cable weld spatter resistant black, UL approved, drag chain suitable, torsion resistant
	V1S-G-PG9	Male connector M12 straight A-coded 4-pin, for cable diameter 6 - 8 mm, field-attachable
	VAZ-V1-B3L	Blind plug for M12 sockets
	MH V1-SCREWDRIVER	Torque screwdriver (0.6 Nm)
	MH V1-BIT M12	plug-in cap M12