

# Inductive sensor


## NBB2-8GS35-E2-V3



- 2 mm flush
- Increased operating distance
- Stainless steel version
- Extended temperature range  
-40 ... +85 °C



### Dimensions



### Technical Data

| General specifications              |                |                                                                           |
|-------------------------------------|----------------|---------------------------------------------------------------------------|
| Switching function                  |                | Normally open (NO)                                                        |
| Output type                         |                | PNP                                                                       |
| Rated operating distance            | s <sub>n</sub> | 2 mm                                                                      |
| Installation                        |                | flush                                                                     |
| Output polarity                     |                | DC                                                                        |
| Assured operating distance          | s <sub>a</sub> | 0 ... 1.62 mm                                                             |
| Actuating element                   |                | mild steel, e. g. 1.0037, SR235JR (formerly St37-2)<br>8 mm x 8 mm x 1 mm |
| Reduction factor r <sub>Al</sub>    |                | 0.2                                                                       |
| Reduction factor r <sub>Cu</sub>    |                | 0.1                                                                       |
| Reduction factor r <sub>304</sub>   |                | 0.55                                                                      |
| Reduction factor r <sub>Brass</sub> |                | 0.25                                                                      |
| Output type                         |                | 3-wire                                                                    |
| Nominal ratings                     |                |                                                                           |
| Operating voltage                   | U <sub>B</sub> | 5 ... 30 V                                                                |
| Switching frequency                 | f              | 0 ... 6000 Hz                                                             |
| Hysteresis                          | H              | typ. 5%                                                                   |
| Reverse polarity protection         |                | reverse polarity protected                                                |
| Short-circuit protection            |                | pulsing                                                                   |
| Voltage drop                        | U <sub>d</sub> | ≤ 1.5 V                                                                   |
| Operating current                   | I <sub>L</sub> | 0 ... 100 mA                                                              |

Release date: 2024-05-27 Date of issue: 2024-05-31 Filename: 304615-0084\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**


Technical Data

|                                                 |       |                                                              |
|-------------------------------------------------|-------|--------------------------------------------------------------|
| Off-state current                               | $I_r$ | 0 ... 0.2 mA                                                 |
| No-load supply current                          | $I_0$ | ≤ 10 mA                                                      |
| Time delay before availability                  | $t_v$ | ≤ 100 ms                                                     |
| Switching state indicator                       |       | Multihole-LED, yellow                                        |
| <b>Functional safety related parameters</b>     |       |                                                              |
| MTTF <sub>d</sub>                               |       | 960 a                                                        |
| Mission Time (T <sub>M</sub> )                  |       | 20 a                                                         |
| Diagnostic Coverage (DC)                        |       | 0 %                                                          |
| <b>Compliance with standards and directives</b> |       |                                                              |
| Standard conformity                             |       |                                                              |
| Standards                                       |       | EN IEC 60947-5-2                                             |
| <b>Approvals and certificates</b>               |       |                                                              |
| UL approval                                     |       | cULus Listed, General Purpose, Class 2 Power Source          |
| CCC approval                                    |       | CCC approval / marking not required for products rated ≤36 V |
| <b>Ambient conditions</b>                       |       |                                                              |
| Ambient temperature                             |       | -40 ... 85 °C (-40 ... 185 °F)                               |
| Storage temperature                             |       | -40 ... 85 °C (-40 ... 185 °F)                               |
| <b>Mechanical specifications</b>                |       |                                                              |
| Connection type                                 |       | Connector plug M8 x 1 , 3-pin                                |
| Housing material                                |       | Stainless steel 1.4305 / AISI 303                            |
| Sensing face                                    |       | LCP                                                          |
| Degree of protection                            |       | IP65 / IP66 / IP67                                           |
| <b>Dimensions</b>                               |       |                                                              |
| Length                                          |       | 50 mm                                                        |
| Diameter                                        |       | 8 mm                                                         |
| <b>General information</b>                      |       |                                                              |
| Scope of delivery                               |       | 2 hex nuts included                                          |

Connection



Connection Assignment



Release date: 2024-05-27 Date of issue: 2024-05-31 Filename: 304615-0084\_eng.pdf

Connection Assignment

Wire colors in accordance with EN 60947-5-2

|   |    |         |
|---|----|---------|
| 1 | BN | (brown) |
| 3 | BU | (blue)  |
| 4 | BK | (black) |

Release date: 2024-05-27 Date of issue: 2024-05-31 Filename: 304615-0084\_eng.pdf