


Capacitive sensor


CJ10-30GM-WS



- 10 mm non-flush
- The switching distance can be set over a wide range with the potentiometer



Dimensions



Technical Data

General specifications		
Switching function		Normally open (NO)
Output type		Two-wire
Rated operating distance	s_n	10 mm
Installation		non-flush
Output polarity		AC
Assured operating distance	s_a	0 ... 7.2 mm
Output type		2-wire
Nominal ratings		
Installation conditions		
A		0 mm
B		0 mm
C		30 mm
F		50 mm
Operating voltage	U_B	20 ... 253 V AC ¹⁾
Switching frequency	f	0 ... 10 Hz
Hysteresis	H	2 ... 10 % typ. 5 %

Release date: 2025-02-27 Date of issue: 2025-02-27 Filename: 037645_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Reverse polarity protection	reverse polarity tolerant	
Voltage drop at I _L		
Voltage drop I _L = 100 mA, switching element on	U _d	typ. 7 V
Momentary current (20 ms, 0.1 Hz)		0 ... 1200 mA
Rated insulation voltage	U _{BIS}	1500 V
Operating current	I _L	5 ... 200 mA
Lowest operating current	I _m	5 mA
Off-state current	I _r	0.7 ... 1.5 mA typ.
Time delay before availability	t _v	≤ 300 ms
Switching state indicator		LED, yellow
Indicators/operating means		
Potentiometer		sensitivity adjustment
Compliance with standards and directives		
Standard conformity		
Standards	EN IEC 60947-5-2	
Approvals and certificates		
UL approval	cULus Listed, General Purpose	
CCC approval		Certified by China Compulsory Certification (CCC)
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Storage temperature		-25 ... 85 °C (-13 ... 185 °F)
Mechanical specifications		
Connection type	cable	
Housing material		Stainless steel 1.4305 / AISI 303
Sensing face	PBT	
Degree of protection		IP67
Cable		
Wire end ferrules		yes
Cable diameter	6.4 mm ± 0.2 mm	
Bending radius		> 10 x cable diameter
Material	PVC	
Color		grey
Number of cores	3	
Core cross section		0.75 mm ²
Length	L	2 m
Dimensions		
Length	80 mm	
Diameter		30 mm
Note	1) In the temperature range below 0 °C, permissible operating voltage U _b 80...253 V Safety fuse ≤ 0.8 A (quick-blow) according to IEC 60127-2 Sheet 1 Recommendation: after a short circuit, check that the device is functioning correctly.	

Connection



Installation Conditions