


# Active infrared scanner

## TOPSCAN2-8-HS-2500-2/L750/38a



- Moving presence sensor for swing doors
- Configurable for a wide range of door leaf widths
- Each beam can be adjusted individually
- Selectable background suppression and evaluation
- Beam adjustment to closing edge width
- Test input
- Double-beam version


Single or multi-beam light curtain for individual protection



### Function

The TopScan2 series is a modular sensor system that can be used in a flexible manner for various requirements relating to the monitoring of automatic doors. The system can be mounted for either static or mobile use. The housing can be easily shortened and up to five sensor modules can be arranged side by side, whereby each beam can be configured individually. When it comes to the operating modes, there is the choice between background suppression and background evaluation. The light or dark switching modes, detection range and closing edge alignment can also be adjusted. These features make the TopScan2 active infrared scanner ideal for use with a wide range of automatic door systems.

### Dimensions



### Technical Data

#### General specifications

|                                   |                                                                                          |
|-----------------------------------|------------------------------------------------------------------------------------------|
| Detection range min.              | 0 ... 1500 mm by background evaluation,<br>500 ... 1500 mm by background suppression     |
| Detection range max.              | 0 ... 2500 mm with background evaluation,<br>500 ... 2500 mm with background suppression |
| Light source                      | IRED                                                                                     |
| Black-white difference (6 %/90 %) | < 20 % at 2000 mm sensor range                                                           |
| Marking                           | CE                                                                                       |
| Number of beams                   | 2 (number of built-in sensor modules AIR)                                                |
| Operating mode                    | switching between background suppression/evaluation                                      |
| Diameter of the light spot        | 75 x 75 mm by sensing range 2000 mm                                                      |

#### Indicators/operating means

Release date: 2024-07-19 Date of issue: 2024-07-19 Filename: 418036\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS


## Technical Data

|                                                 |       |                                                                                                                                                                                              |
|-------------------------------------------------|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Function indicator                              |       | LED red                                                                                                                                                                                      |
| Control elements                                |       | Sensing range adjuster, light-on/dark-on changeover switch, changeover switch for mode of operation Background suppression / Background evaluation ; Adjuster for edge monitoring left/right |
| Factory setting                                 |       | Background suppression                                                                                                                                                                       |
| <b>Electrical specifications</b>                |       |                                                                                                                                                                                              |
| Operating voltage                               | $U_B$ | 17 ... 30 V DC , 18 ... 28 V AC                                                                                                                                                              |
| No-load supply current                          | $I_0$ | < 100 mA                                                                                                                                                                                     |
| <b>Input</b>                                    |       |                                                                                                                                                                                              |
| Test input                                      |       | emitter deactivation with $U = 17 \dots 30$ V DC only in background evaluation mode of operation and DC operation                                                                            |
| <b>Output</b>                                   |       |                                                                                                                                                                                              |
| Switching type                                  |       | Light-on/dark-on changeover switch                                                                                                                                                           |
| Signal output                                   |       | Relay, 1 alternator                                                                                                                                                                          |
| Switching voltage                               |       | max. 24 V DC , 48 V AC                                                                                                                                                                       |
| Switching current                               |       | $\leq 1$ A                                                                                                                                                                                   |
| Switching power                                 |       | 24 W / 55 VA                                                                                                                                                                                 |
| Response time                                   |       | 30 ms , 2 s after test                                                                                                                                                                       |
| <b>Compliance with standards and directives</b> |       |                                                                                                                                                                                              |
| Standard conformity                             |       |                                                                                                                                                                                              |
| Standards                                       |       | EN 61000-6-2, EN 61000-6-3                                                                                                                                                                   |
| <b>Approvals and certificates</b>               |       |                                                                                                                                                                                              |
| CCC approval                                    |       | CCC approval / marking not required for products rated $\leq 36$ V                                                                                                                           |
| UN/ECE Regulation No. 10 (E1)                   |       | Type-approval number: 047349                                                                                                                                                                 |
| <b>Ambient conditions</b>                       |       |                                                                                                                                                                                              |
| Ambient temperature                             |       | -20 ... 60 °C (-4 ... 140 °F)                                                                                                                                                                |
| <b>Mechanical specifications</b>                |       |                                                                                                                                                                                              |
| Housing length L                                |       | 750 mm                                                                                                                                                                                       |
| Mounting height                                 |       | max. 2500                                                                                                                                                                                    |
| Degree of protection                            |       | IP52                                                                                                                                                                                         |
| Connection                                      |       | screw terminals                                                                                                                                                                              |
| Material                                        |       |                                                                                                                                                                                              |
| Housing                                         |       | aluminum / ABS                                                                                                                                                                               |
| Optical face                                    |       | PC                                                                                                                                                                                           |
| Mass                                            |       | approx. 500 g                                                                                                                                                                                |
| Dimensions                                      |       |                                                                                                                                                                                              |
| Height                                          |       | 42 mm                                                                                                                                                                                        |
| Depth                                           |       | 37 mm                                                                                                                                                                                        |
| Length                                          |       | 750 mm                                                                                                                                                                                       |


Connection Assignment



Assembly






Characteristic Curve




Release date: 2024-07-19 Date of issue: 2024-07-19 Filename: 418036\_eng.pdf

Characteristic Curve



Release date: 2024-07-19 Date of issue: 2024-07-19 Filename: 418036\_eng.pdf


Application



Release date: 2024-07-19 Date of issue: 2024-07-19 Filename: 418036\_eng.pdf

## Configuration information

### Configuring the Monitoring Edge




The transmitter of each sensor features two beam position settings via which the monitoring edge can be aligned to the left or to the right.

#### Detection range setting:


1. Rotate the adjustment screw counter-clockwise until the LED illuminates
2. Slowly rotate the adjustment screw clockwise until the LED goes out
3. Then rotate the adjustment screw further by 1/8 of a rotation

 shorter  
 longer  
 switch approx. 15 cm ... 20 cm  
 above ground



#### Angle settings:

By rotating the sensor around its rotational axis (1), the offset (2) of the detection point to the wall can be easily changed. The angle setting can be continuously adjusted from 0° to 30°.



#### Programming:

Both the switching mode and the operating mode can be configured via the programming switch for each sensor.

Test input (TE) — background suppression operating mode

| TE     | Switching mode | LED                 | Signal output |
|--------|----------------|---------------------|---------------|
| Active | Light          | Does not illuminate | Closed        |
| Active | Dark           | Does not illuminate | Open          |

Note: only if there is an object in the detection area

Test input (TE) — background evaluation operating mode

| TE     | Switching mode | LED         | Signal output |
|--------|----------------|-------------|---------------|
| Active | Light          | Illuminates | Open          |
| Active | Dark           | Illuminates | Closed        |

Note: Regardless of whether or not there is an object in the detection area

#### Light On Switching Mode (H)

A light scanner's output is switched on (activated) if the receiver detects "light", i.e. there is an object in the operating range.

#### Dark On Switching Mode (D)

A light scanner's output is switched on (activated) if the receiver detects "dark", i.e. there is no object in the operating range.

Programming switch

|     | Left (1)               | Right (2) |
|-----|------------------------|-----------|
| Off | Background suppression | Dark on   |
| On  | Background evaluation  | Light on  |

## Function Principle

The two large-area lenses (one for the infrared transmitter and one for the two photodiode receivers with ambient light filter) have an optical center-to-center distance of approx. 150 mm, resulting in a light spot size of 75 mm x 75 mm. The angle of the two lens systems can be adjusted to each other via a precision gear according to the principle of background/foreground suppression. Such precisely defined focal lengths enable a precision detection range setting of up to 2500 mm.

The detection range can be extended up to 2500 mm and responds to any object in the detection area, with minimal effect from the surface color and structure. Reflection levels that exceed the specified maximum detection range are not detected by the sensor, even with highly reflective objects — for example corrugated aluminum plates or marble floors (with background suppression). The detection fields of several devices can be overlapped without interference.

#### Background Suppression Operating Mode

In this operating mode, the background is "detected" but not actually evaluated (ignored). A reflection signal from an object within the specified detection area is required as a switching signal.

#### Background Evaluation Operating Mode

The TopScan2 can also be used with a test option, regardless of whether or not there is an object/person in the detection area. The receiver constantly sees the reflected light from the transmitter when the background is present. Testing is performed by disconnecting the transmitter from the supply voltage.

The background is used as a reflector. If the light beam is broken by an object, a switching signal is triggered.

## Application

- Protection mechanism for closing edges on automatic sliding doors and revolving doors
- Anti-collision protection for people/objects in the vicinity of revolving doors
- Edge and pinch protection for sliding doors
- Entry monitoring for buses and trains operated within the public transportation network