

## Connection cable

### V1-W-YE10M-PVC-U-V1-G




- Degree of protection IP68 / IP69
- UL listed for USA and Canada
- Specific design protects against loosening and inaccurate installation

Cordset M12 socket angled to M12 plug straight A-coded, 4-pin, PVC cable yellow, UL approved



## Dimensions



## Technical Data

### General specifications

|                           |       |                                     |
|---------------------------|-------|-------------------------------------|
| Connector 1               |       |                                     |
| Connection                |       | socket                              |
| Construction type         |       | M12                                 |
| Style                     |       | angled                              |
| Locking                   |       | screw connection                    |
| Number of pins            |       | 4                                   |
| Coding                    |       | A-coded                             |
| Connector 2               |       |                                     |
| Connection                |       | plug                                |
| Construction type         |       | M12                                 |
| Style                     |       | straight                            |
| Locking                   |       | screw connection                    |
| Number of pins            |       | 4                                   |
| Coding                    |       | A-coded                             |
| Electrical specifications |       |                                     |
| Operating voltage         | $U_B$ | max. 250 V AC/DC                    |
| Operating current         | $I_B$ | max. 4 A                            |
| Conformity                |       |                                     |
| Degree of protection      |       | EN 60529                            |
| Plug connection           |       | connector M12 x 1 : IEC 61076-2-101 |

Release date: 2023-07-13 Date of issue: 2023-07-13 Filename: 456603\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com




Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

## Technical Data

|                            |   |                                                                 |
|----------------------------|---|-----------------------------------------------------------------|
| Flammability               |   | UL 1581 , IEC 60332-1-2                                         |
| Approvals and certificates |   |                                                                 |
| UL approval                |   | AWM STYLE 2095 AWM I/II A/B 80°C 300V FT1 (cable)               |
| UL File Number             |   | E231213                                                         |
| Ambient conditions         |   |                                                                 |
| Ambient temperature        |   |                                                                 |
| Plug connector             |   | -40 ... 90 °C (-40 ... 194 °F)                                  |
| Cable, fixed               |   | -25 ... 80 °C (-13 ... 176 °F)                                  |
| Cable, flexing             |   | -5 ... 80 °C (23 ... 176 °F)                                    |
| Pollution degree           |   | 3                                                               |
| Mechanical specifications  |   |                                                                 |
| Plug connector             |   |                                                                 |
| Tightening torque          |   | 0.6 Nm                                                          |
| Loosening protection       |   | available                                                       |
| Tool installation          |   | straight knurling and hexagon nut SW = 14 mm                    |
| Mating cycles              |   | min. 100                                                        |
| Degree of protection       |   | IP68 / IP69                                                     |
| Cable                      |   | according to IEC/EN 60228 (DIN VDE 0295) class 5                |
| Sheath diameter            |   | 4.3 mm                                                          |
| Bending radius             |   | > 15 x cable diameter, moving<br>> 5 x cable diameter, fixed    |
| Sheath stripping force     |   | max. 50 N / 300 mm                                              |
| Sheath color               |   | yellow (similar to RAL 1021)                                    |
| Number of cores            |   | 4                                                               |
| Core cross section         |   | 0.34 mm²                                                        |
| Cores color                |   | Core 1: brown<br>Core 2: white<br>Core 3: blue<br>Core 4: black |
| Core construction          |   | 19 x 0.15 mm Ø                                                  |
| Length                     | L | 10 m                                                            |
| Cable code                 |   | Li YY 4 x 0,34                                                  |
| Material                   |   |                                                                 |
| Plug connector             |   |                                                                 |
| Screw connection           |   | Zinc diecast, nickel-plated                                     |
| Body                       |   | TPU, black                                                      |
| Seal                       |   | FKM                                                             |
| Contact surface            |   | gold plated (Au)                                                |
| Flammability               |   | V-2                                                             |
| Cable                      |   |                                                                 |
| Sheathing                  |   | PVC                                                             |
| Core insulation            |   | PVC                                                             |
| Flammability               |   | FT1                                                             |

## Connection



## Accessories

|                                                                                   |                              |                                                  |
|-----------------------------------------------------------------------------------|------------------------------|--------------------------------------------------|
|  | <b>MH V1-SCREWDRIVER</b>     | Torque screwdriver (0.6 Nm)                      |
|  | <b>MH V1-BIT M12</b>         | plug-in cap M12                                  |
|  | <b>V1/V3-LABELHOLDER</b>     | Label holder                                     |
|  | <b>V1/V3-LABEL</b>           | Label plate                                      |
|  | <b>MH V1-Holder</b>          | Modular universal holder for M12 connectors      |
|  | <b>V1-CLIP</b>               | Unlocking protector for M12 connector            |
|  | <b>V1-MARKING-RING-COLOR</b> | Marking rings for M12 connectors, various colors |