




IO-Link master ICE3-8IOL-G65L-V1D

- PROFINET IO, Modbus/TCP and OPC UA Support
- Web-based configuration of module and IO-Link devices
- Integrated IODD storage for more than 100 IODDs
- Downloadable module configuration
- M12 L-coded power connector


PROFINET IO IO-Link master with 8 inputs/outputs



Function

The module is a PROFINET IO fieldbus module with 8 type A IO-Link master ports according to IO-Link standard V1.1. The fieldbus module serves as an interface between the controller of a PROFINET IO fieldbus system and IO-Link devices in the field level. The integrated web server and IODD interpreter enabling complete configuration of the fieldbus module and attached IO-Link devices without the need for special software tools. Information regarding the status of the module is also displayed and network parameters such as the IP address and subnet mask can be configured. The module is capable of storing all configuration enabling stand-alone usage without a higher-level PLC. MultiLink simultaneously provides data access via different communication protocols like PROFINET IO, Modbus/TCP and OPC UA to multiple controllers. An L-coded M12 connector plug used for supplying power enables a current rating of up to 2 x 16 A. The inputs and outputs are equipped with A-coded M12 connector plugs. Connection to the fieldbus is achieved using a D-coded M12 connector plug. Status information for each channel is displayed via LEDs as a diagnostic function.

Dimensions



Release date: 2024-06-08 Date of issue: 2024-06-08 Filename: 70104876_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

General specifications			
UL File Number		E360395	
Indicators/operating means			
LED indication		see manual	
Rotary switch		Setting the IP address	
Electrical specifications			
Rated operating voltage	U _e	20 ... 30 V DC	
Nominal voltage		24 V DC	
Current consumption		typ. 120 mA	
Current loading capacity		Max. 2 x 16 A per module (Loop-through current via L-coded power supply) Total current: max. 6.7 A per module	
Galvanic isolation		between US and UA	
Interface 1			
Interface type		Industrial Ethernet	
Physical		M12, D-coded	
Protocol		PROFINET IO with media redundancy protocol (MRP) + Modbus TCP + OPC UA + MQTT Modbus max PDI: 33 times / sec OPC UA max PDI update rate: 20 times / sec MQTT max PDI update rate: 10 times / sec	
Transfer rate		10/100 Mbps	
Inputs/Outputs			
Number/Type		8 x IO-Link Class A (X1 – X8) Configurable as: Max. 8 IO-Link and 8 digital inputs Max. 16 digital inputs Max. 8 digital inputs and 8 digital outputs short-circuit protected	
Sensor supply		Port 1: max. 1.6 A Via L+ (pin 1) Port 3: max. 1 A via L+ (pin 1) Ports 2 and 4 – 8: max. 500 mA per port via L+ (pin 1)	
Output current	I _e	max. 200 mA Per port via C/Q (pin 4)	
Directive conformity			
Electromagnetic compatibility			
Directive 2014/30/EU		EN 61000-6-2 , EN 61000-6-4	
Standard conformity			
Degree of protection		EN 60529	
Fieldbus standard		Type 1 according to IEC 61131-2, EN 61131-9	
Electrical safety		CSA C22.2 No. 61010-1-12 UL 61010-1, IEC 61010-2-201	
Emitted interference		EN 61000-6-4, FCC Part 15 Subpart B, ICES-001, AS/NZS CISPR 11	
Noise immunity		EN 61000-6-2 , EN 61131-2 , EN 61131-9	
Shock resistance		EN 60068-2-27	
Ambient conditions			
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)	
Storage temperature		-40 ... 85 °C (-40 ... 185 °F)	
Relative humidity		max. 95 %	
Altitude		0 ... 2000 m	
Shock and impact resistance		15g, 11ms, half-sine	
Mechanical specifications			
Degree of protection		IP67	
Connection		Power Supply M12, L-coded Fieldbus M12, D-coded Inputs/Outputs M12, A-coded	
Material			
Housing		Molded Polyamide 66	
Mass		454 g	
Tightening torque, fastening screws		8 Nm	

Release date: 2024-06-08 Date of issue: 2024-06-08 Filename: 70104876_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**


Technical Data

Tightening torque, cable gland	0.6 Nm
Dimensions	
Height	212 mm
Width	65 mm
Length	29.8 mm
Construction type	Field housing

Connection



Assembly



Release date: 2024-06-08 Date of issue: 2024-06-08 Filename: 70104876_eng.pdf