

Serial Device Server

ICDM-RX/TCP-4DB9/2RJ45-PM



- Web-based configuration
- RS-232/422/485 software selectable interfaces
- NEMA TS2 Certified
- TCP/IP & UDP Socket Services
- Device drivers (Windows and Linux)
- Panel mount with DB9 serial connectors


Device Server 4-port panel mount DB9



Function

The ICDM-RX/TCP product family enables the connection of serial devices (RS-232 / RS-422 / RS-485) using a device driver (Windows or Linux) or Ethernet TCP/IP devices using socket services to an industrial Ethernet network. The integrated webserver enables complete configuration of all module parameters like serial interface, baud rate, parity, data bits, stop bits, or flow control. Products are available in different versions for DB9 or screw terminal connection.

Dimensions



Unit Height = 36.5

Technical Data

General specifications

UL File Number	E185802
MTBF	35.5 a

Indicators/operating means

LED indication	see manual
----------------	------------

Electrical specifications

Rated operating voltage	U _e	9 ... 30 V DC
Nominal voltage		24 V DC
Surge protection		15 KV / 200 A for 1 ns

Interface

Interface type	Software selectable interfaces: RS-232 , RS-422 , RS-485 (2 and 4-wire)
Physical	4 x DB9
Protocol	Raw serial
Supported baud rates	300 bps to 230Kbps

Interface 1

Interface type	Industrial Ethernet
Physical	2 x RJ45
Protocol	TCP/IP
Additional protocols	ARP, BOOTP, DHCP/RARP, HTTP, HTTPS, SSH, SSL/TLS, ICMP, RFC 1006 (ISO over TCP), SNMP (MIB-II), TCP/IP & UDP socket services, Telnet, and TFTP, and supports IP multicast data transmission
Transfer rate	10/100 Mbps

Release date: 2024-10-01 Date of issue: 2024-10-01 Filename: 70114046_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data


Directive conformity		
Electromagnetic compatibility		
Directive 2014/30/EU		EN 55032:2015+A11:2020 , EN 55035:2017/A11:2020
RoHS		EN IEC 63000:2018
Standard conformity		
Degree of protection		NEMA TS2
Electrical safety		EN 62368-1:2014-08
Emitted interference		EN 55032, FCC Part 15 Subpart B, ICES-003, AS/NZS CISPR 32
Noise immunity		EN 55035:2017/A11:2020
Ambient conditions		
Ambient temperature		-40 ... 75 °C (-40 ... 167 °F)
Storage temperature		-40 ... 85 °C (-40 ... 185 °F)
Relative humidity		max. 95 %
Altitude		0 ... 3048 m
Mechanical specifications		
Degree of protection		IP20
Connection		Power Supply: screw terminals Fieldbus: 2 x RJ45 Inputs/outputs: 4 x DB9
Material		
Housing		steel, black coated
Mass		1.5kg
Dimensions		
Height		38.1 mm
Width		160 mm
Length		275 mm
Construction type		Cabinet module
Mounting		Panel

Connection



Release date: 2024-10-01 Date of issue: 2024-10-01 Filename: 70114046_eng.pdf

Assembly



Release date: 2024-10-01 Date of issue: 2024-10-01 Filename: 70114046_eng.pdf