



Ultrasonic transducer


USI2500-27X13E-3M-V3

- Extremely compact dimensions
- Elliptic sound cone
- 3 m cable length
- Temperature range up to 80 °C (176 °F)

Ultrasonic transducer with 3 m cable, exclusively for the USi ultrasonic sensor systems



Dimensions



Technical Data

General specifications

Type	Ultrasonic transducer
------	-----------------------

Ambient conditions

Ambient temperature	-40 ... 80 °C (-40 ... 176 °F)
Storage temperature	-40 ... 85 °C (-40 ... 185 °F)

Mechanical specifications

Connection type	fixed cable with plug
Degree of protection	IP69 for the front surface , otherwise IP67
Material	
Housing	PA 6.6
Transducer	PBT , silicone
Connector	
Threading	M8 x 1
Number of pins	3
Material	PUR
Cable	
Cable diameter	2 mm
Bending radius	> 5 x cable diameter, cable fixed > 10 x cable diameter, cable moving
Drag chain suitability	bending cycles for $r > 10 \times$ cable diameter: 200000 bending cycles for $r \geq 50\text{mm}$: ca. 1200000 acceleration max. 12 m/s^2 traverse distance horizontal $\leq 50 \text{ cm}$ traverse distance vertical $\leq 50 \text{ cm}$ moving speed 12 m/s
Tension force	max. 20 N

Release date: 2024-10-17 Date of issue: 2024-10-17 Filename: 70131324_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

Material		PUR
Color		black
Length	L	3 m
Mass		35 g
Dimensions		
Height		26.6 mm
Width		12.6 mm
Length		21 mm

Installation Conditions

Note for Mounting
The ultrasonic transducer can be installed in the mounting brackets available from Pepperl+Fuchs as well as in mounting brackets designed in-house. The sensor must only be fixed in place using the factory-fitted O-rings. These are mainly used for acoustic decoupling.

Commissioning

This component is only intended for use in conjunction with the ultrasonic sensor system USi-safety or USi-industry. Further details, mounting and commissioning instructions can be found in the corresponding documentation on the relevant product page at www.pepperl-fuchs.com.

Release date: 2024-10-17 Date of issue: 2024-10-17 Filename: 70131324_eng.pdf