





## Mounting bracket USI-MH-27X13-V-01

- Screw mounting for simple installation
- Robust construction

Vertical mounting bracket exclusively for ultrasonic transducers of the USi ultrasonic sensor systems

### Dimensions



### Technical Data

Release date: 2024-10-17 Date of issue: 2024-10-17 Filename: 70131326\_eng.pdf

#### Ambient conditions

Ambient temperature	-40 ... 80 °C (-40 ... 176 °F)
Storage temperature	-40 ... 85 °C (-40 ... 185 °F)

#### Mechanical specifications

Material	
Housing	PA12
Mounting materials	2 x cylinder head screw M5x16 (included with delivery) 2 x cylinder head screw M3x10 (included with delivery)
Tightening torque, fastening screws	for screw M5 : max. 1.5 Nm for screw M3 : max. 0.5 Nm
Dimensions	25 mm x 46.9 mm x 32 mm
Height	32 mm
Width	46.9 mm
Length	25 mm

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

 PEPPERL+FUCHS

## Commissioning

This component is only intended for use in conjunction with the ultrasonic sensor system USI-safety or USI-industry. Further details, mounting and commissioning instructions can be found in the corresponding documentation on the relevant product page at [www.pepperl-fuchs.com](http://www.pepperl-fuchs.com).