

PSS67 Supply cable

380321



By the metre, PUR, black RAL9005, 5x0.5, suitable for drag chains, colour of the single wires: Brown, white, blue, black, grey

Technical details

General data	
Approval:	CE, UKCA
Technical data	
Electrical data	
Typ. conductor resistance K1:	39 Ohm/km
Insulation resistance cable K1:	1000 MOhm x km
Specific contact resistance K1:	$\geq 1E+17$ Ohm*cm
Specific conductor capacity K1:	105pF/m
Environmental data	
Ambient temperature:	-25 - 80 °C
Mechanical data	
Cable material K1:	Cu
Insulation material cable K1:	PP9P
Cable type K1:	Li9YH-11YH
Colour cable insulation 1:	Black, similar to RAL9005
Material of cable insulation 1:	TPU / TPE-U, PUR
Trailing capability of cable 1:	yes
Bend radius (when laying) K1:	5 x Ø
Max. outside diameter cable K1:	6.2 - 6.2 mm
Conductor cross section:	0.5 - 0.5 mm ²

Cable cross section AWG K1:	20
Stranding K1:	5 cores round PP splice yarn
Shielding K1:	no
Number of conductors:	5
Approvals for cable K1:	UL AWM-Style 20549
Halogen-free:	yes
Oil resistance:	resistant
Flame resistance:	UL 1581, CSA 22.2 FT2
Net weight:	50 g
Gross weight:	50 g
Environment	
WEEE classification (08/2018):	0 not relevant
Commercial data	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27060411
ETIM Version:	ETIM-7.0