

PSEN cable M8-8sf M8-8sm, 5m

533158



Connection cable, PUR, yellow RAL1003, suitable for drag chains, 8-pin, socket straight M8, on connector straight M8, A-coded, cable length: 5m

Technical details

General data	
Approval:	CE, UKCA, cULus Listed
Technical data	
Electrical data	
Rated current:	1.5 A
Typ. conductor resistance K1:	140 Ohm/km
Specific contact resistance K1:	$\geq 7E+15 \text{ Ohm} \cdot \text{cm}$
Specific conductor capacity K1:	57.5pF/m
Environmental data	
Ambient temperature:	-40 - 80 °C
Pollution degree clear.&creep.:	3
Mechanical data	
Connector type 1:	8 pin M8 male connector
Shape of connector type 1:	straight
Connector type 2:	8-pin M8 female connector
Shape of connector type 2:	straight
Contact surfaces material 1:	Au
Contact surfaces material 2:	Au
Material of pins:	CuZn
Material of sockets:	CuSn

Cable material K1:	Cu
Insulation material cable K1:	PP cold resistance
Cable type K1:	LiF9Y11Y
Length cable:	5 m
Colour cable insulation 1:	Yellow, similar to RAL 1003
Housing colour:	Black
Material of cable insulation 1:	TPU / TPE-U, PUR
Trailing capability of cable 1:	yes
Bend radius (when laying) K1:	5 x Ø
Max. outside diameter cable K1:	5.7 - 5.7 mm
Conductor cross section:	0.14 - 0.14 mm ²
Cable cross section AWG K1:	26
Stranding K1:	8 cores round cotton filler
Shielding K1:	no
Number of conductors:	8
Approvals for cable K1:	UL AWM-Style 20233, UL/CSA
Halogen-free:	yes
Oil resistance:	resistant
Flame resistance:	CSA FT-2, UL 1581, Cable Flame
Housing material:	PUR
Torque interlocking screw:	0.4 Nm
Net weight:	180 g
Gross weight:	185 g
Environment	
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27060311
ETIM Version:	ETIM-7.0

ETIM Reference Group:

EG000026