

PSEN opII Y Junction M12-M12/M12

632511



Cable, Y-adapter- with T plug-in connector, IP67, M12 male connector(X2, evaluation device), black, straight, 5-pin, A-coded on M12 female connector (X2, transmitter), black, straight, 5-pin, A-coded and M12 female connector (X3, receiver), black, straight, 5-pin, A-coded, PUR 0.15 m, 8× 0.25 mm², yellow, to connect the transmitter and receiver for PSENopt II to an M12 port (2FDI).

Technical details

General data	
Approval:	CE, UKCA
Technical data	
Electrical data	
Rated current:	2 A
Typ. conductor resistance K1:	78 Ohm/km
Specific contact resistance K1:	$\geq 1E+16 \text{ Ohm} \cdot \text{cm}$
Environmental data	
Ambient temperature:	-25 - 80 °C
Pollution degree clear.&creep.:	3
Mechanical data	
Connector type 1:	5-pin M12 female connector
Shape of connector type 1:	straight
Coding of M12 connector 1:	A coded
Connector type 2:	5-pin M12 female connector
Shape of connector type 2:	straight
Coding of M12 connector 2:	A coded
Connector type 3:	5-pin M12 male connector
Shape of connector type 3:	straight
Coding of M12 connector 3:	A coded

Matl threaded ring conn 1:	GD-Zn, Ni
Matl threaded ring conn 2:	GD-Zn, Ni
Material threaded ring conn 3:	GD-Zn, Ni
Housing material connector 3:	TPU, UL 94 HB
Contact surfaces material 1:	CuZn, Ni b/Au 0.2 gal.
Contact surfaces material 2:	CuZn, Ni b/Au 0.2 gal.
Contact surfaces material 3:	CuZn, Ni b / Au 0.2 gal.
Seal material:	FPM
Material of pins:	CuZn
Material of sockets:	CuZn
Cable material K1:	Cu
Insulation material cable K1:	PP (9Y)
Cable type K1:	Li9Y11Y
Length cable:	0.15 m
Colour cable insulation 1:	Signal yellow RAL1003
Housing colour:	Black
Material of cable insulation 1:	TPU / TPE-U
Bend radius (when laying) K1:	6 x Ø
Max. outside diameter cable K1:	6.2 - 6.2 mm
Conductor cross section:	0.25 - 0.25 mm ²
Cable cross section AWG K1:	24
Stranding K1:	8 cores round filler
Shielding K1:	no
Number of conductors:	8
Approvals for cable K1:	UL AWM-Style 20549
Approvals for connector 1:	UL 94
Approvals for connector 2:	UL 94
Approvals for connector 3:	UL 94
Halogen-free:	yes

Flame resistance:	cULus 20549
Torque interlocking screw:	0.6 Nm
Net weight:	42 g
Gross weight:	42 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6c
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27272791
ETIM Version:	ETIM-7.0