



## BCG19-A1CM1007

EcoLine

WIRE DRAW ENCODERS

**SICK**  
Sensor Intelligence.



## Ordering information

Type	part no.
BCG19-A1CM1007	1061039

**Included in delivery:** AFM60B-S1AC004096 (1), MRA-G190-110D3 (1)

Other models and accessories → [www.sick.com/EcoLine](http://www.sick.com/EcoLine)



## Detailed technical data

## Safety-related parameters

<b>MTTF<sub>D</sub> (mean time to dangerous failure)</b>	250 years (EN ISO 13849-1) <sup>1)</sup>
--	--

<sup>1)</sup> This product is a standard product and does not constitute a safety component as defined in the Machinery Directive. Calculation based on nominal load of components, average ambient temperature 40°C, frequency of use 8760 h/a. All electronic failures are considered hazardous. For more information, see document no. 8015532.

## Performance

<b>Measurement range</b>	0 m ... 10 m
<b>Encoder</b>	Absolute encoders
<b>Resolution (wire draw + encoder)</b>	0.14 mm <sup>1) 2)</sup>
<b>Repeatability</b>	≤ 0.2 mm <sup>3)</sup>
<b>Linearity</b>	≤ ± 2 mm <sup>3)</sup>
<b>Hysteresis</b>	≤ 0.4 mm <sup>3)</sup>

<sup>1)</sup> The values shown have been rounded.

<sup>2)</sup> Example calculation based on the BCG08 with PROFINET: 230 mm (wire draw length per revolution - see Mechanical data): 262,144 (number of steps per revolution) = 0.001 mm (resolution of wire draw + encoder combination).

<sup>3)</sup> Value applies to wire draw mechanism.

## Interfaces

<b>Communication interface</b>	SSI
--------------------------------	-----

## Electronics

<b>Connection type</b>	Male connector, M12, 8-pin, radial
<b>Supply voltage</b>	4.5 V DC ... 32 V DC
<b>Power consumption</b>	≤ 0.7 W (without load)

## Mechanics

<b>Weight</b>	2.2 kg
<b>Measuring wire material</b>	Highly flexible stranded steel 1,4401 stainless steel V4A
<b>Measuring wire diameter</b>	0.55 mm
<b>Weight (measuring wire)</b>	7.1 g/m
<b>Housing material, wire draw mechanism</b>	Plastic, Noryl
<b>Spring return force</b>	9 N ... 12 N <sup>1)</sup>
<b>Length of wire pulled out per revolution</b>	555 mm
<b>Life of wire draw mechanism</b>	Typ. 1,000,000 cycles <sup>2) 3)</sup>
<b>Actual wire draw length</b>	10.2 m
<b>Wire acceleration</b>	8 m/s <sup>2</sup>
<b>Operating speed</b>	3 m/s
<b>Mounted encoder</b>	AFM60 SSI, AFM60B-S1AC004096, 1037869
<b>Mounted mechanic</b>	MRA-G190-110D3, 5326242

<sup>1)</sup> These values were measured at an ambient temperature of 25 °C. There may be variations at other temperatures.

<sup>2)</sup> Average values, which depend on the application.

<sup>3)</sup> The service life depends on the type of load. This is influenced by environmental conditions, the installation location, the measuring range in use, the traversing speed, and acceleration.

## Ambient data

<b>EMC</b>	According to EN 61000-6-2 and EN 61000-6-3 <sup>1)</sup>
<b>Enclosure rating</b>	IP50, mounted mechanic IP67, Encoder (IEC 60529) <sup>2)</sup>
<b>Operating temperature range</b>	-30 °C ... +70 °C

<sup>1)</sup> EMC according to the standards quoted is achieved if shielded cables are used.

<sup>2)</sup> For devices with male connector: with mounted mating connector.

## Certificates


<b>EU declaration of conformity</b>	✓
<b>UK declaration of conformity</b>	✓
<b>ACMA declaration of conformity</b>	✓
<b>Moroccan declaration of conformity</b>	✓
<b>China-RoHS</b>	✓

## Classifications

<b>ECLASS 5.0</b>	27270590
<b>ECLASS 5.1.4</b>	27270590
<b>ECLASS 6.0</b>	27270590
<b>ECLASS 6.2</b>	27270590
<b>ECLASS 7.0</b>	27270590
<b>ECLASS 8.0</b>	27270590
<b>ECLASS 8.1</b>	27270590
<b>ECLASS 9.0</b>	27270590
<b>ECLASS 10.0</b>	27270613


<b>ECLASS 11.0</b>	27270503
<b>ECLASS 12.0</b>	27270503
<b>ETIM 5.0</b>	EC001486
<b>ETIM 6.0</b>	EC001486
<b>ETIM 7.0</b>	EC001486
<b>ETIM 8.0</b>	EC001486
<b>UNSPSC 16.0901</b>	41112113

## Dimensional drawing



Dimensions in mm (inch)


## PIN assignment M12 male connector, 8-pin and cable, 8-wire, SSI/Gray



view of M12 male device connector on encoder

PIN	Wire colors (cable connection)	Signal	Explanation
1	Brown	Data -	Interface signals
2	White	Data +	Interface signals
3	Black	V/R	Sequence in direction of rotation
4	Pink	SET	Electronic adjustment Interface signals
5	Yellow	Clock +	Interface signals
6	Purple	Clock -	Interface signals
7	Blue	GND	Ground connection
8	Red	U <sub>S</sub>	Operating voltage
-	-	Screen	Screen connected to housing on encoder side. Connected to ground on control side.

## Diagrams



The maximum speed is also dependent on the shaft type.

## Recommended accessories

Other models and accessories → [www.sick.com/EcoLine](http://www.sick.com/EcoLine)

	<b>Brief description</b>	<b>Type</b>	<b>part no.</b>
Mounting systems	<ul style="list-style-type: none"> <li><b>Description:</b> Spare mounting set for MRA-G190 (10 m EcoLine)</li> </ul>	BEF-MK-MRA-G01	5326294
Wire draw mechanism	 <ul style="list-style-type: none"> <li><b>Product segment:</b> Wire draw mechanism</li> <li><b>Product family:</b> Wire draw mechanism for wire draw encoders</li> <li><b>Description:</b> EcoLine wire draw mechanism for servo flange with 6 mm shaft, measuring range 0 m ... 10 m</li> <li><b>Items supplied:</b> Without encoder</li> </ul>	MRA-G190-110D3	5326242

	Brief description	Type	part no.
connectors and cables			
	<ul style="list-style-type: none"><li><b>Connection type head A:</b> Female connector, M12, 8-pin, straight, A-coded</li><li><b>Signal type:</b> Incremental, SSI</li><li><b>Cable:</b> CAT5, CAT5e</li><li><b>Description:</b> Incremental, shieldedSSI</li><li><b>Connection systems:</b> IDC quick connection</li><li><b>Permitted cross-section:</b> 0.14 mm<sup>2</sup> ... 0.34 mm<sup>2</sup></li></ul>	DOS-1208-GA01	6045001
	<ul style="list-style-type: none"><li><b>Connection type head A:</b> Flying leads</li><li><b>Connection type head B:</b> Flying leads</li><li><b>Signal type:</b> SSI, Incremental, HIPERFACE®</li><li><b>Items supplied:</b> By the meter</li><li><b>Cable:</b> 8-wire, PUR, halogen-free</li><li><b>Description:</b> SSI, shieldedIncrementalHIPERFACE®</li></ul>	LTG-2308-MWENC	6027529
	<ul style="list-style-type: none"><li><b>Connection type head A:</b> Female connector, M12, 8-pin, straight</li><li><b>Connection type head B:</b> Flying leads</li><li><b>Signal type:</b> Incremental, SSI</li><li><b>Cable:</b> 2 m, 8-wire, PUR, halogen-free</li><li><b>Description:</b> Incremental, shieldedSSI</li><li><b>Connection systems:</b> Flying leads</li></ul>	DOL-1208-G02MAC1	6032866
	<ul style="list-style-type: none"><li><b>Connection type head A:</b> Female connector, M12, 8-pin, straight</li><li><b>Connection type head B:</b> Flying leads</li><li><b>Signal type:</b> Incremental, SSI</li><li><b>Cable:</b> 5 m, 8-wire, PUR, halogen-free</li><li><b>Description:</b> Incremental, shieldedSSI</li><li><b>Connection systems:</b> Flying leads</li></ul>	DOL-1208-G05MAC1	6032867
	<ul style="list-style-type: none"><li><b>Connection type head A:</b> Female connector, M12, 8-pin, straight</li><li><b>Connection type head B:</b> Flying leads</li><li><b>Signal type:</b> Incremental, SSI</li><li><b>Cable:</b> 10 m, 8-wire, PUR, halogen-free</li><li><b>Description:</b> Incremental, shieldedSSI</li><li><b>Connection systems:</b> Flying leads</li></ul>	DOL-1208-G10MAC1	6032868
	<ul style="list-style-type: none"><li><b>Connection type head A:</b> Female connector, M12, 8-pin, straight</li><li><b>Connection type head B:</b> Flying leads</li><li><b>Signal type:</b> Incremental, SSI</li><li><b>Cable:</b> 20 m, 8-wire, PUR, halogen-free</li><li><b>Description:</b> Incremental, shieldedSSI</li><li><b>Connection systems:</b> Flying leads</li></ul>	DOL-1208-G20MAC1	6032869
	<ul style="list-style-type: none"><li><b>Connection type head A:</b> Female connector, M12, 8-pin, straight</li><li><b>Connection type head B:</b> Flying leads</li><li><b>Signal type:</b> Incremental, SSI</li><li><b>Cable:</b> 25 m, 8-wire, PUR, halogen-free</li><li><b>Description:</b> Incremental, shieldedSSI</li><li><b>Connection systems:</b> Flying leads</li></ul>	DOL-1208-G25MAC1	6067859

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is "Sensor Intelligence."**

## WORLDWIDE PRESENCE:

Contacts and other locations [www.sick.com](http://www.sick.com)