



CMB30-25NPPECOSA00

CMB

CAPACITIVE PROXIMITY SENSORS

SICK
Sensor Intelligence.



Ordering information

Type	part no.
CMB30-25NPPECOSA00	6080644

Other models and accessories → www.sick.com/CMB

Illustration may differ



Detailed technical data

Features

Housing	Metric						
Thread size	M30 x 1.5						
Diameter	Ø 30 mm						
Sensing range S_n	0 mm ... 25 mm						
Safe sensing range S_a	19.13 mm ¹⁾						
Installation type	Non-flush						
Switching frequency	50 Hz						
Connection type	Male connector M12, 4-pin						
Switching output	PNP						
Switching output detail	PNP						
Output function	Complementary						
Output characteristic	Wire configurable						
Electrical wiring	DC 4-wire						
Adjustment	<table border="1"> <tr> <td>Potentiometer</td> <td>Sensitivity (11 turns)</td> </tr> <tr> <td>Wire/pin</td> <td>Sensitivity</td> </tr> <tr> <td>IO-Link</td> <td>Sensitivity, sensor parameters and Smart Task functions</td> </tr> </table>	Potentiometer	Sensitivity (11 turns)	Wire/pin	Sensitivity	IO-Link	Sensitivity, sensor parameters and Smart Task functions
Potentiometer	Sensitivity (11 turns)						
Wire/pin	Sensitivity						
IO-Link	Sensitivity, sensor parameters and Smart Task functions						
Enclosure rating	IP67 IP68 ²⁾ IP69K						
Special features	Visual adjustment indicator						

¹⁾ For flush mounting in electrically conductive materials $S_a = 0.8 \times S_n$ at temperatures <0 °C and >60 °C.²⁾ 1 m water depth / 60 min.

Pin 2 configuration	External input, Teach-in, switching signal
Items supplied	Mounting nut, PA12 plastic (2x) Screwdriver for potentiometer adjustment (1 x)

1) For flush mounting in electrically conductive materials $S_a = 0.8 \times S_r$ at temperatures $< 0 \text{ }^\circ\text{C}$ and $> 60 \text{ }^\circ\text{C}$.
 2) 1 m water depth / 60 min.

Mechanics/electronics

Supply voltage	10 V DC ... 36 V DC
Ripple	$\leq 10 \text{ \%}$ ¹⁾
Voltage drop	$\leq 2 \text{ V DC}$ ²⁾
Current consumption	$\leq 20 \text{ mA}$ ³⁾
Time delay before availability	$\leq 300 \text{ ms}$
Hysteresis	3 \% ... 20 %
Reproducibility	$\leq 5 \text{ \%}$ ⁴⁾ 5)
Temperature drift (of S_r)	$\pm 10 \text{ \%}$
EMC	EN 61000-4-2 ESD: > 40 kV CD and AD EN 61000-4-3 Radiated RF: 20 V/m EN 61000-4-4 burst: +/- 4 kV / 5 kHz EN 61000-4-5 Surge: Voltage supply > 2 kV with 500 ohm; switching output > 2 kV with 500 ohm EN 61000-4-6 HF: > 20 V _{rms} EN 61000-4-8 mains frequency magnetic fields: Permanent > 60 A/m, 75,9 μ tesla; briefly > 600 A/m, 759 μ tesla
Continuous current I_a	$\leq 200 \text{ mA}$
Short-circuit protection	✓
Power-up pulse protection	✓
Shock and vibration resistance	EN 60068-2-27 shock resistance Ea: 30 g 11 ms; 3 shocks in each direction of the 3 coordinate axes IEC 60068-2-31 drop test: 2 times from 1 m, 100 times from 0.5 m EN 60068-2-6 vibration resistance Fc: 10 Hz ... 150 Hz, 1 mm / 15 g
Ambient operating temperature	-30 $\text{ }^\circ\text{C}$... +85 $\text{ }^\circ\text{C}$ ⁶⁾
Ambient temperature, storage	-40 $\text{ }^\circ\text{C}$... +85 $\text{ }^\circ\text{C}$
Housing material	Plastic, PBT
Housing length	74 mm
Thread length	45.5 mm
Tightening torque, max.	$\leq 7.5 \text{ Nm}$
UL File No.	NRKH.E191603

1) Of U_B .

2) At I_a max.

3) Without load.

4) Of S_r .

5) Supply voltage U_B and constant ambient temperature T_a .

6) +120 $\text{ }^\circ\text{C}$ short time, at the front of the sensor.

Safety-related parameters

MTTF_D	786 years
DC_{avg}	0%

T_M (mission time)	20 years
Communication interface	
Communication interface	IO-Link V1.1
Communication Interface detail	COM2 (38,4 kBaud)
Cycle time	> 5 ms
Process data length	4 Byte
Process data structure	<p>Bit 0 = switching signal Q_{L1} Bit 1 = switching signal Q_{L2} Bit 2 = Sensor switching channel Qint1 Bit 3 = Sensor switching channel Qint2 Bit 4 = Contamination alarm for switching channel Qint1 Bit 5 = Contamination channel for Qint2 Bit 6 = Temperature alarm Bit 7 = Short-circuit Bit 16 ... 31 = Analog value (digit value, not linearized)</p>
Reduction factors	
Note	The values are reference values which may vary
Metal	1
Water	1
PVC	Approx. 0.4
Oil	Approx. 0.25
Glass	0.6
Ceramics	0.5
Alcohol	0.7
Wood	0.2 ... 0.7
Installation note	
Remark	Associated graphic see "Installation"
A	30 mm
B	60 mm
C	30 mm
D	75 mm
E	14.5 mmIn critical distances, the sensor should be tested in the application
F	75 mm
Smart Task	
Smart Task name	Base logics
Logic function	Direct AND OR Window Hysteresis
Timer function	Deactivated Switch-on delay Off delay ON and OFF delay Impulse (one shot)
Inverter	Yes
Switching signal	

Switching signal Q _{L1}	Switching output
Switching signal Q _{L2}	Switching output


Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
China-RoHS	✓
ECOLAB certificate	✓
cULus certificate	✓
IO-Link	✓


Classifications

ECLASS 5.0	27270102
ECLASS 5.1.4	27270102
ECLASS 6.0	27270102
ECLASS 6.2	27270102
ECLASS 7.0	27270102
ECLASS 8.0	27270102
ECLASS 8.1	27270102
ECLASS 9.0	27270102
ECLASS 10.0	27270102
ECLASS 11.0	27270102
ECLASS 12.0	27274201
ETIM 5.0	EC002715
ETIM 6.0	EC002715
ETIM 7.0	EC002715
ETIM 8.0	EC002715
UNSPSC 16.0901	39122230

Installation note Non-flush installation




Connection diagram Cd-526




Q_{L1}/C = Switching output,
 IO-Link communication
 MF = Multifunction

Response diagram CMB30, Non-flush installation



Dimensional drawing CMB30, non-flush, connector



Dimensions in mm (inch)

- ① Potentiometer for sensitivity adjustment
- ② LED yellow: output active
- ③ LED green: operating indicator

Recommended accessories

Other models and accessories → www.sick.com/CMB

	Brief description	Type	part no.
network devices			
		IOLA2US-01101 (SiLink2 Master)	1061790
		SIG200-0A0412200	1089794
connectors and cables			
	<ul style="list-style-type: none">Connection type head A: Male connector, M12, 4-pin, straight, A-codedDescription: UnshieldedConnection systems: Screw-type terminalsPermitted cross-section: ≤ 0.75 mm²	STE-1204-G	6009932
	<ul style="list-style-type: none">Connection type head A: Female connector, M12, 4-pin, straight, A-codedConnection type head B: Flying leadsSignal type: Sensor/actuator cableCable: 5 m, 4-wire, PVCDescription: Sensor/actuator cable, unshieldedApplication: Zones with chemicals, Uncontaminated zones	YF2A14-050VB3XLEAX	2096235
Mounting systems			
	<ul style="list-style-type: none">Description: Mounting bracket for M30 sensorsMaterial: SteelDetails: Steel, zinc coatedItems supplied: Without mounting hardware	BEF-WN-M30	5308445
	<ul style="list-style-type: none">Description: Mounting plate for M30 sensorsMaterial: SteelDetails: Steel, zinc coatedItems supplied: Without mounting hardware	BEF-WG-M30	5321871
	<ul style="list-style-type: none">Description: Integrated adapterMaterial: PlasticDetails: Plastic (POM)	BEF-EA-CM30	2043770

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations www.sick.com