



DBS60E-RGFPD1024

DBS60

INCREMENTAL ENCODERS

SICK
Sensor Intelligence.



Ordering information

Type	part no.
DBS60E-RGFPD1024	1116070

Other models and accessories → www.sick.com/DBS60

Illustration may differ



Detailed technical data

Safety-related parameters

MTTF_D (mean time to dangerous failure)	500 years (EN ISO 13849-1) ¹⁾
--	--

¹⁾ This product is a standard product and does not constitute a safety component as defined in the Machinery Directive. Calculation based on nominal load of components, average ambient temperature 40 °C, frequency of use 8760 h/a. All electronic failures are considered hazardous. For more information, see document no. 8015532.

Performance

Pulses per revolution	1,024
Measuring step	≤ 90°, electric/pulses per revolution
Measuring step deviation	± 18° / pulses per revolution
Error limits	Measuring step deviation x 3
Duty cycle	≤ 0.5 ± 5 %

Interfaces

Communication interface	Incremental
Communication Interface detail	TTL / HTL / HTL ¹⁾
Number of signal channels	6-channel
Initialization time	< 5 ms ²⁾
Output frequency	+ 300 kHz ³⁾
Load current	≤ 30 mA, per channel
Power consumption	≤ 0.5 W (without load)

¹⁾ Output level depends on the supply voltage.

²⁾ Valid signals can be read once this time has elapsed.

³⁾ Up to 450 kHz on request.

Electronics

Connection type	Cable, 8-wire, with male connector, M12, 8-pin, universal, 0.5 m ¹⁾
------------------------	--

¹⁾ The universal cable connection is positioned so that it is possible to lay it without bends in a radial or axial direction.

²⁾ Short-circuit opposite to another channel, US or GND permissible for maximum 30 s.

Supply voltage	4.5 ... 30 V
Reference signal, number	1
Reference signal, position	90°, electric, logically gated with A and B
Reverse polarity protection	✓
Short-circuit protection of the outputs	✓ ²⁾

1) The universal cable connection is positioned so that it is possible to lay it without bends in a radial or axial direction.

2) Short-circuit opposite to another channel, US or GND permissible for maximum 30 s.

Mechanics

Mechanical design	Through hollow shaft
Shaft diameter	14 mmRear clamping
Flange type / stator coupling	1-sided stator coupling, slot, screw hole circle radius 31.5–48.5 mm
Weight	+ 0.25 kg ¹⁾
Shaft material	Stainless steel
Flange material	Aluminum
Housing material	Aluminum
Material, cable	PVC
Start up torque	+ 0.5 Ncm (+20 °C)
Operating torque	0.4 Ncm (+20 °C)
Permissible movement static	± 0.3 mm (radial) ± 0.5 mm (axial) ²⁾
Permissible movement dynamic	± 0.1 mm (radial) ± 0.2 mm (axial) ²⁾
Operating speed	6,000 min ⁻¹ ³⁾
Maximum operating speed	9,000 min ⁻¹ ⁴⁾
Moment of inertia of the rotor	50 gcm ²
Bearing lifetime	3.6 x 10 ⁹ revolutions
Angular acceleration	≤ 500,000 rad/s ²

1) Based on encoder with male connector or cable with male connector.

2) Not applicable for stator coupling type C and K.

3) Allow for self-heating of 2.6 K per 1,000 rpm when designing the operating temperature range.

4) Maximum speed which does not cause mechanical damage to the encoder. Impact on the service life and signal quality is possible. Please note the maximum output frequency.

Ambient data

EMC	According to EN 61000-6-2 and EN 61000-6-3
Enclosure rating	IP65, housing side (IEC 60529) ¹⁾ IP65, shaft side (IEC 60529)
Permissible relative humidity	90 % (Condensation not permitted)
Operating temperature range	-30 °C ... +100 °C, at maximum 3,000 pulses per revolution ²⁾
Storage temperature range	-40 °C ... +100 °C, without package
Resistance to shocks	250 g, 3 ms (EN 60068-2-27)

1) With mating connector fitted.

2) These values relate to all mechanical versions including recommended accessories unless otherwise noted.

Resistance to vibration	30 g, 10 Hz ... 2,000 Hz (EN 60068-2-6)
--------------------------------	---

¹⁾ With mating connector fitted.

²⁾ These values relate to all mechanical versions including recommended accessories unless otherwise noted.




Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
China-RoHS	✓
cRUs certificate	✓
Information according to Art. 3 of Data Act (Regulation EU 2023/2854)	✓

Classifications

ECLASS 5.0	27270501
ECLASS 5.1.4	27270501
ECLASS 6.0	27270590
ECLASS 6.2	27270590
ECLASS 7.0	27270501
ECLASS 8.0	27270501
ECLASS 8.1	27270501
ECLASS 9.0	27270501
ECLASS 10.0	27270501
ECLASS 11.0	27270501
ECLASS 12.0	27270501
ETIM 5.0	EC001486
ETIM 6.0	EC001486
ETIM 7.0	EC001486
ETIM 8.0	EC001486
UNSPSC 16.0901	41112113

Dimensional drawing



Dimensions in mm (inch)


XF7 values see shaft diameter table for through hollow shaft, clamping at the back

① Zero pulse mark on housing

② zero pulse mark on flange under stator coupling

Type	Through hollow shaft with rear clamping	Shaft diameter XF7
DBS60x-RAxxxxxxx	DBS60x-R1xxxxxx	6 mm
DBS60x-RBxxxxxx	DBS60x-R2xxxxxx	8 mm
DBS60x-RCxxxxxx	DBS60x-R3xxxxxx	3/8"
DBS60x-RDxxxxxx	DBS60x-R4xxxxxx	10 mm
DBS60x-RExxxxxx	DBS60x-R5xxxxxx	12 mm
DBS60x-RFxxxxxx	DBS60x-R6xxxxxx	1/2"
DBS60x-RGxxxxxx	DBS60x-R7xxxxxx	14 mm
DBS60x-RHxxxxxx	DBS60x-R8xxxxxx	15 mm
DBS60x-RJxxxxxx		5/8"

Attachment specifications Through hollow shaft with rear clamping




customer side

Type	Through hollow shaft with rear clamping	Shaft diameter xj7
DBS60x-RAxxxxxxx	DBS60x-R1xxxxxx	6 mm
DBS60x-RBxxxxxx	DBS60x-R2xxxxxx	8 mm
DBS60x-RCxxxxxx	DBS60x-R3xxxxxx	3/8"
DBS60x-RDxxxxxx	DBS60x-R4xxxxxx	10 mm

Type	Through hollow shaft with rear clamping	Shaft diameter xj7
DBS60x-RExxxxxxx	DBS60x-R5xxxxxx	12 mm
DBS60x-RFxxxxxx	DBS60x-R6xxxxxx	1/2"
DBS60x-RGxxxxxx	DBS60x-R7xxxxxx	14 mm
DBS60x-RHxxxxxx	DBS60x-R8xxxxxx	15 mm
DBS60x-RJxxxxxx		5/8"
		-

PIN assignment




view of M12 male device connector on cable / housing


Wire colors (cable connection)	Male connector M12, 8-pin	Male connector M23, 12-pin	TTL/HTL 6-channel signal	Explanation
Brown	1	6	A-	Signal wire
White	2	5	A	Signal wire
Black	3	1	B-	Signal wire
Pink	4	8	B	Signal wire
Yellow	5	4	Z-	Signal wire
Purple	6	3	Z	Signal wire
Blue	7	10	GND	Ground connection
Red	8	12	+U _s	Supply voltage
-	-	9	Not assigned	Not assigned
-	-	2	Not assigned	Not assigned
-	-	11	Not assigned	Not assigned
-	-	7	Not assigned	Not assigned
Screen	Screen	Screen	Screen	Screen connected to encoder housing

Diagrams

Pulses per revolution



Diagrams Signal outputs for electrical interfaces TTL and HTL



Cw with view on the encoder shaft in direction "A", compare dimensional drawing.

Supply voltage	Output
4,5 V ... 5,5 V	TTL
10 V ... 30 V	TTL
10 V ... 27 V	HTL

Supply voltage	Output
4,5 V ... 30 V	TTL/HTL universal
4,5 V ... 30 V	TTL

Recommended accessories

Other models and accessories → www.sick.com/DBS60

	Brief description	Type	part no.
connectors and cables			
	<ul style="list-style-type: none">Connection type head A: Flying leadsConnection type head B: Flying leadsSignal type: SSI, Incremental, HIPERFACE®Items supplied: By the meterCable: 8-wire, PUR, halogen-freeDescription: SSI, shielded, Incremental, HIPERFACE®	LTG-2308-MWENC	6027529
	<ul style="list-style-type: none">Connection type head A: Flying leadsConnection type head B: Flying leadsSignal type: SSI, IncrementalItems supplied: By the meterCable: 11-wire, PURDescription: SSI, shielded, Incremental	LTG-2411-MW	6027530
	<ul style="list-style-type: none">Connection type head A: Flying leadsConnection type head B: Flying leadsSignal type: SSI, IncrementalItems supplied: By the meterCable: 12-wire, PUR, halogen-freeDescription: SSI, shielded, Incremental	LTG-2512-MW	6027531
	<ul style="list-style-type: none">Connection type head A: Flying leadsConnection type head B: Flying leadsSignal type: SSI, TTL, HTL, IncrementalItems supplied: By the meterCable: 12-wire, UV and saltwater-resistant, PUR, halogen-freeDescription: SSI, shielded, TTL, HTL, Incremental	LTG-2612-MW	6028516
	<ul style="list-style-type: none">Connection type head A: Female connector, M12, 8-pin, straightConnection type head B: Flying leadsSignal type: Incremental, SSICable: 2 m, 8-wire, PUR, halogen-freeDescription: Incremental, shieldedSSIConnection systems: Flying leads	DOL-1208-G02MAC1	6032866
	<ul style="list-style-type: none">Connection type head A: Female connector, M12, 8-pin, straightConnection type head B: Flying leadsSignal type: Incremental, SSICable: 5 m, 8-wire, PUR, halogen-freeDescription: Incremental, shieldedSSIConnection systems: Flying leads	DOL-1208-G05MAC1	6032867
	<ul style="list-style-type: none">Connection type head A: Female connector, M12, 8-pin, straightConnection type head B: Flying leadsSignal type: Incremental, SSICable: 10 m, 8-wire, PUR, halogen-freeDescription: Incremental, shieldedSSIConnection systems: Flying leads	DOL-1208-G10MAC1	6032868
	<ul style="list-style-type: none">Connection type head A: Female connector, M12, 8-pin, straightConnection type head B: Flying leadsSignal type: Incremental, SSICable: 20 m, 8-wire, PUR, halogen-freeDescription: Incremental, shieldedSSIConnection systems: Flying leads	DOL-1208-G20MAC1	6032869
	<ul style="list-style-type: none">Connection type head A: Female connector, M12, 8-pin, straightConnection type head B: Flying leadsSignal type: Incremental, SSICable: 25 m, 8-wire, PUR, halogen-freeDescription: Incremental, shieldedSSIConnection systems: Flying leads	DOL-1208-G25MAC1	6067859
	<ul style="list-style-type: none">Connection type head A: Female connector, M12, 8-pin, straight, A-codedSignal type: Incremental, SSICable: CAT5, CAT5eDescription: Incremental, shieldedSSIConnection systems: IDC quick connectionPermitted cross-section: 0.14 mm² ... 0.34 mm²	DOS-1208-GA01	6045001
	<ul style="list-style-type: none">Connection type head A: Female connector, M12, 8-pin, straight, A-codedConnection type head B: Male connector, M12, 8-pin, straight, A-codedCable: 20 m, 8-wire, PUR, halogen-freeDescription: Shielded	YF2AA8-200S01M-KA18	2099208

	Brief description	Type	part no.
	<ul style="list-style-type: none"> • Permitted cross-section: $\leq 0.25 \text{ mm}^2$ • Note: Drag chain use • Application: Drag chain operation 		
	<ul style="list-style-type: none"> • Connection type head A: Female connector, M12, 8-pin, straight, A-coded • Connection type head B: Male connector, M12, 8-pin, straight, A-coded • Cable: 2 m, 8-wire, PUR, halogen-free • Description: Shielded • Permitted cross-section: $\leq 0.25 \text{ mm}^2$ • Note: Drag chain use • Application: Drag chain operation 	YF2AA8-020S01M-KA18	2099207
	<ul style="list-style-type: none"> • Connection type head A: Female connector, M12, 8-pin, straight, A-coded • Connection type head B: Male connector, M12, 8-pin, straight, A-coded • Cable: 5 m, 8-wire, PUR, halogen-free • Description: Shielded • Permitted cross-section: $\leq 0.25 \text{ mm}^2$ • Note: Drag chain use • Application: Drag chain operation 	YF2AA8-050S01M-KA18	2099209
	<ul style="list-style-type: none"> • Connection type head A: Female connector, M12, 8-pin, straight, A-coded • Connection type head B: Male connector, M12, 8-pin, straight, A-coded • Cable: 10 m, 8-wire, PUR, halogen-free • Description: Shielded • Permitted cross-section: $\leq 0.25 \text{ mm}^2$ • Note: Drag chain use • Application: Drag chain operation 	YF2AA8-100S01M-KA18	2099210

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations www.sick.com