

Short-circuit protection of the outputs	✓ ¹⁾
--	-----------------

¹⁾ Short-circuit opposite to another channel, US or GND permissable for maximum 30 s.

Mechanics

Mechanical design	Blind hollow shaft
Shaft diameter	12 mmFront clamp
Weight	+ 0.2 kg
Shaft material	Stainless steel
Flange material	Aluminum
Housing material	Aluminum die cast
Start up torque	0.8 Ncm (+20 °C)
Operating torque	0.6 Ncm (+20 °C)
Permissible movement static	± 0.3 mm (radial) ± 0.5 mm (axial)
Permissible movement dynamic	± 0.05 mm (radial) ± 0.01 mm (axial)
Operating speed	≤ 6,000 min ⁻¹ ¹⁾
Moment of inertia of the rotor	40 gcm ²
Bearing lifetime	3.6 x 10 ¹⁰ revolutions
Angular acceleration	≤ 500,000 rad/s ²

¹⁾ Allow for self-heating of 3.3 K per 1,000 rpm when designing the operating temperature range.

Ambient data

EMC	According to EN 61000-6-2 and EN 61000-6-4
Enclosure rating	IP67, Housing side, male connector (IEC 60529) ¹⁾ IP65, shaft side (IEC 60529)
Permissible relative humidity	90 % (Condensation not permitted)
Operating temperature range	−40 °C ... +100 °C ²⁾ −30 °C ... +100 °C ³⁾
Storage temperature range	−40 °C ... +100 °C, without package
Resistance to shocks	100 g, 6 ms (EN 60068-2-27)
Resistance to vibration	30 g, 10 Hz ... 2,000 Hz (EN 60068-2-6)

1) With mating connector fitted.

2) Stationary position of the cable.

3) Flexible position of the cable.

Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
Moroccan declaration of conformity	✓
China-RoHS	✓
cULus certificate	✓
Information according to Art. 3 of Data Act (Regulation EU 2023/2854)	✓

ECLASS 5.0	27270501
ECLASS 5.1.4	27270501
ECLASS 6.0	27270590
ECLASS 6.2	27270590
ECLASS 7.0	27270501
ECLASS 8.0	27270501
ECLASS 8.1	27270501
ECLASS 9.0	27270501
ECLASS 10.0	27270501
ECLASS 11.0	27270501
ECLASS 12.0	27270501
ETIM 5.0	EC001486
ETIM 6.0	EC001486
ETIM 7.0	EC001486
ETIM 8.0	EC001486
UNSPSC 16.0901	41112113

Technical drawing of the 1000 Series 1/2" (25.4 mm) ball valve, showing three views: side view, end view, and top view.

Side View Dimensions:


- Overall length: 45.5 (1.79)
- Distance from end to first port: 9.4 (0.37)
- Distance between ports: 3.4 (0.13)
- Distance from second port to end: 2.5 (0.10)
- Port diameter: $\varnothing 32.6$ (1.28)
- Port diameter: $\varnothing 60$ (2.36)
- Port diameter: $\varnothing 72$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (1.85)
- Port diameter: $\varnothing 63 \pm 0.2$ (2.48)
- Port diameter: $\varnothing 72 \pm 0.3$ (2.83)
- Port diameter: $\varnothing 3.2^{+0.1}_{-0.1}$ (0.13)
- Port diameter: $\varnothing 47$ (

4 INCREMENTAL ENCODERS | SICK

General tolerances according to DIN ISO 2768-mk

[illegible]

PIN assignment



view of M23 male device connector on encoder

PINMale connector M12, 8-pin	PINMale connector M23, 12-pin	Wire colors (cable connection)	TTL/HTL signal	Sin/Cos 1.0 V _{PP}	Explanation
1	6	Brown	$\overline{A}$	COS-	Signal wire
2	5	White	A	COS+	Signal wire
3	1	Black	$\overline{B}$	SIN-	Signal wire
4	8	Pink	B	SIN+	Signal wire
5	4	Yellow	$\overline{Z}$	$\overline{Z}$	Signal wire
6	3	Purple	Z	Z	Signal wire
7	10	Blue	GND	GND	Ground connection
8	12	Red	+U _S	+U _S	Supply voltage
-	9	-	N.c.	N.c.	Not assigned
-	2	-	N.c.	N.c.	Not assigned
-	11	-	N.c.	N.c.	Not assigned
-	7 ¹⁾	Orange	O-SET ¹⁾	N.c.	Set zero pulse ¹⁾
Screen	Screen	Screen	Screen	Screen	Screen connected to housing on encoder side. Connected to ground on control side.

¹⁾For electrical interfaces only: M, U, V, W with O-SET function on PIN 7 on M23 plug. The O-SET input is used to set the zero pulse to the current shaft position. If the O-SET input is applied to US for longer than 250 ms after it has previously been open or applied to GND for at least 1,000 ms, the current shaft position is assigned zero pulse signal "Z".

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

[illegible]

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations – www.sick.com