



## DKV60E-21EZA0S01

DKV60

MEASURING WHEEL ENCODERS

**SICK**  
Sensor Intelligence.



Illustration may differ

## Ordering information

| Type             | part no. |
|------------------|----------|
| DKV60E-21EZA0S01 | 1122720  |

Other models and accessories → [www.sick.com/DKV60](http://www.sick.com/DKV60)

## Detailed technical data

## Features

|                                  |   |
|----------------------------------|---|
| <b>Special device</b>            | ✓   |
| <b>Specialty</b>                 | <p>Communication interface 10 V ... 30 V HTL/push-pull</p> <p>Measuring drum, knurled surface DIN 82 – RAA1</p> <p>Cable, 5-wire, 1.5 m, M12 male connector with 5-pin male connector at cable end</p> <p>1,000 pulses (0.2 mm/increment)</p> <p>Also included with delivery:</p> <p>Mounting plate: 022-190-001-260</p> <p>Mounting plate: 022-190-001-270</p> <p>Hexagon screw, 2 pcs. M5 x 12: 022-240-301-340</p> <p>Hexagon screw, 2 pcs. M5 x 30: 022-240-302-390</p> <p>Hexagon nut, 2 pcs. M5: 022-150-100-130</p> <p>Washer, 4 pcs. 5.3 x 9 x 1: 022-170-001-340</p> |
| <b>Standard reference device</b> | DKV60E-21EKA1000, 1115704   |

## Performance

|   |  |
|---|--|
| <b>Pulses per revolution</b>                        | 1,000  |
| <b>Resolution in pulses/mm</b>                      | 5  |
| <b>Measuring increment (resolution in mm/pulse)</b> | 0.2  |
| <b>Measuring step deviation</b>                     | ± 18°, / pulses per revolution                               |
| <b>Error limits</b>                                 | ± 0.5 mm/m, subject to the measuring wheel (wheel + surface) |
| <b>Duty cycle</b>                                   | ≤ 0.5 ± 5 %  |
| <b>Initialization time</b>                          | ≤ 3 ms   |

## Interfaces

|                                       |                 |
|---------------------------------------|-----------------|
| <b>Communication interface</b>        | Incremental     |
| <b>Communication Interface detail</b> | HTL / Push pull |
| <b>Number of signal channels</b>      | 6-channel       |

## Electrical data

|  |  |
|--|--|
| <b>Operating power consumption (no load)</b> | 50 mA  |
| <b>Connection type</b>                       | Cable, 5-wire, with male connector, M12, 5-pin, universal, 1.5 m |
| <b>Supply voltage</b>                        | 10 V ... 30 V  |
| <b>Load current max.</b>                     | 30 mA  |
| <b>Maximum output frequency</b>              | ≤ 300 kHz  |
| <b>Reference signal, number</b>              | 1  |

|                                    |   |
|------------------------------------|---|
| <b>Reference signal, position</b>  | 90°, electric, logically gated with A and B |
| <b>Reverse polarity protection</b> | ✓   |

## Mechanical data

|  |                                       |
|--|---------------------------------------|
| <b>Measuring wheel circumference</b>                                       | 200 mm                                |
| <b>Measuring wheel surface</b>   | Cross knurled aluminium <sup>1)</sup> |
| <b>Spring arm design</b>   | 69.5 mm spring arm                    |
| <b>Mass</b>  | 420 g                                 |
| <b>Encoder material</b>  |                                       |
| Shaft  | Stainless steel                       |
| Flange   | Aluminum                              |
| Housing  | Aluminum                              |
| Cable  | PVC                                   |
| <b>Spring arm mechanism material</b>                                       |                                       |
| Spring element   | Spring steel, anti-corrosive          |
| Measuring wheel, spring arm  | Spring steel, anti-corrosive          |
| <b>Start up torque</b>   | 0.9 Ncm (at 20 °C)                    |
| <b>Operating torque</b>  | 0.4 Ncm (at 20 °C)                    |
| <b>Operating speed</b>   | ≤ 1,000 min <sup>-1</sup>             |
| <b>Maximum operating speed</b>   | 1,500 min <sup>-1</sup>               |
| <b>Bearing lifetime</b>  | 2 x 10 <sup>9</sup> revolutions       |
| <b>Maximum travel/deflection of spring arm</b>                             | 8 mm at 14 N spring travel            |
| <b>Recommended pretension</b>  | 8 N at 4 mm deflection <sup>2)</sup>  |
| <b>Max. permissible working area for the spring (continuous operation)</b> | ± 1.5 mm                              |
| <b>Recommended spring deflection</b>                                       | 2 mm ... 8 mm                         |
| <b>Mounted encoder</b>   | DBS50 Core, DBS50E-SKEKA1000          |

<sup>1)</sup> The surface of a measuring wheel is subject to wear. This depends on contact pressure, acceleration behavior in the application, traversing speed, measurement surface, mechanical alignment of the measuring wheel, temperature, and ambient conditions. We recommend you regularly check the condition of the measuring wheel and replace as required.

<sup>2)</sup> When measured from the top of the measuring surface.

## Ambient data

|                                    |  |
|------------------------------------|--|
| <b>EMC</b>                         | According to EN 61000-6-2 and EN 61000-6-3 (class A) |
| <b>Enclosure rating</b>            | IP65   |
| <b>Operating temperature range</b> | -20 °C ... +60 °C<br>-35 °C ... +95 °C (on request)  |
| <b>Storage temperature range</b>   | -40 °C ... +100 °C, without package                  |


## Certificates

|  |   |
|--|---|
| <b>EU declaration of conformity</b>  | ✓ |
| <b>UK declaration of conformity</b>  | ✓ |
| <b>ACMA declaration of conformity</b>  | ✓ |
| <b>China-RoHS</b>  | ✓ |
| <b>Information according to Art. 3 of Data Act (Regulation EU 2023/2854)</b> | ✓ |

## Classifications


|                       |          |
|-----------------------|----------|
| <b>ECLASS 5.0</b>     | 27270501 |
| <b>ECLASS 5.1.4</b>   | 27270501 |
| <b>ECLASS 6.0</b>     | 27270590 |
| <b>ECLASS 6.2</b>     | 27270590 |
| <b>ECLASS 7.0</b>     | 27270501 |
| <b>ECLASS 8.0</b>     | 27270501 |
| <b>ECLASS 8.1</b>     | 27270501 |
| <b>ECLASS 9.0</b>     | 27270501 |
| <b>ECLASS 10.0</b>    | 27270790 |
| <b>ECLASS 11.0</b>    | 27270707 |
| <b>ECLASS 12.0</b>    | 27270504 |
| <b>ETIM 5.0</b>       | EC001486 |
| <b>ETIM 6.0</b>       | EC001486 |
| <b>ETIM 7.0</b>       | EC001486 |
| <b>ETIM 8.0</b>       | EC001486 |
| <b>UNSPSC 16.0901</b> | 41112113 |

## Dimensional drawing Mounting plate 022-190-001-260




Dimensions in mm (inch)

## Dimensional drawing Mounting plate 022-190-001-270



Dimensions in mm (inch)

Dimensional drawing



Dimensions in mm (inch)

- ① M4 x 20 set screw
- ② 2 x Ø 5.5


PIN assignment

| PIN | Signal         | Explanation                 |
|-----|----------------|-----------------------------|
| 1   | U <sub>s</sub> | supply voltage <sup>①</sup> |
| 2   | B              | signal line                 |
| 3   | GND            | encoder ground connection   |
| 4   | A              | signal line                 |
| 5   | Z              | signal line for zero set    |



<sup>①</sup> Potentia free to housing  
View of the connector fitted to the encoder body

## Diagrams



## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is "Sensor Intelligence."**

## WORLDWIDE PRESENCE:

Contacts and other locations [www.sick.com](http://www.sick.com)