



# GTE10-P1221


G10

PHOTOELECTRIC SENSORS

**SICK**  
Sensor Intelligence.



Illustration may differ



## Ordering information

| Type        | part no. |
|-------------|----------|
| GTE10-P1221 | 1085298  |

Other models and accessories → [www.sick.com/G10](http://www.sick.com/G10)

## Detailed technical data

### Features

|                                        |                                  |
|----------------------------------------|----------------------------------|
| <b>Functional principle</b>            | Photoelectric proximity sensor   |
| <b>Functional principle detail</b>     | Energetic                        |
| <b>Dimensions (W x H x D)</b>          | 20 mm x 50 mm x 39 mm            |
| <b>Housing design (light emission)</b> | Rectangular                      |
| <b>Sensing range max.</b>              | 20 mm ... 2,000 mm <sup>1)</sup> |
| <b>Sensing range</b>                   | 40 mm ... 1,400 mm <sup>1)</sup> |
| <b>Type of light</b>                   | Infrared light                   |
| <b>Light source</b>                    | LED <sup>2)</sup>                |
| <b>Light spot size (distance)</b>      | Ø 57 mm (1,500 mm)               |
| <b>Wave length</b>                     | 850 nm                           |
| <b>Adjustment</b>                      | Potentiometer, 270°              |

<sup>1)</sup> Object with 90% remission (based on standard white, DIN 5033).

<sup>2)</sup> Average service life: 100,000 h at T<sub>U</sub> = +25 °C.

### Mechanics/electronics

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| <b>Supply voltage U<sub>B</sub></b> | 10 V DC ... 30 V DC <sup>1)</sup> |
|-------------------------------------|-----------------------------------|

<sup>1)</sup> Limit values when operated in short-circuit protected network: max. 8 A.

<sup>2)</sup> May not fall below or exceed U<sub>V</sub> tolerances.

<sup>3)</sup> Signal transit time with resistive load.

<sup>4)</sup> With light/dark ratio 1:1.

<sup>5)</sup> Do not bend below 0 °C.

<sup>6)</sup> A = V<sub>S</sub> connections reverse-polarity protected.

<sup>7)</sup> B = inputs and output reverse-polarity protected.

<sup>8)</sup> C = interference suppression.

<sup>9)</sup> D = outputs overcurrent and short-circuit protected.

<sup>10)</sup> Complies with the UL325 standard when used with sturdy protection hood (e.g. BEF-G10WSG, 2071960).

|                                            |                                                                          |
|--------------------------------------------|--------------------------------------------------------------------------|
| <b>Ripple</b>                              | < 5 V <sub>pp</sub> <sup>2)</sup>                                        |
| <b>Current consumption</b>                 | 20 mA                                                                    |
| <b>Switching output</b>                    | PNP                                                                      |
| <b>Switching mode</b>                      | Light/dark switching                                                     |
| <b>Switching mode selector</b>             | Selectable via light/dark selector                                       |
| <b>Output current I<sub>max.</sub></b>     | ≤ 100 mA                                                                 |
| <b>Response time</b>                       | ≤ 500 μs <sup>3)</sup>                                                   |
| <b>Switching frequency</b>                 | 1,000 Hz <sup>4)</sup>                                                   |
| <b>Connection type</b>                     | Cable, 3-wire, 2 m <sup>5)</sup>                                         |
| <b>Cable material</b>                      | Plastic, PVC                                                             |
| <b>Conductor cross section</b>             | 0.14 mm <sup>2</sup>                                                     |
| <b>Circuit protection</b>                  | A <sup>6)</sup><br>B <sup>7)</sup><br>C <sup>8)</sup><br>D <sup>9)</sup> |
| <b>Protection class</b>                    | III                                                                      |
| <b>Weight</b>                              | 90 g                                                                     |
| <b>Housing material</b>                    | Plastic, ABS/PMMA                                                        |
| <b>Enclosure rating</b>                    | IP67                                                                     |
| <b>Electromagnetic compatibility (EMC)</b> | EN 60947-5-2                                                             |
| <b>Ambient operating temperature</b>       | -30 °C ... +60 °C                                                        |
| <b>Ambient temperature, storage</b>        | -40 °C ... +70 °C                                                        |
| <b>UL File No.</b>                         | NRKH.E348498 & NRKH7.E348498                                             |
| <b>More standards</b>                      | UL325 <sup>10)</sup>                                                     |

<sup>1)</sup> Limit values when operated in short-circuit protected network: max. 8 A.

<sup>2)</sup> May not fall below or exceed U<sub>y</sub> tolerances.

<sup>3)</sup> Signal transit time with resistive load.

<sup>4)</sup> With light/dark ratio 1:1.

<sup>5)</sup> Do not bend below 0 °C.

<sup>6)</sup> A = V<sub>S</sub> connections reverse-polarity protected.

<sup>7)</sup> B = inputs and output reverse-polarity protected.

<sup>8)</sup> C = interference suppression.

<sup>9)</sup> D = outputs overcurrent and short-circuit protected.

<sup>10)</sup> Complies with the UL325 standard when used with sturdy protection hood (e.g. BEF-G10WSG, 2071960).


## Certificates

|                                                          |   |
|----------------------------------------------------------|---|
| <b>EU declaration of conformity</b>                      | ✓ |
| <b>UK declaration of conformity</b>                      | ✓ |
| <b>ACMA declaration of conformity</b>                    | ✓ |
| <b>Moroccan declaration of conformity</b>                | ✓ |
| <b>China-RoHS</b>                                        | ✓ |
| <b>cULus certificate</b>                                 | ✓ |
| <b>Photobiological safety (DIN EN 62471) certificate</b> | ✓ |

Classifications


|                       |          |
|-----------------------|----------|
| <b>ECLASS 5.0</b>     | 27270903 |
| <b>ECLASS 5.1.4</b>   | 27270903 |
| <b>ECLASS 6.0</b>     | 27270903 |
| <b>ECLASS 6.2</b>     | 27270903 |
| <b>ECLASS 7.0</b>     | 27270903 |
| <b>ECLASS 8.0</b>     | 27270903 |
| <b>ECLASS 8.1</b>     | 27270903 |
| <b>ECLASS 9.0</b>     | 27270903 |
| <b>ECLASS 10.0</b>    | 27270904 |
| <b>ECLASS 11.0</b>    | 27270904 |
| <b>ECLASS 12.0</b>    | 27270903 |
| <b>ETIM 5.0</b>       | EC001821 |
| <b>ETIM 6.0</b>       | EC001821 |
| <b>ETIM 7.0</b>       | EC002719 |
| <b>ETIM 8.0</b>       | EC002719 |
| <b>UNSPSC 16.0901</b> | 39121528 |

Adjustments




- ⑥ Adjustment of sensing range
- ⑦ Light/dark selector

Connection diagram Cd-044




## Operating reserve

Operating reserve




- ① Sensing range on white, 90% remission factor
- ② Sensing range on gray, 18% remission factor
- ③ Sensing range on black, 6% remission factor

## Light spot size




## scanning range



■ Sensing range      ■ Sensing range max.

- ① Sensing range on white, 90% remission factor
- ② Sensing range on gray, 18% remission factor
- ③ Sensing range on black, 6% remission factor

Dimensional drawing CableGTE10, GL10, GL10G, DC, connector



Recommended accessories

Other models and accessories → [www.sick.com/G10](http://www.sick.com/G10)

|                                                                                     | Brief description                                                                                                                                                                                                                                                                               | Type          | part no. |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|----------|
| connectors and cables                                                               |                                                                                                                                                                                                                                                                                                 |               |          |
|  | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Male connector, M8, 3-pin, straight, A-coded</li><li>• <b>Description:</b> Unshielded</li><li>• <b>Connection systems:</b> Screw-type terminals</li><li>• <b>Permitted cross-section:</b> 0.14 mm² ... 0.5 mm²</li></ul> | STE-0803-G    | 6037322  |
| Mounting systems                                                                    |                                                                                                                                                                                                                                                                                                 |               |          |
|  | <ul style="list-style-type: none"><li>• <b>Description:</b> Q-Lock, bar clamp system for G10 and reflector P250</li><li>• <b>Material:</b> Zinc diecast, steel</li><li>• <b>Details:</b> Die-cast zinc, steel, zinc coated</li><li>• <b>Suitable for:</b> G10 and reflector P250</li></ul>      | BEF-KHSQ12R01 | 2071260  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)