




# MZT7-03VNS-KR0

## MZT7

CYLINDER SENSORS


**SICK**  
Sensor Intelligence.



## Ordering information

| Type           | part no. |
|----------------|----------|
| MZT7-03VNS-KR0 | 1070823  |

Other models and accessories → [www.sick.com/MZT7](http://www.sick.com/MZT7)



## Detailed technical data

### Features

|                                    |                                                                                                                            |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| <b>Cylinder type</b>               | T-slot                                                                                                                     |
| <b>Cylinder types with adapter</b> | Profile cylinder<br>Tie rod cylinder<br>Round body cylinder<br>Dovetail groove cylinder<br>SMC rail CDQ2<br>SMC rail ECDQ2 |
| <b>Housing length</b>              | 29.5 mm                                                                                                                    |
| <b>Switching output</b>            | NPN                                                                                                                        |
| <b>Switching frequency</b>         | 1,000 Hz                                                                                                                   |
| <b>Output function</b>             | NO                                                                                                                         |
| <b>Electrical wiring</b>           | DC 3-wire                                                                                                                  |
| <b>Enclosure rating</b>            | IP65 <sup>1)</sup><br>IP67                                                                                                 |

<sup>1)</sup> According to EN 60529.

### Mechanics/electronics

|                                         |                        |
|-----------------------------------------|------------------------|
| <b>Supply voltage</b>                   | 10 V DC ... 30 V DC    |
| <b>Power consumption</b>                | 8 mA, without load     |
| <b>Voltage drop</b>                     | ≤ 2 V                  |
| <b>Continuous current I<sub>a</sub></b> | ≤ 100 mA               |
| <b>Protection class</b>                 | III                    |
| <b>Response sensitivity, typ.</b>       | 3 mT                   |
| <b>Overrun distance, typ.</b>           | 10 mm                  |
| <b>Hysteresis, typ.</b>                 | < 0.8 mT               |
| <b>Reproducibility</b>                  | ≤ 0.1 mT <sup>1)</sup> |
| <b>Reverse polarity protection</b>      | Yes                    |
| <b>Short-circuit protection</b>         | Yes                    |

<sup>1)</sup> Supply voltage U<sub>B</sub> and constant ambient temperature T<sub>a</sub>.

|                                       |                                                                                        |
|---------------------------------------|----------------------------------------------------------------------------------------|
| <b>Status indicator LED</b>           | Yes                                                                                    |
| <b>Teach-in</b>                       | No                                                                                     |
| <b>Ambient operating temperature</b>  | -30 °C ... +80 °C                                                                      |
| <b>Shock and vibration resistance</b> | 30 g, 11 ms / 10 ... 55 Hz, 1 mm                                                       |
| <b>EMC</b>                            | According to EN 60947-5-2                                                              |
| <b>Connection type</b>                | Cable with connector M8, 3-pin, with knurled nut, drag chain use, 0.5 m                |
| <b>Connection type Detail</b>         |                                                                                        |
| Conductor cross section               | 0.14 mm²                                                                               |
| Cable diameter                        | Ø 2.9 mm                                                                               |
| Bending radius                        | With fixed installation > 8 x cable diameter<br>For flexible use > 12 x cable diameter |
| Cable outlet                          | Axial                                                                                  |
| <b>Material</b>                       |                                                                                        |
| Housing                               | Plastic                                                                                |
| Cable                                 | PUR                                                                                    |
| <b>UL File No.</b>                    | NRKH.E181493 & NRKH7.E181493                                                           |

<sup>1)</sup> Supply voltage  $U_B$  and constant ambient temperature  $T_a$ .

## Safety-related parameters

|                                     |             |
|-------------------------------------|-------------|
| <b>MTTF<sub>D</sub></b>             | 1,300 years |
| <b>DC<sub>avg</sub></b>             | 0 %         |
| <b>T<sub>M</sub> (mission time)</b> | 20 years    |

## Certificates


|                                           |   |
|-------------------------------------------|---|
| <b>EU declaration of conformity</b>       | ✓ |
| <b>UK declaration of conformity</b>       | ✓ |
| <b>ACMA declaration of conformity</b>     | ✓ |
| <b>Moroccan declaration of conformity</b> | ✓ |
| <b>China-RoHS</b>                         | ✓ |
| <b>cULus certificate</b>                  | ✓ |

## Classifications


|                     |          |
|---------------------|----------|
| <b>ECLASS 5.0</b>   | 27270104 |
| <b>ECLASS 5.1.4</b> | 27270104 |
| <b>ECLASS 6.0</b>   | 27270104 |
| <b>ECLASS 6.2</b>   | 27270104 |
| <b>ECLASS 7.0</b>   | 27270104 |
| <b>ECLASS 8.0</b>   | 27270104 |
| <b>ECLASS 8.1</b>   | 27270104 |
| <b>ECLASS 9.0</b>   | 27270104 |
| <b>ECLASS 10.0</b>  | 27270104 |
| <b>ECLASS 11.0</b>  | 27270104 |
| <b>ECLASS 12.0</b>  | 27274301 |

|                |          |
|----------------|----------|
| ETIM 5.0       | EC002544 |
| ETIM 6.0       | EC002544 |
| ETIM 7.0       | EC002544 |
| ETIM 8.0       | EC002544 |
| UNSPSC 16.0901 | 39122230 |


Installation note



Connection diagram Cd-002



Dimensional drawing Cable with connector M8, with knurled nut



- Dimensions in mm (inch)
- ① Connection
  - ② Position sensor element
  - ③ Display LED
  - ④ Fixing screw SW 2.5
  - ⑤ retaining ribs

| Part no. | Type              | L       | Number of cores |
|----------|-------------------|---------|-----------------|
| 1094040  | MZT7-03VPS-KRDS10 | 150 mm  | 3               |
| 1082422  | MZT7-03VPS-KRD    | 300 mm  | 3               |
| 1084695  | MZT7-03VPS-KRDS04 | 300 mm  | 3               |
| 1089066  | MZT7-03VNS-KRD    | 300 mm  | 3               |
| 1070821  | MZT7-03VPS-KR0    | 500 mm  | 3               |
| 1070823  | MZT7-03VPS-KR0    | 500 mm  | 3               |
| 1084694  | MZT7-03VPS-KR0S03 | 500 mm  | 3               |
| 1088702  | MZT7-03VPS-KRDS08 | 1000 mm | 3               |

### Recommended accessories

Other models and accessories → [www.sick.com/MZT7](http://www.sick.com/MZT7)

|                                                                                     | Brief description                                                                                                                                                                                                                                                                                                                                                                                                | Type            | part no. |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------|
| Mounting systems                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |          |
|    | <ul style="list-style-type: none"> <li>• <b>Description:</b> Mounting bracket on round body cylinder with piston diameter of 8 mm ... 130 mm, ambient temperature min -30 °C max 80 °C</li> <li>• <b>Material:</b> Stainless steel, Zinc cast</li> <li>• <b>Details:</b> Stainless steel, Zinc cast</li> <li>• <b>Packing unit:</b> 1 piece</li> <li>• <b>Suitable for:</b> T-slot</li> </ul>                    | BEF-KHZ-RT1-130 | 2077684  |
|    | <ul style="list-style-type: none"> <li>• <b>Description:</b> Mounting bracket on round body cylinder with piston diameter of 8 mm ... 25 mm, ambient temperature min -30 °C max 80 °C</li> <li>• <b>Material:</b> Stainless steel, Zinc cast</li> <li>• <b>Details:</b> Stainless steel, Zinc cast</li> <li>• <b>Packing unit:</b> 1 piece</li> <li>• <b>Suitable for:</b> T-slot</li> </ul>                     | BEF-KHZ-RT1-25  | 2077682  |
|    | <ul style="list-style-type: none"> <li>• <b>Description:</b> Mounting bracket on round body cylinder with piston diameter of 8 mm ... 63 mm, ambient temperature min -30 °C max 80 °C</li> <li>• <b>Material:</b> Stainless steel, Zinc cast</li> <li>• <b>Details:</b> Stainless steel, Zinc cast</li> <li>• <b>Packing unit:</b> 1 piece</li> <li>• <b>Suitable for:</b> T-slot</li> </ul>                     | BEF-KHZ-RT1-63  | 2077683  |
|    | <ul style="list-style-type: none"> <li>• <b>Description:</b> Mounting bracket on round body cylinder with piston diameter of 12 mm, ambient temperature min 0 °C max 50 °C</li> <li>• <b>Dimensions (W x H x L):</b> 22.4 m</li> <li>• <b>Material:</b> Plastic, Aluminum</li> <li>• <b>Details:</b> Plastic, Aluminum</li> <li>• <b>Packing unit:</b> 1 piece</li> <li>• <b>Suitable for:</b> T-slot</li> </ul> | BEF-KHZ-RT-12   | 2077681  |
|   | <ul style="list-style-type: none"> <li>• <b>Description:</b> Mounting bracket on round body cylinder with piston diameter of 16 mm, ambient temperature min 0 °C max 50 °C</li> <li>• <b>Dimensions (W x H x L):</b> 26.6 m</li> <li>• <b>Material:</b> Plastic, Aluminum</li> <li>• <b>Details:</b> Plastic, Aluminum</li> <li>• <b>Packing unit:</b> 1 piece</li> <li>• <b>Suitable for:</b> T-slot</li> </ul> | BEF-KHZ-RT-16   | 2077680  |
|  | <ul style="list-style-type: none"> <li>• <b>Description:</b> Mounting bracket on round body cylinder with piston diameter of 20 mm, ambient temperature min 0 °C max 50 °C</li> <li>• <b>Dimensions (W x H x L):</b> 30.6 m</li> <li>• <b>Material:</b> Plastic, Aluminum</li> <li>• <b>Details:</b> Plastic, Aluminum</li> <li>• <b>Packing unit:</b> 1 piece</li> <li>• <b>Suitable for:</b> T-slot</li> </ul> | BEF-KHZ-RT-20   | 2077679  |
|  | <ul style="list-style-type: none"> <li>• <b>Description:</b> Mounting bracket on round body cylinder with piston diameter of 25 mm, ambient temperature min 0 °C max 50 °C</li> <li>• <b>Dimensions (W x H x L):</b> 35.7 m</li> <li>• <b>Material:</b> Plastic, Aluminum</li> <li>• <b>Details:</b> Plastic, Aluminum</li> <li>• <b>Packing unit:</b> 1 piece</li> <li>• <b>Suitable for:</b> T-slot</li> </ul> | BEF-KHZ-RT-25   | 2077678  |
|  | <ul style="list-style-type: none"> <li>• <b>Description:</b> Mounting bracket on round body cylinder with piston diameter of 32 mm, ambient temperature min 0 °C max 50 °C</li> <li>• <b>Dimensions (W x H x L):</b> 42.9 m</li> <li>• <b>Material:</b> Plastic, Aluminum</li> <li>• <b>Details:</b> Plastic, Aluminum</li> <li>• <b>Packing unit:</b> 1 piece</li> <li>• <b>Suitable for:</b> T-slot</li> </ul> | BEF-KHZ-RT-32   | 2077677  |
|  | <ul style="list-style-type: none"> <li>• <b>Description:</b> Mounting bracket on round body cylinder with piston diameter of 40 mm, ambient temperature min 0 °C max 50 °C</li> <li>• <b>Dimensions (W x H x L):</b> 50.9 m</li> <li>• <b>Material:</b> Plastic, Aluminum</li> <li>• <b>Details:</b> Plastic, Aluminum</li> <li>• <b>Packing unit:</b> 1 piece</li> </ul>                                        | BEF-KHZ-RT-40   | 2077676  |

|                                                                                     | Brief description                                                                                                                                                                                                                                                                                                                                                                                                                                | Type          | part no. |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|----------|
|    | <ul style="list-style-type: none"><li>• <b>Suitable for:</b> T-slot</li><li>• <b>Description:</b> Mounting bracket on round body cylinder with piston diameter of 50 mm, ambient temperature min 0 °C max 50 °C</li><li>• <b>Dimensions (W x H x L):</b> 61.8 mm</li><li>• <b>Material:</b> Plastic, Aluminum</li><li>• <b>Details:</b> Plastic, Aluminum</li><li>• <b>Packing unit:</b> 1 piece</li><li>• <b>Suitable for:</b> T-slot</li></ul> | BEF-KHZ-RT-50 | 2077675  |
|    | <ul style="list-style-type: none"><li>• <b>Description:</b> Mounting bracket on round body cylinder with piston diameter of 63 mm, ambient temperature min 0 °C max 50 °C</li><li>• <b>Dimensions (W x H x L):</b> 73.9 mm</li><li>• <b>Material:</b> Plastic, Aluminum</li><li>• <b>Details:</b> Plastic, Aluminum</li><li>• <b>Packing unit:</b> 1 piece</li><li>• <b>Suitable for:</b> T-slot</li></ul>                                       | BEF-KHZ-RT-63 | 2077674  |
|    | <ul style="list-style-type: none"><li>• <b>Description:</b> Mounting bracket for integrated profile cylinder/tie-rod cylinder</li><li>• <b>Material:</b> Zinc diecast</li><li>• <b>Details:</b> Zinc diecast</li><li>• <b>Items supplied:</b> Mounting hardware included</li></ul>                                                                                                                                                               | BEF-KHZ-PT1   | 2022702  |
|    | <ul style="list-style-type: none"><li>• <b>Description:</b> Mounting bracket for mounting on SMC rails ECDQ2 (T-slot)</li><li>• <b>Material:</b> Aluminum</li><li>• <b>Details:</b> Aluminum</li><li>• <b>Items supplied:</b> Without mounting hardware</li></ul>                                                                                                                                                                                | BEF-KHZ-TT1   | 2046439  |
|    | <ul style="list-style-type: none"><li>• <b>Description:</b> Mounting bracket for mounting on SMC rails CDQ2 (T-slot)</li><li>• <b>Material:</b> Aluminum</li><li>• <b>Details:</b> Aluminum</li><li>• <b>Items supplied:</b> Without mounting hardware</li></ul>                                                                                                                                                                                 | BEF-KHZ-TT2   | 2046440  |
|   | <ul style="list-style-type: none"><li>• <b>Description:</b> Mounting bracket for cylinder with dovetail slot</li><li>• <b>Material:</b> Aluminum</li><li>• <b>Details:</b> Aluminum</li><li>• <b>Items supplied:</b> Without mounting hardware</li></ul>                                                                                                                                                                                         | BEF-KHZ-ST1   | 2022703  |
| device protection and care                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                  |               |          |
|  | <ul style="list-style-type: none"><li>• <b>Description:</b> Protective adapter</li><li>• <b>Material:</b> Zinc diecast</li><li>• <b>Items supplied:</b> Mounting hardware included</li><li>• <b>Suitable for:</b> MZT7, RZT7, MZT8</li></ul>                                                                                                                                                                                                     | BEF-SG-MRZT   | 2077201  |

|                                                                                     | Brief description                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Type               | part no. |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------|
| connectors and cables                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                    |          |
|    | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Male connector, M8, 3-pin, straight, A-coded</li> <li><b>Description:</b> Unshielded</li> <li><b>Connection systems:</b> Screw-type terminals</li> <li><b>Permitted cross-section:</b> 0.14 mm² ... 0.5 mm²</li> </ul>                                                                                                                                                                             | STE-0803-G         | 6037322  |
|    | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M8, 3-pin, straight, A-coded</li> <li><b>Description:</b> Unshielded</li> <li><b>Connection systems:</b> Screw-type terminals</li> <li><b>Permitted cross-section:</b> 0.14 mm² ... 0.5 mm²</li> </ul>                                                                                                                                                                           | DOS-0803-G         | 7902077  |
|    | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M8, 3-pin, angled, A-coded</li> <li><b>Description:</b> Unshielded</li> <li><b>Connection systems:</b> Solder connection</li> <li><b>Permitted cross-section:</b> ≤ 0.25 mm²</li> </ul>                                                                                                                                                                                          | DOS-0803-W         | 7902078  |
|    | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M8, 3-pin, straight, A-coded</li> <li><b>Connection type head B:</b> Flying leads</li> <li><b>Signal type:</b> Sensor/actuator cable</li> <li><b>Cable:</b> 2 m, 3-wire, PVC</li> <li><b>Description:</b> Sensor/actuator cable, unshielded</li> <li><b>Application:</b> Zones with chemicals, Untaminated zones</li> </ul>                                                      | YF8U13-020VA1XLEAX | 2095860  |
|    | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M8, 3-pin, straight, A-coded</li> <li><b>Connection type head B:</b> Flying leads</li> <li><b>Signal type:</b> Sensor/actuator cable</li> <li><b>Cable:</b> 5 m, 3-wire, PVC</li> <li><b>Description:</b> Sensor/actuator cable, unshielded</li> <li><b>Application:</b> Zones with chemicals, Untaminated zones</li> </ul>                                                      | YF8U13-050VA1XLEAX | 2095884  |
|   | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M8, 3-pin, angled, A-coded</li> <li><b>Connection type head B:</b> Flying leads</li> <li><b>Signal type:</b> Sensor/actuator cable</li> <li><b>Cable:</b> 2 m, 3-wire, PVC</li> <li><b>Description:</b> Sensor/actuator cable, unshielded</li> <li><b>Application:</b> Zones with chemicals, Untaminated zones</li> </ul>                                                        | YG8U13-020VA1XLEAX | 2096165  |
|  | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M8, 3-pin, angled, A-coded</li> <li><b>Connection type head B:</b> Flying leads</li> <li><b>Signal type:</b> Sensor/actuator cable</li> <li><b>Cable:</b> 5 m, 3-wire, PVC</li> <li><b>Description:</b> Sensor/actuator cable, unshielded</li> <li><b>Application:</b> Zones with chemicals, Untaminated zones</li> </ul>                                                        | YG8U13-050VA1XLEAX | 2096166  |
|  | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M8, 3-pin, straight, A-coded</li> <li><b>Connection type head B:</b> Flying leads</li> <li><b>Signal type:</b> Sensor/actuator cable</li> <li><b>Cable:</b> 2 m, 3-wire, PUR, halogen-free</li> <li><b>Description:</b> Sensor/actuator cable, unshielded</li> <li><b>Application:</b> Untaminated zones, Zones with oils and lubricants, Robot, Drag chain operation</li> </ul> | YF8U13-020UA1XLEAX | 2094782  |
|  | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M8, 3-pin, straight, A-coded</li> <li><b>Connection type head B:</b> Flying leads</li> <li><b>Signal type:</b> Sensor/actuator cable</li> <li><b>Cable:</b> 5 m, 3-wire, PUR, halogen-free</li> <li><b>Description:</b> Sensor/actuator cable, unshielded</li> <li><b>Application:</b> Untaminated zones, Zones with oils and lubricants, Robot, Drag chain operation</li> </ul> | YF8U13-050UA1XLEAX | 2094788  |
|  | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M8, 3-pin, angled, A-coded</li> <li><b>Connection type head B:</b> Flying leads</li> <li><b>Signal type:</b> Sensor/actuator cable</li> <li><b>Cable:</b> 2 m, 3-wire, PUR, halogen-free</li> <li><b>Description:</b> Sensor/actuator cable, unshielded</li> <li><b>Application:</b> Untaminated zones, Zones with oils and lubricants, Robot, Drag chain operation</li> </ul>   | YG8U13-020UA1XLEAX | 2094794  |
|  | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M8, 3-pin, angled, A-coded</li> <li><b>Connection type head B:</b> Flying leads</li> <li><b>Signal type:</b> Sensor/actuator cable</li> <li><b>Cable:</b> 5 m, 3-wire, PUR, halogen-free</li> <li><b>Description:</b> Sensor/actuator cable, unshielded</li> </ul>                                                                                                               | YG8U13-050UA1XLEAX | 2095586  |

|                                                                                   | Brief description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Type               | part no. |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------|
|  | <ul style="list-style-type: none"><li>• <b>Application:</b> Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation</li><li>• <b>Connection type head A:</b> Female connector, M8, 3-pin, angled, A-coded</li><li>• <b>Connection type head B:</b> Flying leads</li><li>• <b>Signal type:</b> Sensor/actuator cable</li><li>• <b>Cable:</b> 0.6 m, 3-wire, PUR, halogen-free</li><li>• <b>Description:</b> Sensor/actuator cable, unshielded</li><li>• <b>Application:</b> Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation</li></ul> | YG8U13-C60UA1XLEAX | 2145889  |
|                                                                                   | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Female connector, M8, 3-pin, angled, A-coded</li><li>• <b>Connection type head B:</b> Flying leads</li><li>• <b>Signal type:</b> Sensor/actuator cable</li><li>• <b>Cable:</b> 3 m, 3-wire, PUR, halogen-free</li><li>• <b>Description:</b> Sensor/actuator cable, unshielded</li><li>• <b>Application:</b> Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation</li></ul>                                                                                                                   | YG8U13-030UA1XLEAX | 2145891  |
|                                                                                   | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Female connector, M8, 3-pin, straight, A-coded</li><li>• <b>Connection type head B:</b> Flying leads</li><li>• <b>Signal type:</b> Sensor/actuator cable</li><li>• <b>Cable:</b> 0.6 m, 3-wire, PVC</li><li>• <b>Description:</b> Sensor/actuator cable, unshielded</li><li>• <b>Application:</b> Zones with chemicals, Uncontaminated zones</li></ul>                                                                                                                                                                    | YF8U13-C60VA1XLEAX | 2146368  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)