



# PFT-FRB016SF20SSVLSSZ

PFT

PRESSURE SENSORS

**SICK**  
Sensor Intelligence.



Illustration may differ



## Ordering information

| Type                  | part no. |
|-----------------------|----------|
| PFT-FRB016SF20SSVLSSZ | 6044771  |

Other models and accessories → [www.sick.com/PFT](http://www.sick.com/PFT)

## Detailed technical data

### Features

|                                            |                                                                                                                                                                                     |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Medium</b>                              | Liquid, gaseous                                                                                                                                                                     |
| <b>Pressure type</b>                       | Gauge pressure                                                                                                                                                                      |
| <b>Pressure unit</b>                       | bar                                                                                                                                                                                 |
| <b>Measuring range</b>                     | 0 bar ... 16 bar                                                                                                                                                                    |
| <b>Process temperature</b>                 | -30 °C ... +100 °C                                                                                                                                                                  |
| <b>Maximum ohmic load <math>R_A</math></b> | 4 mA ... 20 mA, 2-wire ( $R_A \leq (L^+ - 10 \text{ V}) / 0.02 \text{ A [Ohm]}$ ), 0 V ... 5 V, 3-wire ( $R_A > 5 \text{ kOhm}$ ), 0 V ... 10 V, 3-wire ( $R_A > 10 \text{ kOhm}$ ) |
| <b>Output signal</b>                       | 0 V ... 10 V, 3-wire                                                                                                                                                                |
| <b>Specialty</b>                           | Without                                                                                                                                                                             |

### Mechanics/electronics

|                                    |                                                                                                                                                  |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Communication interface</b>     | -                                                                                                                                                |
| <b>Process connection</b>          | G ½ B flush-mounted with O-ring                                                                                                                  |
| <b>Wetted parts</b>                | Flush-mounted membrane: Stainless steel 1.4571 with NBR O-ring or FKM O-ring (FKM with integrated cooling element)                               |
| <b>Internal transmission fluid</b> | Synthetic oil (Not available for version with standard membrane for pressure ranges > 25 bar)                                                    |
| <b>Pressure port</b>               | Front-flush membrane                                                                                                                             |
| <b>Housing material</b>            | Stainless steel 1.4571                                                                                                                           |
| <b>Connection type</b>             | L-connector (DIN EN 175301-803 A)                                                                                                                |
| <b>Supply voltage</b>              | 14 V DC ... 30 V DC                                                                                                                              |
| <b>Electrical safety</b>           | Overvoltage protection: 36 V DC<br>Short-circuit protection: $Q_A$ towards M<br>Reverse polarity protection: $L^+$ to M<br>Protection class: III |
| <b>Dielectric strength</b>         | 500 V DC, NEC Class 02 power supply (low voltage and low current max. 100 VA even in the event of a fault)                                       |
| <b>CE-conformity</b>               | Pressure equipment directive: 2014/68/EU<br>EMC directive: 2004/108/EC, EN 61326-2-3                                                             |

<sup>1)</sup> Enclosure rating IP per IEC 60529. The enclosure rating classes specified only apply when connected with female connectors that provide the corresponding enclosure rating.

|                         |                                                                                                              |
|-------------------------|--------------------------------------------------------------------------------------------------------------|
| Weight sensor           | Approx. 200 g                                                                                                |
| Seal                    | NBR                                                                                                          |
| Enclosure rating        | IP65 <sup>1)</sup>                                                                                           |
| Protection class III    | ✓                                                                                                            |
| MTTF                    | 452 years                                                                                                    |
| Pressure peak dampening | Through optional integrated pressure port 0.6 mm or 0.3 mm for process connector G ¼ according to DIN 3852-E |

<sup>1)</sup> Enclosure rating IP per IEC 60529. The enclosure rating classes specified only apply when connected with female connectors that provide the corresponding enclosure rating.

Performance

|                                                    |                                                                                                                                                                                                                                                                                                       |
|----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Non-linearity                                      | ≤ ± 0.2 %, of span (Best Fit Straight Line, BFSL) according to IEC 61298-2                                                                                                                                                                                                                            |
| Accuracy                                           | ≤ ± 0.5 %, of the span (= ± 0.25% of the span (optionally for pressure ranges = 0.25 bar). applies inclusive of nonlinearity, hysteresis, non-repeatability, zero-point and full-scale error (corresponds to error of measurement as per IEC 61298-2) Calibrated with vertical installation position) |
| Non-repeatability                                  | ≤ ± 0.1 % of the span                                                                                                                                                                                                                                                                                 |
| Response time (10 % ... 90 %)                      | ≤ 1 ms ≤ 10 ms at medium temperatures below < -30 °C for pressure ranges up to 25 bar or with flush-mounted membrane                                                                                                                                                                                  |
| Long-term drift/one-year stability                 | ≤ ± 0.2 % of span (at reference conditions)                                                                                                                                                                                                                                                           |
| Temperature coefficient in rated temperature range | Mean TC of zero: ≤ 0.2 % of span / 10 K (< 0.4 % for pressure ranges ≤ 0.25 bar)<br>Mean TC of span ≤ 0.2 % of span / 10 K                                                                                                                                                                            |
| Rated temperature range                            | 0 °C ... +80 °C                                                                                                                                                                                                                                                                                       |
| Service life                                       | Minimum 10 Mio. load cycles                                                                                                                                                                                                                                                                           |

Ambient data

|                                |                                                                                                                                                                         |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature, operation | -20 °C ... +80 °C                                                                                                                                                       |
| Storage temperature            | -40 °C ... +100 °C, with flush-mounted membrane and cooling element -20 °C ... +100 °C                                                                                  |
| Shock load                     | 1000 g according to IEC 60068-2-27 (mechanical shock)<br>400 g according to IEC 60068-2-27 (mechanical shock) for version with integrated cooling element               |
| Vibration load                 | 20 g according to IEC 60068-2-6 (vibration under resonance)<br>10 g according to IEC 60068-2-6 (vibration undencer resonae) for version with integrated cooling element |

Classifications


|              |          |
|--------------|----------|
| ECLASS 5.0   | 27200614 |
| ECLASS 5.1.4 | 27200614 |
| ECLASS 6.0   | 27200614 |
| ECLASS 6.2   | 27200614 |
| ECLASS 7.0   | 27200614 |
| ECLASS 8.0   | 27200614 |
| ECLASS 8.1   | 27200614 |
| ECLASS 9.0   | 27200614 |
| ECLASS 10.0  | 27200614 |
| ECLASS 11.0  | 27200614 |
| ECLASS 12.0  | 27200614 |
| ETIM 5.0     | EC011478 |

|                |          |
|----------------|----------|
| ETIM 6.0       | EC011478 |
| ETIM 7.0       | EC011478 |
| ETIM 8.0       | EC011478 |
| UNSPSC 16.0901 | 41112410 |

Certificates


|                              |   |
|------------------------------|---|
| EU declaration of conformity | ✓ |
| UK declaration of conformity | ✓ |
| China-RoHS                   | ✓ |

Dimensional drawing G  $\frac{1}{2}$  B with cooling section




Dimensions in mm (inch)

Dimensional drawing G  $\frac{1}{2}$  B without cooling section




Dimensions in mm (inch)

Dimensional drawing Housing with L-connector (DIN EN 175301-803 A)



Dimensions in mm (inch)

Connection type



Recommended accessories

Other models and accessories → [www.sick.com/PFT](http://www.sick.com/PFT)

|                                                                                     | Brief description                                                                                                                                                                                                                        | Type               | part no. |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------|
| Mounting systems                                                                    |                                                                                                                                                                                                                                          |                    |          |
|  | <ul style="list-style-type: none"><li>• <b>Description:</b> Mounting bracket for simple and stable wall mounting of pressure sensors with 27 mm hexagon</li><li>• <b>Material:</b> Aluminum</li><li>• <b>Details:</b> Aluminum</li></ul> | BEF-FL-ALUPBS-HLDR | 5322501  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)