



# WSE4S-3F1330V


W4

PHOTOELECTRIC SENSORS

**SICK**  
Sensor Intelligence.



Illustration may differ



## Ordering information

| Type          | part no. |
|---------------|----------|
| WSE4S-3F1330V | 1052880  |

Other models and accessories → [www.sick.com/W4](http://www.sick.com/W4)

## Detailed technical data

### Features

|                                             |                                           |
|---------------------------------------------|-------------------------------------------|
| <b>Functional principle</b>                 | Through-beam photoelectric sensor         |
| <b>Sensing range max.</b>                   | 0 m ... 5 m                               |
| <b>Sensing range</b>                        | 0 m ... 4.5 m                             |
| <b>Emitted beam</b>                         |                                           |
| Light source                                | PinPoint LED <sup>1)</sup>                |
| Type of light                               | Visible red light                         |
| Light spot size (distance)                  | Ø 50 mm (2 m)                             |
| <b>Key LED figures</b>                      |                                           |
| Wave length                                 | 650 nm                                    |
| <b>Adjustment</b>                           | None                                      |
| <b>Special applications</b>                 | Hygienic and washdown zones               |
| <b>Part number of individual components</b> | 2058460 WS4S-3D1330V 2058687 WE4S-3F1330V |
| <b>Housing design</b>                       | Washdown                                  |

<sup>1)</sup> Average service life: 100,000 h at T<sub>U</sub> = +25 °C.

### Safety-related parameters

|                                     |           |
|-------------------------------------|-----------|
| <b>MTTF<sub>D</sub></b>             | 968 years |
| <b>DC<sub>avg</sub></b>             | 0 %       |
| <b>T<sub>M</sub> (mission time)</b> | 20 years  |

## Electronics

|                                        |                                                       |
|----------------------------------------|-------------------------------------------------------|
| <b>Supply voltage <math>U_B</math></b> | 10 V DC ... 30 V DC <sup>1)</sup>                     |
| <b>Ripple</b>                          | < 5 V <sub>pp</sub> <sup>2)</sup>                     |
| <b>Protection class</b>                | III                                                   |
| <b>Digital output</b>                  |                                                       |
| Type                                   | PNP                                                   |
| Switching mode                         | Dark switching                                        |
| Output current I <sub>max.</sub>       | ≤ 100 mA                                              |
| Response time                          | < 0.5 ms <sup>3)</sup>                                |
| Switching frequency                    | 1,000 Hz <sup>4)</sup>                                |
| <b>Circuit protection</b>              | A <sup>5)</sup><br>B <sup>6)</sup><br>C <sup>7)</sup> |
| <b>Test input sender off</b>           | TE to 0 V                                             |

<sup>1)</sup> Limit values, reverse-polarity protected, operation in short-circuit protected network: max. 8 A.

<sup>2)</sup> May not fall below or exceed U<sub>y</sub> tolerances.

<sup>3)</sup> Signal transit time with resistive load.

<sup>4)</sup> With light/dark ratio 1:1.

<sup>5)</sup> A = V<sub>S</sub> connections reverse-polarity protected.

<sup>6)</sup> B = inputs and output reverse-polarity protected.

<sup>7)</sup> C = interference suppression.

## Mechanics

|                               |                                           |
|-------------------------------|-------------------------------------------|
| <b>Housing</b>                | Rectangular                               |
| <b>Design detail</b>          | Slim                                      |
| <b>Dimensions (W x H x D)</b> | 15.25 mm x 48.6 mm x 22.2 mm              |
| <b>Connection</b>             | Cable, 3-wire, 2 m <sup>1)</sup>          |
| <b>Connection detail</b>      |                                           |
| Conductor size                | 0.14 mm <sup>2</sup>                      |
| Length of cable (L)           | 2 m <sup>1)</sup>                         |
| <b>Material</b>               |                                           |
| Housing                       | Metal, Stainless steel V4A (1.4404, 316L) |
| Front screen                  | Plastic, PMMA                             |
| Cable                         | Plastic, PVC                              |
| <b>Weight</b>                 | 80 g                                      |

<sup>1)</sup> Do not bend below 0 °C.

## Ambient data

|                                      |                                 |
|--------------------------------------|---------------------------------|
| <b>Enclosure rating</b>              | IP66<br>IP67<br>IP68<br>IP69K   |
| <b>Ambient operating temperature</b> | -30 °C ... +70 °C <sup>1)</sup> |
| <b>Ambient temperature, storage</b>  | -30 °C ... +75 °C               |

<sup>1)</sup> At UV ≤ 24 V and IA < 30 mA.

|             |                              |
|-------------|------------------------------|
| UL File No. | NRKH.E181493 & NRKH7.E181493 |
|-------------|------------------------------|

<sup>1)</sup> At UV ≤ 24 V and IA < 30 mA.


Certificates

|                                                   |   |
|---------------------------------------------------|---|
| EU declaration of conformity                      | ✓ |
| UK declaration of conformity                      | ✓ |
| ACMA declaration of conformity                    | ✓ |
| Moroccan declaration of conformity                | ✓ |
| China-RoHS                                        | ✓ |
| ECOLAB certificate                                | ✓ |
| cULus certificate                                 | ✓ |
| Photobiological safety (DIN EN 62471) certificate | ✓ |


Classifications

|                |          |
|----------------|----------|
| ECLASS 5.0     | 27270901 |
| ECLASS 5.1.4   | 27270901 |
| ECLASS 6.0     | 27270901 |
| ECLASS 6.2     | 27270901 |
| ECLASS 7.0     | 27270901 |
| ECLASS 8.0     | 27270901 |
| ECLASS 8.1     | 27270901 |
| ECLASS 9.0     | 27270901 |
| ECLASS 10.0    | 27270901 |
| ECLASS 11.0    | 27270901 |
| ECLASS 12.0    | 27270901 |
| ETIM 5.0       | EC002716 |
| ETIM 6.0       | EC002716 |
| ETIM 7.0       | EC002716 |
| ETIM 8.0       | EC002716 |
| UNSPSC 16.0901 | 39121528 |


Connection diagram Cd-061




## Characteristic curve WSE4S-3V, WSE4S-3H



## Sensing range diagram WSE4S-3



Dimensional drawing WL4S-3V, WLG4S-3V, without single teach-in button



Dimensions in mm (inch)

- ① Center of optical axis
- ② Threaded mounting hole M8
- ③ LED indicator yellow: Status of received light beam
- ④ LED indicator green: Supply voltage active

Recommended accessories

Other models and accessories → [www.sick.com/W4](http://www.sick.com/W4)

|                                                                                     | Brief description                                                                                                                                                                                                                                                                                              | Type       | part no. |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|----------|
| connectors and cables                                                               |                                                                                                                                                                                                                                                                                                                |            |          |
|  | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Male connector, M8, 3-pin, straight, A-coded</li><li>• <b>Description:</b> Unshielded</li><li>• <b>Connection systems:</b> Screw-type terminals</li><li>• <b>Permitted cross-section:</b> 0.14 mm² ... 0.5 mm²</li></ul>                | STE-0803-G | 6037322  |
| Mounting systems                                                                    |                                                                                                                                                                                                                                                                                                                |            |          |
|  | <ul style="list-style-type: none"><li>• <b>Description:</b> Mounting bracket for floor mounting</li><li>• <b>Material:</b> Stainless steel</li><li>• <b>Details:</b> Stainless steel 1.4571</li><li>• <b>Items supplied:</b> Mounting hardware included</li><li>• <b>Suitable for:</b> W4S, W4F, W4S</li></ul> | BEF-W4-B   | 2051630  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)