



# WTB4S-3P3262H

W4

PHOTOELECTRIC SENSORS

**SICK**  
Sensor Intelligence.



Illustration may differ



Ordering information

| Type          | part no. |
|---------------|----------|
| WTB4S-3P3262H | 1048094  |

Other models and accessories → [www.sick.com/W4](http://www.sick.com/W4)

Detailed technical data

Features

|                                    |                            |                                |
|------------------------------------|----------------------------|--------------------------------|
| <b>Functional principle</b>        |                            | Photoelectric proximity sensor |
| <b>Functional principle detail</b> |                            | Background suppression         |
| <b>Sensing range max.</b>          |                            | 4 mm ... 500 mm <sup>1)</sup>  |
| <b>Sensing range</b>               |                            | 10 mm ... 350 mm <sup>1)</sup> |
| <b>Emitted beam</b>                | Light source               | PinPoint LED <sup>2)</sup>     |
|                                    | Type of light              | Visible red light              |
|                                    | Light spot size (distance) | Ø 6.5 mm (150 mm)              |
| <b>Key LED figures</b>             |                            |                                |
|                                    | Wave length                | 650 nm                         |
| <b>Adjustment</b>                  |                            | Single teach-in button         |
| <b>Special applications</b>        |                            | Hygienic and washdown zones    |
| <b>Housing design</b>              |                            | Hygiene                        |

<sup>1)</sup> Object with 90% remission (based on standard white, DIN 5033).

<sup>2)</sup> Average service life: 100,000 h at T<sub>J</sub> = +25 °C.

Safety-related parameters

|                                     |             |
|-------------------------------------|-------------|
| <b>MTTF<sub>D</sub></b>             | 1,186 years |
| <b>DC<sub>avg</sub></b>             | 0 %         |
| <b>T<sub>M</sub> (mission time)</b> | 20 years    |

## Electronics

|                                        |                                                       |
|----------------------------------------|-------------------------------------------------------|
| <b>Supply voltage <math>U_B</math></b> | 10 V DC ... 30 V DC <sup>1)</sup>                     |
| <b>Ripple</b>                          | < 5 V <sub>pp</sub> <sup>2)</sup>                     |
| <b>Current consumption</b>             | 30 mA <sup>3)</sup>                                   |
| <b>Protection class</b>                | III                                                   |
| <b>Digital output</b>                  |                                                       |
| Type                                   | PNP                                                   |
| Switching mode                         | Light/dark switching                                  |
| Output current I <sub>max.</sub>       | ≤ 100 mA                                              |
| Response time                          | < 0.5 ms <sup>4)</sup>                                |
| Switching frequency                    | 1,000 Hz <sup>5)</sup>                                |
| <b>Output function</b>                 | Complementary                                         |
| <b>Circuit protection</b>              | A <sup>6)</sup><br>B <sup>7)</sup><br>C <sup>8)</sup> |

<sup>1)</sup> Limit values, reverse-polarity protected, operation in short-circuit protected network: max. 8 A.

<sup>2)</sup> May not fall below or exceed U<sub>y</sub> tolerances.

<sup>3)</sup> Without load.

<sup>4)</sup> Signal transit time with resistive load.

<sup>5)</sup> With light/dark ratio 1:1.

<sup>6)</sup> A = V<sub>S</sub> connections reverse-polarity protected.

<sup>7)</sup> B = inputs and output reverse-polarity protected.

<sup>8)</sup> C = interference suppression.

## Mechanics

|                               |                                                      |
|-------------------------------|------------------------------------------------------|
| <b>Housing</b>                | Rectangular                                          |
| <b>Design detail</b>          | Slim                                                 |
| <b>Dimensions (W x H x D)</b> | 15.25 mm x 63.2 mm x 22.15 mm                        |
| <b>Connection</b>             | Cable with M8 male connector, 4-pin <sup>1) 2)</sup> |
| <b>Connection detail</b>      |                                                      |
| Length of cable (L)           | 150 mm <sup>2)</sup>                                 |
| <b>Material</b>               |                                                      |
| Housing                       | Metal, Stainless steel V4A (1.4404, 316L)            |
| Front screen                  | Plastic, PMMA                                        |
| Cable                         | Plastic, PVC                                         |
| <b>Weight</b>                 | 50 g                                                 |

<sup>1)</sup> Max. tightening torque: 0.6 Nm.

<sup>2)</sup> Do not bend below 0 °C.

## Ambient data

|                                      |                                 |
|--------------------------------------|---------------------------------|
| <b>Enclosure rating</b>              | IP66<br>IP67<br>IP68<br>IP69K   |
| <b>Ambient operating temperature</b> | -30 °C ... +70 °C <sup>1)</sup> |

<sup>1)</sup> At UV ≤ 24 V and IA < 30 mA.

|                                     |                                                  |
|-------------------------------------|--------------------------------------------------|
|                                     | -30 °C ... +60 °C                                |
| <b>Ambient temperature, storage</b> | -30 °C ... +75 °C                                |
| <b>UL File No.</b>                  | FDA, UL No. NRKH.E181493 & cUL No. NRKH7.E181493 |

<sup>1)</sup> At UV ≤ 24 V and IA < 30 mA.


## Certificates

|                                                          |   |
|----------------------------------------------------------|---|
| <b>EU declaration of conformity</b>                      | ✓ |
| <b>UK declaration of conformity</b>                      | ✓ |
| <b>ACMA declaration of conformity</b>                    | ✓ |
| <b>Moroccan declaration of conformity</b>                | ✓ |
| <b>China-RoHS</b>                                        | ✓ |
| <b>ECOLAB certificate</b>                                | ✓ |
| <b>cULus certificate</b>                                 | ✓ |
| <b>Photobiological safety (DIN EN 62471) certificate</b> | ✓ |


## Classifications

|                       |          |
|-----------------------|----------|
| <b>ECLASS 5.0</b>     | 27270904 |
| <b>ECLASS 5.1.4</b>   | 27270904 |
| <b>ECLASS 6.0</b>     | 27270904 |
| <b>ECLASS 6.2</b>     | 27270904 |
| <b>ECLASS 7.0</b>     | 27270904 |
| <b>ECLASS 8.0</b>     | 27270904 |
| <b>ECLASS 8.1</b>     | 27270904 |
| <b>ECLASS 9.0</b>     | 27270904 |
| <b>ECLASS 10.0</b>    | 27270904 |
| <b>ECLASS 11.0</b>    | 27270904 |
| <b>ECLASS 12.0</b>    | 27270903 |
| <b>ETIM 5.0</b>       | EC002719 |
| <b>ETIM 6.0</b>       | EC002719 |
| <b>ETIM 7.0</b>       | EC002719 |
| <b>ETIM 8.0</b>       | EC002719 |
| <b>UNSPSC 16.0901</b> | 39121528 |


## Connection type



Connection diagram Cd-083




Characteristic curve WTB4S-3, 500 mm



- ① Sensing range on black, 6% remission factor  
② Sensing range on gray, 18% remission factor  
③ Sensing range on white, 90% remission factor


Sensing range diagram WTB4S-3, 500 mm



■ Sensing range    ■ Sensing range max.

- ① Sensing range on black, 6% remission factor  
② Sensing range on gray, 18% remission factor  
③ Sensing range on white, 90% remission factor

Dimensional drawing WTB4S-3H, WTF4S-3H, with single teach-in button



- Dimensions in mm (inch)
- ① Center of optical axis, receiver
  - ② Center of optical axis, sender
  - ③ Sealing ring (tightening torque 6 Nm)
  - ④ Connector M12
  - ⑤ LED indicator yellow: Status of received light beam
  - ⑥ LED indicator green: Supply voltage active
  - ⑦ Teach-in button

Recommended accessories

Other models and accessories → [www.sick.com/W4](http://www.sick.com/W4)

|                                                                                     | Brief description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Type            | part no. |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------|
| connectors and cables                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                 |          |
|  | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Female connector, M8, 4-pin, straight</li><li>• <b>Connection type head B:</b> Flying leads</li><li>• <b>Signal type:</b> Sensor/actuator cable</li><li>• <b>Cable:</b> 5 m, 4-wire, PVC</li><li>• <b>Description:</b> Sensor/actuator cable, unshielded</li><li>• <b>Connection systems:</b> Flying leads</li><li>• <b>Note:</b> This product is generally resistant to chemical cleaning agents (see ECOLAB). Please do not use cleaning agents of any other Kind., Not resistant against lactic acid &amp; hydrogen peroxide (H2O2)</li><li>• <b>Application:</b> Hygienic and washdown zones</li></ul> | DOL-0804-G05MNI | 6059194  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)