



## NBG633

- for application in food producing machinery
- Enclosure seal for food machinery
- Stainless steel enclosure

## Data

### Ordering data

|                               |               |
|-------------------------------|---------------|
| Product type description      | NBG633        |
| Article number (order number) | 101180083     |
| EAN (European Article Number) | 4250116201723 |
| eCl@ss number, version 9.0    | 27-37-12-05   |
| eCl@ss number, version 11.0   | 27-37-12-05   |
| eCl@ss number, version 12.0   | 27-37-12-05   |
| ETIM number, version 7.0      | EC000200      |
| ETIM number, version 6.0      | EC000200      |

### Approvals - Standards

|              |    |
|--------------|----|
| Certificates | BG |
|--------------|----|

### General data

|                                            |                       |
|--------------------------------------------|-----------------------|
| Enclosure material                         | Stainless steel (V4A) |
| Colour of the bottom part of the enclosure | Silver                |
| Colour of the sealing                      | Grey                  |
| Gross weight                               | 1,250 g               |

## General data - Features

|                             |   |
|-----------------------------|---|
| Number of cable glands      | 1 |
| Number of command positions | 3 |

## Mechanical data

|                             |                |
|-----------------------------|----------------|
| Position of the cable gland | mounting holes |
|-----------------------------|----------------|

## Mechanical data - Connection technique

|                             |         |
|-----------------------------|---------|
| Diameter of the cable gland | 20.3 mm |
|-----------------------------|---------|

## Mechanical data - Dimensions

|                                 |         |
|---------------------------------|---------|
| Width                           | 110 mm  |
| Height                          | 86.5 mm |
| Depth                           | 204 mm  |
| Middle spacing of drilled holes | 60 mm   |

## Ambient conditions

|                              |               |
|------------------------------|---------------|
| Degree of protection         | IP67<br>IP69K |
| Ambient temperature, minimum | -25 °C        |
| Ambient temperature, maximum | +80 °C        |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 10:08