



ZV1H 235-11Z-M20

- Snap action with constant contact pressure up to switching point
- 1 Cable entry M 20 x 1.5
- Metal enclosure
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- 30 mm x 63,5 mm x 30 mm
- Actuator heads can be repositioned by 4 x 90°
- Mounting details to EN 50047
- Lever angle adjustable in 10° steps

Data

Ordering data

Product type description	ZV1H 235-11Z-M20
Article number (order number)	151169330

Approvals - Standards

Certificates	cULus CCC EAC
--------------	---------------------

General data

Standards	BG-GS-ET-15 EN ISO 13849-1 EN IEC 60947-5-1
Housing construction form	Norm construction design
Actuator type to DIN EN 50047	A
Enclosure material	Metal, zinc die-cast
Material of the contacts, electrical	Silver

Lever material	Plastic
----------------	---------

Gross weight	212 g
--------------	-------

General data - Features

Safety functions	Yes
------------------	-----

Number of auxiliary contacts	1
------------------------------	---

Number of safety contacts	1
---------------------------	---

Safety classification

Standards	EN ISO 13849-1
-----------	----------------

Mission time	20 Year(s)
--------------	------------

Safety classification - Safety outputs

B _{10D} Normally-closed contact (NC)	20,000,000 Operations
---	-----------------------

Mechanical data

Actuating element	Roller lever
-------------------	--------------

Roller material	Plastic
-----------------	---------

Mechanical life, minimum	20,000,000 Operations
--------------------------	-----------------------

Actuating speed, minimum	92 mm/min
--------------------------	-----------

Actuating speed, maximum	1 m/s
--------------------------	-------

Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
------------------------	---

Actuating torque, minimum	0.2 Nm
---------------------------	--------

Positive break torque	0.2 Nm
-----------------------	--------

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
-------------	---------------------------

Cable section, minimum	0.75 mm ²
------------------------	----------------------

Cable section, maximum	2.5 mm ²
------------------------	---------------------

Mechanical data - Dimensions

Length of sensor	42.5 mm
Width of sensor	30 mm
Height of sensor	111 mm

Ambient conditions

Degree of protection	IP67 IP65
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation values

Rated insulation voltage U_i	500 V
Rated impulse withstand voltage U_{imp}	6 kV

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	NO contact, NC contact
Switching principle	Snap action
Bounce duration, maximum	3 ms
Switching frequency	5,000 /h
Switchover time, maximum	5.5 ms

