



NBGLC54.3/NSK

- Stainless steel enclosure
- for application in food producing machinery
- Protection class IP69K
- Variable sizes with up to five holes for command devices
- No additional mounting accessories such as spacers required thanks to flange seal under the enclosure

Data

Ordering data

| | |
|-------------------------------|---------------|
| Product type description | NBGLC54.3/NSK |
| Article number (order number) | 103032727 |
| EAN (European Article Number) | 4030661530222 |
| eCl@ss number, version 9.0 | 27-37-12-05 |
| eCl@ss number, version 11.0 | 27-37-12-05 |
| eCl@ss number, version 12.0 | 27-37-12-05 |
| ETIM number, version 7.0 | EC000200 |
| ETIM number, version 6.0 | EC000200 |

General data

| | |
|--|-----------------|
| Enclosure material | Stainless steel |
| Colour of the bottom part of the enclosure | Silver |
| Colour of the sealing | Blue |
| Gross weight | 2,130 g |

General data - Features

| | |
|------------------------|---|
| Number of cable glands | 2 |
|------------------------|---|

Mechanical data

| | |
|-----------------------------|----------------|
| Position of the cable gland | mounting holes |
|-----------------------------|----------------|

Mechanical data - Connection technique

| | |
|-----------------------------|---------|
| Diameter of the cable gland | 20.3 mm |
|-----------------------------|---------|

Mechanical data - Dimensions

| | |
|--------|--------|
| Width | 100 mm |
| Height | 94 mm |
| Depth | 315 mm |

Ambient conditions

| | |
|------------------------------|---------------|
| Degree of protection | IP67 IP69K |
| Ambient temperature, minimum | -25 °C |
| Ambient temperature, maximum | +80 °C |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 10:07