



BDF200-FB-B-DTBK-LTYE-LMGN

- integrated FB interface for connection to the Safety-Field-Box SFB
- Pos 1: Blanking plug
- Pos 2: BLACK pushbutton
- Pos 3: YELLOW illuminated pushbutton
- Pos 4: GREEN signal light
- slender shock-proof thermoplastic enclosure
- to be installed at an ergonomic favourable position
- to be fitted to commercial-off-the-shelf aluminium profiles
- E-STOP with electronic OSSDs

Data

Ordering data

Product type description	BDF200-FB-B-DTBK-LTYE-LMGN
Article number (order number)	103037792
EAN (European Article Number)	4030661543550
eCl@ss number, version 9.0	27-37-12-16
eCl@ss number, version 11.0	27-37-12-16
eCl@ss number, version 12.0	27-37-12-16
ETIM number, version 7.0	EC000225
ETIM number, version 6.0	EC000225

General data

Standards	EN IEC 60947-5-1 EN ISO 13849-1 EN IEC 61508 EN IEC 60947-5-5 EN ISO 13850
Climatic stress	IEC 60947-5-5

Terminal (mechanical)	Connector plug M12, 8-pole, A-coded
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	280 g
Reaction time, maximum	50 ms
Duration of risk, maximum	100 ms
Positions used, position 1	blanking plug
Positions used, position 2	Pushbutton, black
Positions used, position 3	Illuminated pushbutton, yellow
Positions used, position 4	Indicator light, green

General data - Features

Serial diagnostics	No
Field box interface	YN_FIELDBOX_INTERFACE1
Indicator lamp	No
Safety functions	Yes

Safety classification

Standards	EN ISO 13849-1 EN IEC 61508
Performance Level, up to	e
Category to EN ISO 13849	4
PFH value	2.89×10^{-10} /h
Note (PFH-value)	up to max. 5,000 switching cycles/year
Safety Integrity Level (SIL), suitable for applications in	3
Mission time	20 Year(s)

Mechanical data

Mechanical life, Emergency-Stop button	100,000 Operations
--	--------------------

Mechanical life, Command devices

1,000,000 Operations

Mechanical data - Dimensions

Width	40 mm
Height	69 mm
Length x Width x Height	Depth: 233.5 - 252.5 mm (without and with indicator lamp)

Ambient conditions

Degree of protection	IP64
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+65 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+85 °C
Resistance to vibration to EN 60068-2-6	10 ... 150 Hz, amplitude 0.35 mm / 5 g
Resistance to shock	30 g / 11 ms
Protection class	III

Ambient conditions - Insulation values

Rated insulation voltage U_i	32 VDC
Rated impulse withstand voltage U_{imp}	0.8 kV
Overvoltage category	III
Degree of pollution to VDE 0100	3

Electrical data

Current consumption at 24V	5 mA
No-load supply current I_0 , maximum	35 mA
Rated operating voltage	24 VDC -15 % / +10 % (PELV to IEC 60204-1)
Operating current	150 mA 600 mA

Required rated short-circuit current to EN 60947-5-1	100 A
Utilisation category DC-12	24 VDC
Utilisation category DC-12	0.25 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	0.25 A
Inputs, Switching thresholds	–3 V ... 5 V (Low) 15 V ... 30 V (High)

Electrical data - Safety digital outputs

Rated operating current (safety outputs)	250 mA
Design of control elements	short-circuit proof, p-type
Voltage drop U_d , maximum	1 V
Leakage current I_r , maximum	0.5 mA

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 08:10