



NK-T-22-2ST8-2

- Spring-return joystick switches
- Mounting hole 22.3 mm
- Mounting Knurled nut
- up to 6 mm front plate thickness
- Suitable for food processing industry

Data

Ordering data

Product type description	NK-T-22-2ST8-2
Article number (order number)	103012434
EAN (European Article Number)	4030661490298
eCl@ss number, version 9.0	27-37-14-04
eCl@ss number, version 11.0	27-37-14-04
eCl@ss number, version 12.0	27-37-14-04
ETIM number, version 7.0	EC000632
ETIM number, version 6.0	EC000632

Approvals - Standards

Certificates	BG cULus
--------------	-------------

General data

Standards	EN IEC 60947-5-1 EN IEC 62061 EN IEC 60947-5-3 EN IEC 60947-5-5 EN IEC 60204-1 EN IEC 60947-1
Installation conditions (mechanical)	arbitrarily
Material of the operators	Plastic
Material of the front ring	Plastic
Material of the bellows	Silicone
Material thickness of the sealing bellows	1.5 mm
Colour of the front ring	Black
Colour of the bellows	Blue
Gross weight	160 g

General data - Features

Return to zero position	Yes
Sealing element, additional	Yes
External applications	Yes
Probing possible	Yes
Number of directions	2
Number of the touch position	2
Note (Touch positions)	Position A, B
Number of mechanical terminals	2

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Mechanical life, Touch position (for each position)	500,000 Operations
switching angle	20 °
Actuating force, approx.	11 N
Mounting	central nut SW41

Mechanical data - Connection technique

Termination

Connector M12, 8-pole

Mechanical data - Dimensions

Mounting depth	30 mm
Note (Mounting depth)	Plus connectors
Length of the actuator	85 mm
Diameter hole	22.3 mm
Diameter hole, central mounting	22.7 mm
Thickness, of the front panel, minimum	1.5 mm
Thickness of the front panel, maximum	6 mm
Diameter for the Installation to IEC/EN 60947-1	22.3 + 0.4 mm
Spacing	90 x 90 mm

Ambient conditions

Degree of protection of the contact element	IP67
Degree of protection of the front panel	IP67 IP69
Ambient temperature, minimum	-40 °C
Ambient temperature, maximum	+80 °C
Resistance to shock	30 g / 11 ms

Ambient conditions - Insulation values

Rated insulation voltage U_i	30 V
Rated impulse withstand voltage U_{imp}	0.5 kV
Degree of pollution to VDE 0100	2

Electrical data

Operating current	300 mA
Utilisation category DC-12	30 VDC
Utilisation category DC-12	0.3 A

Switching capacity, maximum	7.2 W
Switching principle	Reed contacts, Non-contact principle
Switching frequency	1,200 /h

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 10:13