



## RMEHWS

- high calotte
- integrated multi-LED, extra bright in device head

## Data

### Ordering data

|                               |               |
|-------------------------------|---------------|
| Product type description      | RMEHWS        |
| Article number (order number) | 101195068     |
| EAN (European Article Number) | 4030661601670 |
| eCl@ss number, version 9.0    | 27-37-12-11   |
| eCl@ss number, version 11.0   | 27-37-12-11   |
| eCl@ss number, version 12.0   | 27-37-12-11   |
| ETIM number, version 7.0      | EC000223      |
| ETIM number, version 6.0      | EC000223      |

### General data

|                                      |                                                                                                              |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Standards                            | EN IEC 60947-1<br>EN IEC 62061<br>EN IEC 60947-5-1<br>EN IEC 60947-5-3<br>EN IEC 60947-5-5<br>EN IEC 60204-1 |
| Versions                             | LED - Indicator light - Front plate mounting                                                                 |
| Design                               | Round<br>High calotte                                                                                        |
| Installation conditions (mechanical) | arbitrarily                                                                                                  |

|                            |                                       |
|----------------------------|---------------------------------------|
| Sealing type               | Membrane<br>Lip gaskets<br>Form seals |
| Material of the dome       | Plastic                               |
| Material of the front ring | Aluminium                             |
| Colour of the dome         | White                                 |
| Colour of the front ring   | Silver                                |
| Gross weight               | 50 g                                  |

### General data - Features

|                                      |     |
|--------------------------------------|-----|
| Illuminable                          | Yes |
| Mounting flange                      | Yes |
| Fully insulated                      | Yes |
| Integral system diagnostics, general | Yes |

### Mechanical data

|                                |                     |
|--------------------------------|---------------------|
| Mounting                       | Mounting flange ELM |
| Tightening torque of the screw | 0.6 Nm              |

### Mechanical data - Dimensions

|                                          |               |
|------------------------------------------|---------------|
| Diameter total                           | 39.5 mm       |
| Height of the dome                       | 11 mm         |
| Diameter of the dome                     | 25 mm         |
| Diameter of the front ring               | 39.5 mm       |
| Diameter hole                            | 22.3 mm       |
| Diameter hole, with tolerance indication | 22.3 + 0.4 mm |
| Thickness, of the front panel, minimum   | 1 mm          |
| Thickness of the front panel, maximum    | 6 mm          |
| Spacing                                  | 40 x 50 mm    |

### Ambient conditions

|                              |        |
|------------------------------|--------|
| Degree of protection         | IP65   |
| Ambient temperature, minimum | -25 °C |
| Ambient temperature, maximum | +75 °C |

## Status indication

Note (Integral System Diagnostics, status ) for 24 VAC/DC

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 09:32