



ADP55.3SW

Data

Ordering data

Product type description	ADP55.3SW
Article number (order number)	101054132
EAN (European Article Number)	4030661605951
eCl@ss number, version 9.0	27-37-12-12
eCl@ss number, version 11.0	27-37-12-12
eCl@ss number, version 12.0	27-37-12-12
ETIM number, version 7.0	EC001038
ETIM number, version 6.0	EC001038

General data

Standards	EN IEC 60947-1 EN IEC 62061 EN IEC 60947-5-1 EN IEC 60947-5-3 EN IEC 60947-5-5 EN IEC 60204-1
Versions	Latched pushbutton - Front plate mounting
Design	Round
Sealing type	Form seals
Material of the operators	Plastic

Material of the front ring	Plastic
Colour of the operating element	Black
Colour of the front ring	Black
Gross weight	30 g

General data - Features

Mounting flange	No
Probing possible	Yes
Fully insulated	Yes

Mechanical data

Unlocking	without
Actuating stroke	4 mm
Actuating force, approx.	10.5 N
Mounting	central nut
Tightening torque of the screw	1 Nm

Mechanical data - Dimensions

Height	36 mm
Diameter total	55 mm
diameters for the actuating heads	55 mm
Diameter of the front ring	49 mm
Diameter hole	22.3 mm
Diameter hole, with tolerance indication	22,3 + 0,4 mm
Thickness, of the front panel, minimum	1 mm
Thickness of the front panel, maximum	6 mm
Spacing	70 x 70 mm

Ambient conditions

Degree of protection	IP65
----------------------	------

Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C
Restistance to shock	50 g

Electrical data

Switching frequency	1,200 /h
---------------------	----------

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 10:01